

Type	D1	Type	D2	Type	D3	Type	D4	Type	D5
Location Room	T01	Location Room	T02	Location Room	T03	Location Room	T04	Location Room	G01
Frame	3mm thick galvanised steel double rebate frame to fit 220mm wide brick wall plastered both sides as supplied with door with all necessary building in lugs, etc. Frame to be prepared, primed, undercoated and painted with a polyurethane enamel paint in accordance with paint manufacturers recommendations to an even and consistent finish.	Pressed steel double rebate door frame to SANS 1129 to fit 110mm brick wall plastered both sides manufactured from 1.2mm mild steel sheet to sizes shown above and in accordance with SANS 1129. Provision for adjustable striking plate midpoint of one jamb. Frame to be hot dipped galvanised to SANS 121. Prepare, undercoat and paint with a polyurethane enamel in accordance with the paint manufacturers recommendations to an even and consistent finish.	Pressed steel double rebate door frame to SANS 1129 to fit 220mm brick wall plastered both sides manufactured from 1.2mm mild steel sheet to sizes shown above and in accordance with SANS 1129. Provision for adjustable striking plate midpoint of one jamb. Frame to be hot dipped galvanised to SANS 121. Prepare, undercoat and paint with a polyurethane enamel in accordance with the paint manufacturers recommendations to an even and consistent finish.	1200mm x 2032mm silicon industries or similar approved class 4 fire single door 30mm fire rating constructed from solid wood & steel clad on both sides and all edges with 16mm pre galvanised steel leading edge to be supplied fitted with stainless steel storm bar by manufacturer door seals to be fitted to prevent air leakage	Pressed steel double rebate door frame to SANS 1129 to fit 220mm brick wall plastered both sides manufactured from 1.2mm mild steel sheet to sizes shown above and in accordance with SANS 1129. Provision for door latch on transom. Frame to be hot dipped galvanised to SANS 121. Prepare, undercoat and paint with a polyurethane enamel in accordance with the paint manufacturers recommendations to an even and consistent finish.	1800mm x 2032mm silicon industries or similar approved class 4 fire double doors with 30mm fire rating constructed from solid wood & steel clad on both sides and all edges with 16mm pre galvanised steel door seals to be fitted to prevent air leakage	1800mm x 2032mm silicon industries or similar approved class 4 fire double doors with 30mm fire rating constructed from solid wood & steel clad on both sides and all edges with 16mm pre galvanised steel door seals to be fitted to prevent air leakage	1800mm x 2032mm silicon industries or similar approved class 4 fire double doors with 30mm fire rating constructed from solid wood & steel clad on both sides and all edges with 16mm pre galvanised steel door seals to be fitted to prevent air leakage	Galvanised steel angle frame with screw fixed galvanised steel channel center mullion and with galvanised building in cleats for brick walls.
Door	813 x 2032 x 450mm x 110kg/m ² external exposure heavy duty R4 rifle metal jacket bullet resistant door tested to SANS 1658 . Door faces to be veneer plywood suitable for painting with stainless steel channel edge all round door. Prepare, undercoat and paint with a polyurethane enamel in accordance with the paint manufacturers recommendations to an even and consistent finish.	813 x 2032 x 40mm heavy duty dry interior exposure class 4 door to SANS 545. Solid laminated kiln dried softwood (pine) core with 4mm thick hardwood cross banding & hardwood veneer face suitable for painting. Prepare, undercoat and paint with a polyurethane enamel in accordance with the paint manufacturers recommendations to an even and consistent finish.	813 x 2032 x 40mm heavy duty dry interior exposure class 4 door to SANS 545. Solid laminated kiln dried softwood (pine) core with 4mm thick hardwood cross banding & hardwood veneer face suitable for painting. Prepare, undercoat and paint with a polyurethane enamel in accordance with the paint manufacturers recommendations to an even and consistent finish.	1200mm x 2032mm silicon industries or similar approved class 4 fire single door 30mm fire rating constructed from solid wood & steel clad on both sides and all edges with 16mm pre galvanised steel leading edge to be supplied fitted with stainless steel storm bar by manufacturer door seals to be fitted to prevent air leakage	1800mm x 2032mm silicon industries or similar approved class 4 fire double doors with 30mm fire rating constructed from solid wood & steel clad on both sides and all edges with 16mm pre galvanised steel door seals to be fitted to prevent air leakage	1800mm x 2032mm silicon industries or similar approved class 4 fire double doors with 30mm fire rating constructed from solid wood & steel clad on both sides and all edges with 16mm pre galvanised steel door seals to be fitted to prevent air leakage	1800mm x 2032mm silicon industries or similar approved class 4 fire double doors with 30mm fire rating constructed from solid wood & steel clad on both sides and all edges with 16mm pre galvanised steel door seals to be fitted to prevent air leakage	1964 x 1940 x 44 double skinned galvanised steel door leafs with rockwool insulation. Additional acoustic insulation to be fixed to inside of door. Rubber oil seal between door leafs and frame	
Farlight	nil	Farlight	nil	Farlight	nil	Farlight	nil	Farlight	nil
Glazing	nil	Glazing	nil	Glazing	nil	Glazing	nil	Glazing	nil
Hinges	Continuous heavy duty steel gear hinge as supplied by door manufacturer to full height of hinge reveal.	Hinges	One and a half pairs 100mm steel butt hinges for door leaf supplied with and welded to door frame.	Hinges	One and a half pairs Union Security hinges 8352-100/25P for door leaf supplied with and welded to door frame.	Hinges	Three pairs Union Security hinges 8352-100/25P supplied with and welded to door frame or similar approved by architect	Hinges	2 pairs steel bullet hinges to detail
Ironmongery	Lock – Commercial grade dead lock with stainless steel forend as per Union L-2109-7855 with knob cylinder barrel as per Union 2X195C with stainless steel hidden firing escutcheons as per Union SS5305-05S5 (see note 2) Pull Handle – 1 pair back to back firing 300mm long aluminium bow handles as per Union Dove AL5015-300B8AS (see note 3) Stainless steel side cover strip for full height of lock reveal fixed to door and to fully cover gap between door and frame.	Lock – Commercial grade dead lock with stainless steel forend as per Union L-2109-7855 with knob cylinder barrel as per Union 2X195C with stainless steel hidden firing escutcheons as per Union SS5305-05S5 (see note 2) Indicator ball – Latch with extended handle to inside and backing plate to outside with WC occupied indicator of specially designed for the disabled as per Union Helping Hand Indicator Ball reference 37651 Pull Handle – 1 pair (back to back and 2 bolt through fixings) 300mm long aluminium bow handles as per Union Dove AL5015-300 (BB-287)AS (see note 3)	Lock – Commercial grade dead lock with stainless steel forend as per Union L-2109-7855 with knob cylinder barrel as per Union 2X195C with stainless steel hidden firing escutcheons as per Union SS5305-05S5 (see note 2) Indicator ball – Latch with extended handle to inside and backing plate to outside with WC occupied indicator of specially designed for the disabled as per Union Helping Hand Indicator Ball reference 37651 Pull Handle – 1 pair (back to back and 2 bolt through fixings) 300mm long aluminium bow handles as per Union Dove AL5015-300 (BB-287)AS (see note 3)	Lock – Strong ball Euro Cylinder Deadlock Stainless Steel with Red Case YL21EUS-SS-30 with Euro profile single cylinder 2x205C with stainless steel hidden firing escutcheons as per Union SS5305-05S5 (see note 2) Pull Handle – 1 pair back to back firing 300mm long aluminium bow handles as per Union Dove AL5015-300B8AS (see note 3) Stainless steel side cover strip for full height of lock reveal fixed to door and to fully cover gap between door and frame.	Lock – Strong ball Euro Cylinder Deadlock Stainless Steel with Red Case YL21EUS-SS-30 with Euro profile single cylinder 2x205C with stainless steel hidden firing escutcheons as per Union SS5305-05S5 (see note 2) Pull Handle – 1 pair back to back firing 300mm long aluminium bow handles as per Union Dove AL5015-300B8AS (see note 3) Two of HD galvanised Barrel bolt/pad bolt 200mm fixed with coach bolts	Lock – Strong ball Euro Cylinder Deadlock Stainless Steel with Red Case YL21EUS-SS-30 with Euro profile single cylinder 2x205C with stainless steel hidden firing escutcheons as per Union SS5305-05S5 (see note 2) Pull Handle – 1 pair back to back firing 300mm long aluminium bow handles as per Union Dove AL5015-300B8AS (see note 3) Two of HD galvanised Barrel bolt/pad bolt 200mm fixed with coach bolts	Lock – Strong ball Euro Cylinder Deadlock Stainless Steel with Red Case YL21EUS-SS-30 with Euro profile single cylinder 2x205C with stainless steel hidden firing escutcheons as per Union SS5305-05S5 (see note 2) Pull Handle – 1 pair back to back firing 300mm long aluminium bow handles as per Union Dove AL5015-300B8AS (see note 3) Two of HD galvanised Barrel bolt/pad bolt 200mm fixed with coach bolts	Double lever locking handles as supplied with door (two pieces per door) in die-cast aluminium enabling operation from both sides. Two number cylinder rim night latches as per Union 102202 or other approved keyed alike	
Notes	1) All commercial product names are specified for clarity and may be substituted with equal and approved alternatives 2) Door locks, handles, etc to match ironmongery used on other doors. 3) Pull handles to match pull handles used elsewhere.	1) All commercial product names are specified for clarity and may be substituted with equal and approved alternatives 2) Door locks, handles, etc to match ironmongery used on other doors. 3) Pull handles to match pull handles used elsewhere.	1) All commercial product names are specified for clarity and may be substituted with equal and approved alternatives 2) Door locks, handles, etc to match ironmongery used on other doors. 3) Pull handles to match pull handles used elsewhere.	1) All commercial product names are specified for clarity and may be substituted with equal and approved alternatives 2) Door locks, handles, etc to match ironmongery used on other doors. 3) Pull handles to match pull handles used elsewhere.	1) All commercial product names are specified for clarity and may be substituted with equal and approved alternatives 2) Door locks, handles, etc to match ironmongery used on other doors. 3) Pull handles to match pull handles used elsewhere.	1) All commercial product names are specified for clarity and may be substituted with equal and approved alternatives 2) Door locks, handles, etc to match ironmongery used on other doors. 3) Pull handles to match pull handles used elsewhere.	1) All commercial product names are specified for clarity and may be substituted with equal and approved alternatives 2) Door locks, handles, etc to match ironmongery used on other doors. 3) Pull handles to match pull handles used elsewhere.	1) All commercial product names are specified for clarity and may be substituted with equal and approved alternatives 2) Door locks, handles, etc to match ironmongery used on other doors. 3) Pull handles to match pull handles used elsewhere.	
DOOR SCHEDULE DOOR TYPE D1		DOOR SCHEDULE DOOR TYPE D2		DOOR SCHEDULE DOOR TYPE D3		DOOR SCHEDULE DOOR TYPE D4		DOOR SCHEDULE DOOR TYPE D5	
500 - 01		500 - 02		500 - 03		500 - 04		500 - 05	

DOOR SCHEDULES (Scale 1 : 50)

Type	D6	Type	D7	Type	D8	Type	W1	Type	W2
Reference	S01	Reference	S02	Reference	S03, 04, 05, 06	Reference	T01	Reference	T01
Frame	Nil – Galvanised steel door guides fixed to wall and RIG head member erected by others as part of steel frame.	2x370mm high x 4x270 to 4x800 wide aluminium frame to door and side lights to fit steel portal frame and sloped concrete floor.	2x370mm high x 4x270 to 4x800 wide aluminium frame to door and side lights to fit steel portal frame and sloped concrete floor.	Nil (Opening formed in side cladding glazing)	2 number 600mm wide x 2250 door all height fully welded aluminium frame to slope to match surrounding glazing with all necessary seals, bump stop, guides, etc. Finished frame to be powder coated or other approved finish to match glazing system.	Nil (Opening formed in side cladding glazing)	1175 x 1180 with standard SECURITY WINDOW FRAME configuration to accommodate 38mm bullet resistant glazing complete with lugs for building into a brick wall as per TAC details or similar approved by the architect	1175 x 1180 with standard SECURITY WINDOW FRAME configuration to accommodate 38mm bullet resistant glazing complete with lugs for building into a brick wall as per TAC details or similar approved by the architect	1175 x 1180 with standard SECURITY WINDOW FRAME configuration to accommodate 38mm bullet resistant glazing complete with lugs for building into a brick wall as per TAC details or similar approved by the architect
Door	3980 x 42370mm automatic aluminium door consisting of "fenestra" or punched slots as per Trellidor R540 punched or other approved.	2100 x 42370mm Aluminium framed door	2100 x 42370mm Aluminium framed door	6,3mm laminated safety glass of 55% to 65% solar transmission or 8% to 12% solar reflectance as specified. (glazing differs on each side depending on station orientation)	6,3mm laminated safety glass of 55% to 65% solar transmission or 8% to 12% solar reflectance as specified. (glazing differs on each side depending on station orientation)	6,3mm laminated safety glass of 55% to 65% solar transmission or 8% to 12% solar reflectance as specified. (glazing differs on each side depending on station orientation)	38mm clear bullet resistant glass with predrilled holes & stainless steel cover plate as per TAC specifications or similar approved by the architect	38mm clear bullet resistant glass with predrilled holes & stainless steel cover plate as per TAC specifications or similar approved by the architect	38mm clear bullet resistant glass with predrilled holes & stainless steel cover plate as per TAC specifications or similar approved by the architect
Farlight	nil (open over)	Farlight	nil	Farlight	nil	Farlight	nil	Farlight	nil
Glazing	nil (see fenestra)	Glazing	6,3mm laminated safety glass of 55% to 65% solar transmission or 8% to 12% solar reflectance as specified.	Glazing	6,3mm laminated safety glass of 55% to 65% solar transmission or 8% to 12% solar reflectance as specified.	Glazing	6,3mm laminated safety glass of 55% to 65% solar transmission or 8% to 12% solar reflectance as specified.	Glazing	6,3mm laminated safety glass of 55% to 65% solar transmission or 8% to 12% solar reflectance as specified.
Hinges	nil	Hinges	Three pairs 100mm washed aluminium butt hinges.	Hinges	Three pairs 100mm washed aluminium butt hinges.	Hinges	Three pairs 100mm washed aluminium butt hinges.	Hinges	Three pairs 100mm washed aluminium butt hinges.
Ironmongery	Lock –	Ironmongery	Escape Hardware – Aluminium horizontal touch bar with 3 point locking for double rebated door as per Union J-8537-W-SL or other approved.	Ironmongery	Escape Hardware – Aluminium horizontal touch bar with 3 point locking for double rebated door as per Union J-8537-W-SL or other approved.	Ironmongery	Escape Hardware – Aluminium horizontal touch bar with 3 point locking for double rebated door as per Union J-8537-W-SL or other approved.	Ironmongery	Escape Hardware – Aluminium horizontal touch bar with 3 point locking for double rebated door as per Union J-8537-W-SL or other approved.
Notes	1) All commercial product names are specified for clarity and may be substituted with equal and approved alternatives	Notes	1) All commercial product names are specified for clarity and may be substituted with equal and approved alternatives 2) Door locks, handles, etc to match ironmongery used on other doors. 3) Fabrication to be in accordance with AAMSA	Notes	1) All commercial product names are specified for clarity and may be substituted with equal and approved alternatives 2) Door locks, handles, etc to match ironmongery used on other doors. 3) Fabrication to be in accordance with AAMSA	Notes	1) All commercial product names are specified for clarity and may be substituted with equal and approved alternatives 2) Door locks, handles, etc to match ironmongery used on other doors. 3) Fabrication to be in accordance with AAMSA	Notes	1) All commercial product names are specified for clarity and may be substituted with equal and approved alternatives 2) Door locks, handles, etc to match ironmongery used on other doors. 3) Fabrication to be in accordance with AAMSA
DOOR SCHEDULE DOOR TYPE D6		DOOR SCHEDULE DOOR TYPE D7		DOOR SCHEDULE DOOR TYPE D8		WINDOW SCHEDULE WINDOW TYPE W1		WINDOW SCHEDULE WINDOW TYPE W2	
500 - 06		500 - 07		500 - 08		500 - 09		500 - 10	

DOOR SCHEDULES (Scale 1 : 50)

Sanitaryware Specifications Water Closets - Toilets - WC's WC 1 - Disabled Toilet Wall hung WC pan manufactured from grade 304 stainless steel satin surface finished size 360 x 700 x 350mm. Unit to be a back entry and have a P trap. Unit to be fixed with 3mm thick stainless steel wall fixing brackets and fitted in accordance with manufacturers specifications including all necessary fixings, bolts, etc. Compliant with SANS 1733:1998 and SANS 497:1991. WC pan to flush with 4 and 6 litres of water. Pan to withstand point load of 400kg as per international standards. All as per Franke Model CAP6204 or other equal and approved. Black vandal resistant soft close seat and closing flap as per Estoma or other equal and approved. Concealed cistern mounted in duct with push button operation and spang pipe and connecting to back entry to toilet pan as per Gilbert Korbfiller UP172 or other equal and approved. Wash Hand Basins WHB 1 - Disabled Toilet Oval grade 304 x 1,2mm stainless steel wash hand basins satin surface finished, size 420 x 340 x 185mm deep. Unit to include a one piece pressed bowl, size 360 x 280 x 130mm deep with a 40mm waste outlet, with a 50mm splashback and 1000mm radius apron. Basin supplied and fixed with all necessary brackets, bolts, etc. All as per Franke Oval A or other equal and approved. Chrome plated bottle traps as per Cobra 365/50 or other approved connected to 50 diameter PVC waste pipe. One number chrome plated elbow action medical pillar tap as per Cobra 503-21B or other approved. Chrome plated angled regulating valve as per Cobra 232-10 and stainless steel braided service pipe connection to tap. Basin to be sealed all round to wall surface with a mould resistant white silicon sealant. Mirrors Mirror 1 - Disabled Toilet 420 x 900 x 4mm float glass silvered mirrors with bevelled edges and protective rear fixed to substrate with minimum 8 strips of 30mm long double sided mirror adhesive tape.		Sanitaryware Specifications Fittings 2 Toilet Roll Holder - Vandal resistant Toilet roll holder stainless steel grade 304 x 1,5mm satin surface finished for surface mounting with inspection window and lockable access cover. Holder to have spindle system for 2 standard toilet rolls with max. 120 mm Ø. second roll will be released after consumption of first roll, reserve roll not to be visible. All necessary fixings to be included. All as per Franke STRX 672 or other equal and approved. Grab Rail Dogs Leg Grab Rail - 300 x 300 x 300mm long x 32mm diameter grade 304 stainless steel satin polished "dogs leg" grab rail with minimum 75mm clearance to wall and fixed to wall with minimum 3x4mm diameter wall anchors per end hidden under tamper resistant cover plates. As per Franke CNTX21N or other approved Grab Rail U Shaped 750mm long x 90 x 32mm diameter grade 304 stainless steel grab rail finished grab rail fixed to wall with 3 stainless steel fixed to wall with minimum 3x4mm diameter wall anchors per end hidden under tamper resistant cover plates. As per Franke CNTX750N or other approved Electric Hand Drier Sensor operated hand dryer for wall mounting manufactured from Grade 304 x 1,2mm stainless steel, brushed finish including all mounting brackets and fittings as well as all required electrical connections. All as per Jetstream Airtronic or similar approved.		Sanitaryware Specifications Fittings 2 Toilet Roll Holder - Vandal resistant Toilet roll holder stainless steel grade 304 x 1,5mm satin surface finished for surface mounting with inspection window and lockable access cover. Holder to have spindle system for 2 standard toilet rolls with max. 120 mm Ø. second roll will be released after consumption of first roll, reserve roll not to be visible. All necessary fixings to be included. All as per Franke STRX 672 or other equal and approved. Grab Rail Dogs Leg Grab Rail - 300 x 300 x 300mm long x 32mm diameter grade 304 stainless steel satin polished "dogs leg" grab rail with minimum 75mm clearance to wall and fixed to wall with minimum 3x4mm diameter wall anchors per end hidden under tamper resistant cover plates. As per Franke CNTX21N or other approved Grab Rail U Shaped 750mm long x 90 x 32mm diameter grade 304 stainless steel grab rail finished grab rail fixed to wall with 3 stainless steel fixed to wall with minimum 3x4mm diameter wall anchors per end hidden under tamper resistant cover plates. As per Franke CNTX750N or other approved Electric Hand Drier Sensor operated hand dryer for wall mounting manufactured from Grade 304 x 1,2mm stainless steel, brushed finish including all mounting brackets and fittings as well as all required electrical connections. All as per Jetstream Airtronic or similar approved.		Sanitaryware Specifications Fittings 2 Toilet Roll Holder - Vandal resistant Toilet roll holder stainless steel grade 304 x 1,5mm satin surface finished for surface mounting with inspection window and lockable access cover. Holder to have spindle system for 2 standard toilet rolls with max. 120 mm Ø. second roll will be released after consumption of first roll, reserve roll not to be visible. All necessary fixings to be included. All as per Franke STRX 672 or other equal and approved. Grab Rail Dogs Leg Grab Rail - 300 x 300 x 300mm long x 32mm diameter grade 304 stainless steel satin polished "dogs leg" grab rail with minimum 75mm clearance to wall and fixed to wall with minimum 3x4mm diameter wall anchors per end hidden under tamper resistant cover plates. As per Franke CNTX21N or other approved Grab Rail U Shaped 750mm long x 90 x 32mm diameter grade 304 stainless steel grab rail finished grab rail fixed to wall with 3 stainless steel fixed to wall with minimum 3x4mm diameter wall anchors per end hidden under tamper resistant cover plates. As per Franke CNTX750N or other approved Electric Hand Drier Sensor operated hand dryer for wall mounting manufactured from Grade 304 x 1,2mm stainless steel, brushed finish including all mounting brackets and fittings as well as all required electrical connections. All as per Jetstream Airtronic or similar approved.		Sanitaryware Specifications Fittings 2 Toilet Roll Holder - Vandal resistant Toilet roll holder stainless steel grade 304 x 1,5mm satin surface finished for surface mounting with inspection window and lockable access cover. Holder to have spindle system for 2 standard toilet rolls with max. 120 mm Ø. second roll will be released after consumption of first roll, reserve roll not to be visible. All necessary fixings to be included. All as per Franke STRX 672 or other equal and approved. Grab Rail Dogs Leg Grab Rail - 300 x 300 x 300mm long x 32mm diameter grade 304 stainless steel satin polished "dogs leg" grab rail with minimum 75mm clearance to wall and fixed to wall with minimum 3x4mm diameter wall anchors per end hidden under tamper resistant cover plates. As per Franke CNTX21N or other approved Grab Rail U Shaped 750mm long x 90 x 32mm diameter grade 304 stainless steel grab rail finished grab rail fixed to wall with 3 stainless steel fixed to wall with minimum 3x4mm diameter wall anchors per end hidden under tamper resistant cover plates. As per Franke CNTX750N or other approved Electric Hand Drier Sensor operated hand dryer for wall mounting manufactured from Grade 304 x 1,2mm stainless steel, brushed finish including all mounting brackets and fittings as well as all required electrical connections. All as per Jetstream Airtronic or similar approved.		Sanitaryware Specifications Fittings 2 Toilet Roll Holder - Vandal resistant Toilet roll holder stainless steel grade 304 x 1,5mm satin surface finished for surface mounting with inspection window and lockable access cover. Holder to have spindle system for 2 standard toilet rolls with max. 120 mm Ø. second roll will be released after consumption of first roll, reserve roll not to be visible. All necessary fixings to be included. All as per Franke STRX 672 or other equal and approved. Grab Rail Dogs Leg Grab Rail - 300 x 300 x 300mm long x 32mm diameter grade 304 stainless steel satin polished "dogs leg" grab rail with minimum 75mm clearance to wall and fixed to wall with minimum 3x4mm diameter wall anchors per end hidden under tamper resistant cover plates. As per Franke CNTX21N or other approved Grab Rail U Shaped 750mm long x 90 x 32mm diameter grade 304 stainless steel grab rail finished grab rail fixed to wall with 3 stainless steel fixed to wall with minimum 3x4mm diameter wall anchors per end hidden under tamper resistant cover plates. As per Franke CNTX750N or other approved Electric Hand Drier Sensor operated hand dryer for wall mounting manufactured from Grade 304 x 1,2mm stainless steel, brushed finish including all mounting brackets and fittings as well as all required electrical connections. All as per Jetstream Airtronic or similar approved.		Sanitaryware Specifications Fittings 2 Toilet Roll Holder - Vandal resistant Toilet roll holder stainless steel grade 304 x 1,5mm satin surface finished for surface mounting with inspection window and lockable access cover. Holder to have spindle system for 2 standard toilet rolls with max. 120 mm Ø. second roll will be released after consumption of first roll, reserve roll not to be visible. All necessary fixings to be included. All as per Franke STRX 672 or other equal and approved. Grab Rail Dogs Leg Grab Rail - 300 x 300 x 300mm long x 32mm diameter grade 304 stainless steel satin polished "dogs leg" grab rail with minimum 75mm clearance to wall and fixed to wall with minimum 3x4mm diameter wall anchors per end hidden under tamper resistant cover plates. As per Franke CNTX21N or other approved Grab Rail U Shaped 750mm long x 90 x 32mm diameter grade 304 stainless steel grab rail finished grab rail fixed to wall with 3 stainless steel fixed to wall with minimum 3x4mm diameter wall anchors per end hidden under tamper resistant cover plates. As per Franke CNTX750N or other approved Electric Hand Drier Sensor operated hand dryer for wall mounting manufactured from Grade 304 x 1,2mm stainless steel, brushed finish including all mounting brackets and fittings as well as all required electrical connections. All as per Jetstream Airtronic or similar approved.		Sanitaryware Specifications Fittings 2 Toilet Roll Holder - Vandal resistant Toilet roll holder stainless steel grade 304 x 1,5mm satin surface finished for surface mounting with inspection window and lockable access cover. Holder to have spindle system for 2 standard toilet rolls with max. 120 mm Ø. second roll will be released after consumption of first roll, reserve roll not to be visible. All necessary fixings to be included. All as per Franke STRX 672 or other equal and approved. Grab Rail Dogs Leg Grab Rail - 300 x 300 x 300mm long x 32mm diameter grade 304 stainless steel satin polished "dogs leg" grab rail with minimum 75mm clearance to wall and fixed to wall with minimum 3x4mm diameter wall anchors per end hidden under tamper resistant cover plates. As per Franke CNTX21N or other approved Grab Rail U Shaped 750mm long x 90 x 32mm diameter grade 304 stainless steel grab rail finished grab rail fixed to wall with 3 stainless steel fixed to wall with minimum 3x4mm diameter wall anchors per end hidden under tamper resistant cover plates. As per Franke CNTX750N or other approved Electric Hand Drier Sensor operated hand dryer for wall mounting manufactured from Grade 304 x 1,2mm stainless steel, brushed finish including all mounting brackets and fittings as well as all required electrical connections. All as per Jetstream Airtronic or similar approved.		Sanitaryware Specifications Fittings 2 Toilet Roll Holder - Vandal resistant Toilet roll holder stainless steel grade 304 x 1,5mm satin surface finished for surface mounting with inspection window and lockable access cover. Holder to have spindle system for 2 standard toilet rolls with max. 120 mm Ø. second roll will be released after consumption of first roll, reserve roll not to be visible. All necessary fixings to be included. All as per Franke STRX 672 or other equal and approved. Grab Rail Dogs Leg Grab Rail - 300 x 300 x 300mm long x 32mm diameter grade 304 stainless steel satin polished "dogs leg" grab rail with minimum 75mm clearance to wall and fixed to wall with minimum 3x4mm diameter wall anchors per end hidden under tamper resistant cover plates. As per Franke CNTX21N or other approved Grab Rail U Shaped 750mm long x 90 x 32mm diameter grade 304 stainless steel grab rail finished grab rail fixed to wall with 3 stainless steel fixed to wall with minimum 3x4mm diameter wall anchors per end hidden under tamper resistant cover plates. As per Franke CNTX750N or other approved Electric Hand Drier Sensor operated hand dryer for wall mounting manufactured from Grade 304 x 1,2mm stainless steel, brushed finish including all mounting brackets and fittings as well as all required electrical connections. All as per Jetstream Airtronic or similar approved.		Sanitaryware Specifications Fittings 2 Toilet Roll Holder - Vandal resistant Toilet roll holder stainless steel grade 304 x 1,5mm satin surface finished for surface mounting with inspection window and lockable access cover. Holder to have spindle system for 2 standard toilet rolls with max. 120 mm Ø. second roll will be released after consumption of first roll, reserve roll not to be visible. All necessary fixings to be included. All as per Franke STRX 672 or other equal and approved. Grab Rail Dogs Leg Grab Rail - 300 x 300 x 300mm long x 32mm diameter grade 304 stainless steel satin polished "dogs leg" grab rail with minimum 75mm clearance to wall and fixed to wall with minimum 3x4mm diameter wall anchors per end hidden under tamper resistant cover plates. As per Franke CNTX21N or other approved Grab Rail U Shaped 750mm long x 90 x 32mm diameter grade 304 stainless steel grab rail finished grab rail fixed to wall with 3 stainless steel fixed to wall with minimum 3x4mm diameter wall anchors per end hidden under tamper resistant cover plates. As per Franke CNTX750N or other approved Electric Hand Drier Sensor operated hand dryer for wall mounting manufactured from Grade 304 x 1,2mm stainless steel, brushed finish including all mounting brackets and fittings as well as all required electrical connections. All as per Jetstream Airtronic or similar approved.		Sanitaryware Specifications Fittings 2 Toilet Roll Holder - Vandal resistant Toilet roll holder stainless steel grade 304 x 1,5mm satin surface finished for surface mounting with inspection window and lockable access cover. Holder to have spindle system for 2 standard toilet rolls with max. 120 mm Ø. second roll will be released after consumption of first roll, reserve roll not to be visible. All necessary fixings to be included. All as per Franke STRX 672 or other equal and approved. Grab Rail Dogs Leg Grab Rail - 300 x 300 x 300mm long x 32mm diameter grade 304 stainless steel satin polished "dogs leg" grab rail with minimum 75mm clearance to wall and fixed to wall with minimum 3x4mm diameter wall anchors per end hidden under tamper resistant cover plates. As per Franke CNTX21N or other approved Grab Rail U Shaped 750mm long x 90 x 32mm diameter grade 304 stainless steel grab rail finished grab rail fixed to wall with 3 stainless steel fixed to wall with minimum 3x4mm diameter wall anchors per end hidden under tamper resistant cover plates. As per Franke CNTX750N or other approved Electric Hand Drier Sensor operated hand dryer for wall mounting manufactured from Grade 304 x 1,2mm stainless steel, brushed finish including all mounting brackets and fittings as well as all required electrical connections. All as per Jetstream Airtronic or similar approved.		Sanitaryware Specifications Fittings 2 Toilet Roll Holder - Vandal resistant Toilet roll holder stainless steel grade 304 x 1,5mm satin surface finished for surface mounting with inspection window and lockable access cover. Holder to have spindle system for 2 standard toilet rolls with max. 120 mm Ø. second roll will be released after consumption of first roll, reserve roll not to be visible. All necessary fixings to be included. All as per Franke STRX 672 or other equal and approved. Grab Rail Dogs Leg Grab Rail - 300 x 300 x 300mm long x 32mm diameter grade 304 stainless steel satin polished "dogs leg" grab rail with minimum 75mm clearance to wall and fixed to wall with minimum 3x4mm diameter wall anchors per end hidden under tamper resistant cover plates. As per Franke CNTX21N or other approved Grab Rail U Shaped 750mm long x 90 x 32mm diameter grade 304 stainless steel grab rail finished grab rail fixed to wall with 3 stainless steel fixed to wall with minimum 3x4mm diameter wall anchors per end hidden under tamper resistant cover plates. As per Franke CNTX750N or other approved Electric Hand Drier Sensor operated hand dryer for wall mounting manufactured from Grade 304 x 1,2mm stainless steel, brushed finish including all mounting brackets and fittings as well as all required electrical connections. All as per Jetstream Airtronic or similar approved.		Sanitaryware Specifications Fittings 2 Toilet Roll Holder - Vandal resistant Toilet roll holder stainless steel grade 304 x 1,5mm satin surface finished for surface mounting with inspection window and lockable access cover. Holder to have spindle system for 2 standard toilet rolls with max. 120 mm Ø. second roll will be released after consumption of first roll, reserve roll not to be visible. All necessary fixings to be included. All as per Franke STRX 672 or other equal and approved. Grab Rail Dogs Leg Grab Rail - 300 x 300 x 300mm long x 32mm diameter grade 304 stainless steel satin polished
--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	---