

|   |                         |
|---|-------------------------|
| Structure Code:                           | <b>Strsce4518kw.110</b> |
| Phase Conductor:                          | <b>Kingbird</b>         |
| Shield Conductor:                         | <b>wolf</b>             |
| Wind Span: (m)                            | 150                     |
| Weight Span: (m)                          | 347                     |
| Vertical $\Phi$ - $\Phi$ Spacing: (m)     | 2.40                    |
| Vertical $\epsilon$ - $\Phi$ Spacing: (m) | 2.20                    |
| Cah: (m)                                  | 11.00                   |
| Sides                                     | 12                      |
| Total Length: (m)                         | 18                      |
| Tip diameter: (mm)                        | 330                     |
| Base Diameter: (mm)                       | 950                     |
| Wall Thickness: (mm)                      | 12                      |
| Base Plate O.D : (mm)                     | 1300                    |
| Base Plate I.D: (mm)                      | 800                     |
| Base Plate Thickness: (mm)                | 55                      |
| H.D Bolts: (Qty)                          | 36                      |
| H.D Bolts Diameter: (mm)                  | 42                      |
| H.D Bolts PCD: (mm)                       | 1130                    |
| Working Tip Load: (kN)                    | 76                      |
| Base g.I Moment: (kNm)                    | 1363                    |
| Approximate mass: (tons)                  | 4.07                    |