

Supply Chain Management
Warehouse
Scope of work for PPE Footwear

Short Text	Long Text	Quantities Required	Unit of Measure
BOOTS SFTY:10;STRD; STL;BROWN;34-232	BOOTS, SAFETY: SIZE: 10; TOE CONSTRUCTION TYPE: STRD; STL; COLOR: BROWN; MATERIAL: LEATHER FULL GRAIN OILY PULL-UP; STYLE: 34-232; TREAD SURFACE TYPE: PU/VIBRAM RUBBER; SRC SLIP RESISTANCE; FASTENING METHOD: 5 PAIR LOOPS; SKI HOOKS CORROSION-RESISTANT GUNMETAL COATING; BRAIDED LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; MODEL NO: 43606; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	9	PAA

#### Controlled Disclosure

Hard copy printed on: 19/04/2023 Form No.: 240-94026621 Rev 1



BOOTS SFTY:11;STRD; STL;BROWN;34-232	BOOTS, SAFETY: SIZE: 11; TOE CONSTRUCTION TYPE: STRD; STL;	9	PAA
	COLOR: BROWN; MATERIAL: LEATHER FULL GRAIN OILY PULL-UP;		1,75,
	STYLE: 34-232; TREAD SURFACE TYPE: PU/VIBRAM RUBBER; SRC		
	SLIP RESISTANCE; FASTENING METHOD: 5 PAIR LOOPS; SKI		
	HOOKS CORROSION-RESISTANT GUNMETAL COATING; BRAIDED		
	LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; MODEL		
	NO: 43606; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS		
	ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE		
	DARK BROWN; THE LACES SHALL MATCH THE RELEVANT BOOT		
	COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED		
	TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL		
	OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS		
	SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-		
	RESISTANT INSERT		



DOOTO OFTY 40 OTDD OTL DDOWN 04 000	DOOTO CAFETY CIZE 40 TOE CONCEDUCTION TYPE CERR OF		DAA
BOOTS SFTY:12;STRD; STL;BROWN;34-232	BOOTS, SAFETY: SIZE: 12; TOE CONSTRUCTION TYPE: STRD; STL;	9	PAA
	COLOR: BROWN; MATERIAL: LEATHER FULL GRAIN OILY PULL-UP;		
	STYLE: 34-232; TREAD SURFACE TYPE: PU/VIBRAM RUBBER; SRC		
	SLIP RESISTANCE; FASTENING METHOD: 5 PAIR LOOPS; SKI		
	HOOKS CORROSION-RESISTANT GUNMETAL COATING; BRAIDED		
	LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; MODEL		
	NO: 43606; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS		
	ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE		
	DARK BROWN; THE LACES SHALL MATCH THE RELEVANT BOOT		
	COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED		
	TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL		
	OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS		
	SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-		
	RESISTANT INSERT		
	ILCIOTANT INOLIT		



BOOTS SFTY:3;STRD; STL;BROWN;34-232	BOOTS, SAFETY: SIZE: 3; TOE CONSTRUCTION TYPE: STRD; STL;	6	PAA
, , , , ,	COLOR: BROWN; MATERIAL: LEATHER FULL GRAIN OILY PULL-UP;		
	STYLE: 34-232; TREAD SURFACE TYPE: PU/VIBRAM RUBBER; SRC		
	SLIP RESISTANCE; FASTENING METHOD: 5 PAIR LOOPS; SKI		
	HOOKS CORROSION-RESISTANT GUNMETAL COATING; BRAIDED		
	LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; MODEL		
	NO: 43606; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS		
	ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE		
	DARK BROWN; THE LACES SHALL MATCH THE RELEVANT BOOT		
	COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED		
	TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL		
	OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-		
	RESISTANT INSERT		
	INCOIDIANT INOCINT		



BOOTS SFTY:4;STRD; STL;BROWN;34-232	BOOTS, SAFETY: SIZE: 4; TOE CONSTRUCTION TYPE: STRD; STL;	6	PAA
	COLOR: BROWN; MATERIAL: LEATHER FULL GRAIN OILY PULL-UP;		
	STYLE: 34-232; TREAD SURFACE TYPE: PU/VIBRAM RUBBER; SRC		
	SLIP RESISTANCE; FASTENING METHOD: 5 PAIR LOOPS; SKI		
	HOOKS CORROSION-RESISTANT GUNMETAL COATING; BRAIDED		
	LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; MODEL		
	NO: 43606; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS		
	ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE		
	DARK BROWN; THE LACES SHALL MATCH THE RELEVANT BOOT		
	COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED		
	TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL		
	OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS		
	SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION- RESISTANT INSERT		
	RESISTANT INSERT		



BOOTS SFTY:5;STRD; STL;BROWN;34-232	BOOTS, SAFETY: SIZE: 5; TOE CONSTRUCTION TYPE: STRD; STL;	9	PAA
	COLOR: BROWN; MATERIAL: LEATHER FULL GRAIN OILY PULL-UP; STYLE: 34-232; TREAD SURFACE TYPE: PU/VIBRAM RUBBER; SRC		
	SLIP RESISTANCE; FASTENING METHOD: 5 PAIR LOOPS; SKI		
	HOOKS CORROSION-RESISTANT GUNMETAL COATING; BRAIDED		
	LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; MODEL		
	NO: 43606; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE		
	DARK BROWN: THE LACES SHALL MATCH THE RELEVANT BOOT		
	COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED		
	TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL		
	OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS		
	SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION- RESISTANT INSERT		
	REGIOTARY INCERT		



BOOTS SFTY:6;STRD; STL;BROWN;34-232	BOOTS, SAFETY: SIZE: 6; TOE CONSTRUCTION TYPE: STRD; STL; COLOR: BROWN; MATERIAL: LEATHER FULL GRAIN OILY PULL-UP; STYLE: 34-232; TREAD SURFACE TYPE: PU/VIBRAM RUBBER; SRC SLIP RESISTANCE; FASTENING METHOD: 5 PAIR LOOPS; SKI HOOKS CORROSION-RESISTANT GUNMETAL COATING; BRAIDED LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; MODEL NO: 43606; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS	9	PAA
	STYLE: 34-232; TREAD SURFACE TYPE: PU/VIBRAM RUBBER; SRC SLIP RESISTANCE; FASTENING METHOD: 5 PAIR LOOPS; SKI HOOKS CORROSION-RESISTANT GUNMETAL COATING; BRAIDED LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; MODEL		



	1		1
BOOTS SFTY:7;STRD; STL;BROWN;34-232	BOOTS, SAFETY: SIZE: 7; TOE CONSTRUCTION TYPE: STRD; STL; COLOR: BROWN; MATERIAL: LEATHER FULL GRAIN OILY PULL-UP; STYLE: 34-232; TREAD SURFACE TYPE: PU/VIBRAM RUBBER; SRC SLIP RESISTANCE; FASTENING METHOD: 5 PAIR LOOPS; SKI HOOKS CORROSION-RESISTANT GUNMETAL COATING; BRAIDED LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; MODEL NO: 43606; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	15	PAA



BOOTS SFTY:8;STRD; STL;BROWN;34-232	BOOTS, SAFETY: SIZE: 8; TOE CONSTRUCTION TYPE: STRD; STL;	36	PAA
	COLOR: BROWN; MATERIAL: LEATHER FULL GRAIN OILY PULL-UP;		
	STYLE: 34-232; TREAD SURFACE TYPE: PU/VIBRAM RUBBER; SRC		
	SLIP RESISTANCE; FASTENING METHOD: 5 PAIR LOOPS; SKI		
	HOOKS CORROSION-RESISTANT GUNMETAL COATING; BRAIDED		
	LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; MODEL		
	NO: 43606; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS		
	ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE		
	DARK BROWN; THE LACES SHALL MATCH THE RELEVANT BOOT		
	COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED		
	TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL		
	OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS		
	SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-		
	RESISTANT INSERT		



BOOTS SFTY:9;STRD; STL;BROWN;34-232	BOOTS, SAFETY: SIZE: 9; TOE CONSTRUCTION TYPE: STRD; STL; COLOR: BROWN; MATERIAL: LEATHER FULL GRAIN OILY PULL-UP; STYLE: 34-232; TREAD SURFACE TYPE: PU/VIBRAM RUBBER; SRC SLIP RESISTANCE; FASTENING METHOD: 5 PAIR LOOPS; SKI HOOKS CORROSION-RESISTANT GUNMETAL COATING; BRAIDED LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; MODEL NO: 43606; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS	45	PAA
	OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT		



Supply Chain Management
Warehouse
Scope of Work for PPE Footwear

BOOTS SFTY:10;STRD; STL OR CARBON FIBER	BOOTS, SAFETY: SIZE: 10; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	2 130	PAA
BOOTS SFTY:10;CARBON FIBRE;WHITE;34-232	BOOTS, SAFETY: SIZE: 10; TOE CONSTRUCTION TYPE: CARBON FIBRE; COLOR: WHITE; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: SLIP ON; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; BOOTS TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; WITH PENETRATION RESISTANT INSERT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL	8 100	PAA



Supply Chain Management
Warehouse
Scope of Work for PPE Footwear

DOOTS SETVINA STRD. STL OR CARRON FIRED	DOOTS CAFETY, SIZE, 44, TOE CONSTRUCTION TYPE, STRD, ST	000	DAA
BOOTS SFTY:11;STRD; STL OR CARBON FIBER	BOOTS, SAFETY: SIZE: 11; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	600	PAA
BOOTS SFTY:11;CARBON FIBRE;WHITE;34-232	BOOTS, SAFETY: SIZE: 11; TOE CONSTRUCTION TYPE: CARBON FIBRE; COLOR: WHITE; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: SLIP ON; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; BOOTS TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; WITH PENETRATION RESISTANT INSERT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL	1 800	PAA



Supply Chain Management
Warehouse
Scope of Work for PPE Footwear

BOOTS SFTY:12;STRD; STL OR CARBON FIBER	BOOTS, SAFETY: SIZE: 12; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	500	PAA
BOOTS SFTY:12;CARBON FIBRE;WHITE;34-232	BOOTS, SAFETY: SIZE: 12; TOE CONSTRUCTION TYPE: CARBON FIBRE; COLOR: WHITE; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: SLIP ON; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; BOOTS TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; WITH PENETRATION RESISTANT INSERT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL	1 800	PAA



Supply Chain Management
Warehouse
Scope of Work for PPE Footwear

BOOTS SFTY:13;STRD; STL OR CARBON FIBER	BOOTS, SAFETY: SIZE: 13; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	115	PAA
BOOTS SFTY:13;CARBON FIBRE;WHITE;34-232	BOOTS, SAFETY: SIZE: 13; TOE CONSTRUCTION TYPE: CARBON FIBRE; COLOR: WHITE; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: SLIP ON; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; BOOTS TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; WITH PENETRATION RESISTANT INSERT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL	360	PAA



Supply Chain Management
Warehouse

Scope of Work	for PPE Footwear
---------------	------------------

BOOTS SFTY:14;STL;BLACK;UPPER LEATHER	BOOTS, SAFETY: SIZE: 14; TOE CONSTRUCTION TYPE: STL; COLOR: BLACK; MATERIAL: UPPER LEATHER; STYLE: BOVA NEOFLEX 9004; TREAD SURFACE TYPE: SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: ESKOM 34-232; SANS/ISO 20345	6	PAA
BOOTS SFTY:3;STRD; STL OR CARBON FIBER	BOOTS, SAFETY: SIZE: 3; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	120	PAA



Supply Chain Management
Warehouse
Scope of Work for PPE Footwear

BOOTS SFTY:3;CARBON FIBRE;WHITE;34-232	BOOTS, SAFETY: SIZE: 3; TOE CONSTRUCTION TYPE: CARBON FIBRE; COLOR: WHITE; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: SLIP ON; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; BOOTS TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; WITH PENETRATION RESISTANT INSERT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL	1 800	PAA
BOOTS SFTY:4;STRD; STL OR CARBON FIBER	BOOTS, SAFETY: SIZE: 4; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	930	PAA



Supply Chain Management
Warehouse
Scope of Work for PPE Footwear

BOOTS SFTY:4;CARBON FIBRE;WHITE;34-232	BOOTS, SAFETY: SIZE: 4; TOE CONSTRUCTION TYPE: CARBON FIBRE; COLOR: WHITE; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: SLIP ON; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; BOOTS TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; WITH PENETRATION RESISTANT INSERT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL	1 800	PAA
BOOTS SFTY:5;STRD; STL OR CARBON FIBER	BOOTS, SAFETY: SIZE: 5; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	1 820	PAA



Supply Chain Management
Warehouse
Scope of Work for PPE Footwear

BOOTS SFTY:5;CARBON FIBRE;WHITE;34-232	BOOTS, SAFETY: SIZE: 5; TOE CONSTRUCTION TYPE: CARBON FIBRE; COLOR: WHITE; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: SLIP ON; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; BOOTS TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; WITH PENETRATION RESISTANT INSERT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL	1 800	PAA
BOOTS SFTY:6;STRD; STL OR CARBON FIBER	BOOTS, SAFETY: SIZE: 6; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	2 880	PAA



Supply Chain Management
Warehouse
Scope of Work for PPE Footwear

BOOTS SFTY:6;CARBON FIBRE;WHITE;34-232	BOOTS, SAFETY: SIZE: 6; TOE CONSTRUCTION TYPE: CARBON FIBRE; COLOR: WHITE; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: SLIP ON; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; BOOTS TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; WITH PENETRATION RESISTANT INSERT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL	1 800	PAA
BOOTS SFTY:7;STRD; STL OR CARBON FIBER	BOOTS, SAFETY: SIZE: 7; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	4 035	PAA



Supply Chain Management
Warehouse
Scope of Work for PPE Footwear

BOOTS SFTY:7;CARBON FIBRE;WHITE;34-232	BOOTS, SAFETY: SIZE: 7; TOE CONSTRUCTION TYPE: CARBON FIBRE; COLOR: WHITE; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: SLIP ON; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; BOOTS TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; WITH PENETRATION RESISTANT INSERT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL	1 800	PAA
BOOTS SFTY:8;STRD; STL OR CARBON FIBER	BOOTS, SAFETY: SIZE: 8; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	4 340	PAA



Supply Chain Management
Warehouse

Scope of Work for PPE Footwea	ar
-------------------------------	----

BOOTS SFTY:8;CARBON FIBRE;WHITE;34-232	BOOTS, SAFETY: SIZE: 8; TOE CONSTRUCTION TYPE: CARBON FIBRE; COLOR: WHITE; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: SLIP ON; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; BOOTS TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; WITH PENETRATION RESISTANT INSERT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL	1 800	PAA
BOOTS SFTY:9;STRD; STL OR CARBON FIBER	BOOTS, SAFETY: SIZE: 9; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	3 350	PAA



Supply Chain Management
Warehouse

Scope of Work for PPE Footwear

BOOTS SFTY:9;CARBON FIBRE;WHITE;34-232	BOOTS, SAFETY: SIZE: 9; TOE CONSTRUCTION TYPE: CARBON FIBRE; COLOR: WHITE; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: SLIP ON; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; BOOTS TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; WITH PENETRATION RESISTANT INSERT; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL	1 800	PAA
GUMBOOTS SFTY:STL;7;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 7; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; SIZE 255; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; BEARING SABS MARK OF APPROVAL	700	PAA
GUMBOOTS SFTY:STL;10;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 10; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; SIZE 280; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345	720	PAA



Supply Chain Management

Warehouse

Scope of Work for PPE Footwear

GUMBOOTS SFTY:STL;11;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 11; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240- 44175132; SIZE: 290; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345	150	PAA
GUMBOOTS SFTY:STL;12;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 12; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; SIZE 292; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345	90	PAA
GUMBOOTS SFTY:STL;13;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 13; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240- 44175132; SIZE 300; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345	360	PAA
GUMBOOTS SFTY:STL;3;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 3; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345	5 400	PAA



Supply Chain Management
Warehouse

Scope of Work for PPE Footwear

GUMBOOTS SFTY:STL;4;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 4; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345	5 400	PAA
GUMBOOTS SFTY:STL;5;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 5; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345	5 400	PAA
GUMBOOTS SFTY:STL;6;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 6; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; SIZE 247; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345	5 400	PAA
GUMBOOTS SFTY:STL;8;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 8; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; SIZE 262; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345	3 600	PAA



Supply Chain Management
Warehouse
Scope of Work for PPE Footwear

GUMBOOTS SFTY:STL;9;KNEE HEIGHT;BLACK	GUMBOOTS, SAFETY: TOE CAP: STL; SIZE: 9; STYLE: KNEE HEIGHT; COLOR: BLACK; MATERIAL: RUBBER; TREAD TYPE: RUBBER MOLDED; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; SIZE 270; LOW ABRASION; MATERIAL FULL VULCANISED RUBBER; ACID AND OIL RESISTANT; NON SLIP SOLE; WATERPROOF CONSTRUCTION; TO SABS 20345	3 600	PAA
SHOES SFTY:10;STRD; STL OR CARBON FIBER	SHOES, SAFETY: SIZE: 10; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	600	PAA



SHOES SFTY:11;STRD; STL OR CARBON FIBER	SHOES, SAFETY: SIZE: 11; TOE CONSTRUCTION TYPE: STRD; STL	1 800	PAA
	OR CARBON FIBER; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD		
	SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE;		
	MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD:		
	LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132;		
	STANDARD; SHOES TO COMPLY WITH SAFETY SHOES		
	ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE		
	DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN		
	THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES		
	SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND		
	FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE		
	CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008		
	MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT		



SHOES SFTY:12;STRD; STL OR CARBON FIBER	SHOES, SAFETY: SIZE: 12; TOE CONSTRUCTION TYPE: STRD; STL	1 800	PAA
	OR CARBON FIBER; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD		
	SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE;		
	MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD:		
	LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132;		
	STANDARD; SHOES TO COMPLY WITH SAFETY SHOES		
	ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE		
	DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN		
	THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES		
	SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY		
	PRODUCED OR MANUFACTURED TEXTILES LEATHER AND		
	FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE		
	CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008		
	MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT		
		1	



SHOES SFTY:13;STRD; STL OR CARBON FIBER	SHOES, SAFETY: SIZE: 13; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD; SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	1 800	PAA
---	--	-------	-----



SHOES SAFETY: SIZE: 3: TOE CONSTRUCTION TYPE: STRD: STI	200	PAA
	200	FAA
· · · · · · · · · · · · · · · · · · ·		
,		
· ·		
· · · · · · · · · · · · · · · · · · ·		
, ,		
DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN		
THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES		
SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY		
PRODUCED OR MANUFACTURED TEXTILES LEATHER AND		
FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE		
CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008		
MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT		
	THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008	OR CARBON FIBER; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD; SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008



SHOES SFTY:4;STRD; STL OR CARBON FIBER	SHOES, SAFETY: SIZE: 4; TOE CONSTRUCTION TYPE: STRD; STL	400	PAA
, , , , , , , , , , , , , , , , , , , ,	OR CARBON FIBER; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD		
	SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE;		
	MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD:		
	LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132;		
	STANDARD SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL		
	TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN;		
	WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL		
	BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE		
	RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR		
	MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM		
	LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL;		
	WITH PENETRATION-RESISTANT INSERT		
	WITH F LINE HATION-INCOISTAINT INSERT		



SHOES SFTY:5;STRD; STL OR CARBON FIBER  SHOES, SAFETY: SIZE: 5; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT



SHOES SFTY:6;STRD; STL OR CARBON FIBER	SHOES, SAFETY: SIZE: 6; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN;	1 000	PAA
	WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT		



SHOES SFTY:7;STRD; STL OR CARBON FIBER	SHOES, SAFETY: SIZE: 7; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	2 000	PAA



SHOES SFTY:8;STRD; STL OR CARBON FIBER	SHOES, SAFETY: SIZE: 8; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD	1 900	PAA
	SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE;		
	MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132;		
	STANDARD SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN;		
	WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE		
	RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM		
	LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO		
	BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT		



Supply Chain Management
Warehouse
Scope of Work for PPE Footwear

SHOES SFTY:9;STRD; STL OR CARBON FIBER	SHOES, SAFETY: SIZE: 9; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; MATERIAL: UPPER LEATHER FULL GRAIN; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD SHOES TO COMPLY WITH SAFETY SHOES ELECTRICAL TESTING SPECIFICATION 34-232; THE SHOES TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT SHOE COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	1 240	PAA
WADER:FISHERMANS;10;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 10; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	216	PAA
WADER:FISHERMANS;11;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 11; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	216	PAA
WADER:FISHERMANS;12;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 12; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	288	PAA
WADER:FISHERMANS;13;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 13; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	216	PAA

#### Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.



Supply Chain Management
Warehouse

Scope of Work	for PPE	Footwear
---------------	---------	----------

WADER:FISHERMANS;6;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 6; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	288	PAA
WADER:FISHERMANS;7;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 7; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	288	PAA
WADER:FISHERMANS;8;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 8; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	288	PAA
WADER:FISHERMANS;9;PVC;GREEN OLIVE	WADER: TYPE: FISHERMANS; SIZE: 9; MATERIAL: PVC; COLOR: GREEN OLIVE; WATERPROOF; CONSIST OF TROUSERS AND ATTACHED BOOTS; UNIQUE IDENTIFIER 240-44175132	288	PAA

Complied B	/: Cvnthia	Tsotetsi

Signature Communication

Date 19/04/2023

Approved By: Boitshoko Mokolobate

Signature..

Date...19/04/2023.....