

Business Management System

Supply Chain Management

Warehouse

Warehouse Scope of work for Paint

Short Text	Long Text	Quantity Requested	Unit of Measure
PAINT OIL:BROWN DARK;SPRAY	PAINT, OIL: COLOR: BROWN DARK, APPLICATION METHOD: SPRAY; LAC-R	3	EA
PAINT PRMR:OXIDE;CAN 5 L;RED	PAINT, PRIMER: TYPE: OXIDE; CONTAINER: CAN 5 L; COLOR: RED; MANUF P/N: SNK2	5 000	L
PAINT OIL:ENAMEL;BLACK;CAN 5 L;GLOSS	PAINT, OIL: ENAMEL, COLOR: BLACK, CONTAINER: CAN 5 L, FINISH: GLOSS, SPECIFIC USE: EXTERIOR/INTERIOR, DRYING SPEED: FAST, APPLICATION METHOD: BRUSH OR ROLLER, SPECIFICATION: SABS 630 GR 1; MANUF P/N: G2	542	L
PAINT OIL:ENAMEL;STOEP GREEN;CAN 5 L	PAINT, OIL: TYPE: ENAMEL; COLOR: STOEP GREEN; CONTAINER: CAN 5 L; FINISH: GLOSS; SPECIFIC USE: FLOOR; DRYING SPEED: FAST; APPLICATION METHOD: BRUSH OR ROLLER; SPECIFICATION: SABS 630 GR 1; NOTE: MATERIAL DATA SHEET REQUIRE WITH DELIVERY	2 125	L
COATING INSLTN:CLEAR VARNISH;TIN;5 L	COATING, INSULATION: TYPE: CLEAR VARNISH, CONTAINER: TIN, QUANTITY: 5 L, SPECIFICATION: DIN51757; REFERENCE NO: VA00; REFERENCE NO: 009-0008; ELMOTHERM; SINGLE COMPONENT, ANTI-TRACKING, FUNGICIDAL VARNISH, SUITABLE FOR TRANSFORMERS, MOTORS AND WINDINGS; NOTE ! MATERIAL SAFETY DATA SHEET REQUIRE WITH DELIVERY	435	L
THINNER PAINT:LACQUER GRADE A;5 L;ILS 1	THINNER, PAINT: TYPE: LACQUER GRADE A, CONTAINER: 5 L; REFERENCE NO: ILS 1; NOTE: MATERIAL DATA SAFETY SHEET REQUIRE WITH DELIVERY	10 000	L

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse Scope of work for Paint

PAINT OIL:PLASCOTHANE 9000;DARK GREY	PAINT, OIL: PLASCOTHANE 9000, COLOR: DARK GREY, CONTAINER: CAN 4.29 L, FINISH: ACRYLIC ENAMEL, SPECIFIC USE: TRANSFORMER, DRYING SPEED: QUICK, APPLICATION METHOD: SPRAY	500	L
PAINT:PLASCOTHANE 9000 TINTED	PAINT: PLASCOTHANE 9000 TINTED, COLOR: MANILA BS381C	100	EA
THINNER PAINT:BENZINE;5 L;TH3	THINNER, PAINT: TYPE: BENZINE, CONTAINER: 5 L; REFERENCE NO: TH3; NOTE: MATERIAL SAFETY DATA SHEET REQUIRE WITH DELIVERY	440	L
PAINT OIL:AEROLAC;BLACK;GLOSS;QUICK	PAINT, OIL: TYPE: AEROLAC, COLOR: BLACK, CONTAINER: CAN AEROSOL 300 ML, FINISH: GLOSS, SPECIFIC USE: EXTERIOR/INTERIOR, DRYING SPEED: QUICK, APPLICATION METHOD: SPRAY; NOTE; MATERIAL DATA SHEET REQUIRE WITH DELIVERY	100	EA
PAINT OIL:AEROLAC;WHITE;GLOSS;QUICK	PAINT, OIL: TYPE: AEROLAC, COLOR: WHITE, CONTAINER: CAN AEROSOL 300 ML, FINISH: GLOSS, SPECIFIC USE: EXTERIOR/INTERIOR, DRYING SPEED: QUICK, APPLICATION METHOD: SPRAY; NOTE; MATERIAL DATA SHEET REQUIRE WITH DELIVERY	200	EA
PAINT OIL:COLD ZINC GALVANISING;SILVER	PAINT, OIL: TYPE: COLD ZINC GALVANISING; COLOR: SILVER; CONTAINER: CAN AEROSOL 400 ML; FINISH: MATT; APPLICATION METHOD: SPRAY; NOTE: MATERIAL SAFETY DATA SHEET REQUIRE WITH DELIVERY	500	EA
PAINT OIL:ENAMEL;RED SIGNAL;CAN 5 L	PAINT, OIL: TYPE: ENAMEL, COLOR: RED SIGNAL, CONTAINER: CAN 5 L, FINISH: GLOSS, SPECIFIC USE: EXTERIOR/INTERIOR, DRYING SPEED: FAST, APPLICATION METHOD: BRUSH OR ROLLER, SPECIFICATION: SABS 630 GR 1; SUPPL P/N: G7; NOTE: MATERIAL DATA SHEET REQUIRE WITH DELIVERY	100	L

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse Scope of work for Paint

PAINT OIL:ENAMEL;WHITE;CAN 5 L;EGGSHELL	PAINT, OIL: TYPE: ENAMEL, COLOR: WHITE, CONTAINER: CAN 5 L, FINISH: EGGSHELL, SPECIFIC USE: EXTERIOR/INTERIOR, DRYING SPEED: QUICK, APPLICATION METHOD: BRUSH OR ROLLER, SPECIFICATION: SABS 630 GR 1; NOTE: MATERIAL SAFETY DATA SHEET REQUIRE WITH DELIVERY	1 066	L
PAINT PRMR:AEROSOL;CAN 200 ML;GRAY	PAINT, PRIMER: TYPE: COASTCOTE ETCH, CONTAINER: CAN 5 L, COLOR: IVORY; SUPPL P/N: SNK5; NOTE: MATERIAL DATA SHEET REQUIRE WITH DELIVERY	104	EA
THINNER PAINT:G.P. REDUCER EPOXY;5 L	THINNER, PAINT: G.P. REDUCER EPOXY, CONTAINER: 5 L; REFERENCE NO: EPT 1	282	L
PAINT STRIPPER:REMOVALL;CAN 3L;PLASCON	PAINT STRIPPER: TYPE: REMOVALL, CONTAINER TYPE: CAN 3L, TRADE NAME: PLASCON, CONTAINER CAPACITY: 3 L; MANUF P/N: RRA220; NOTE: MATERIAL SAFETY DATA SHEET REQUIRED WITH DELIVERY	500	L
BRUSH PAINT:WD 12 MM	BRUSH, PAINT: 12 MM	50	EA
PAINT OIL:ENAMEL;STOEP RED;CAN 5 L;GLOSS	PAINT, OIL: TYPE: ENAMEL, COLOR: STOEP RED, CONTAINER: CAN 5 L, FINISH: GLOSS, SPECIFIC USE: FLOOR, DRYING SPEED: FAST, APPLICATION METHOD: BRUSH OR ROLLER, SPECIFICATION: SABS 630 GR 1; NOTE: MATERIAL DATA SHEET REQUIRE WITH DELIVERY	54	EA
PAINT OIL:ENAMEL;BLUE SKY;CAN 5 L	PAINT, OIL: TYPE: ENAMEL; COLOR: BLUE SKY; CONTAINER: CAN 5 L; FINISH: HIGH GLOSS; SPECIFIC USE: EXTERIOR/INTERIOR; DRYING SPEED: SLOW DRY; APPLICATION METHOD: BRUSH OR ROLLER; SPECIFICATION: SABS 630 TYPE 1; SUPPLIER NOTE: MATERIAL SAFETY DATA SHEET REQUIRE WITH DELIVERY	180	L

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse Scope of work for Paint

PAINT OIL:ENAMEL;ORANGE LIGHT;5 L;GLOSS	PAINT, OIL: TYPE: ENAMEL, COLOR: ORANGE LIGHT, CONTAINER: 5 L, FINISH: GLOSS, SPECIFIC USE: EXTERIOR/INTERIOR, DRYING SPEED: QUICK, APPLICATION METHOD: BRUSH OR ROLLER, SPECIFICATION: SABS 684-1972; SABS679 TYPE 1; SUPPL P/N: G127; NOTE: MATERIAL SAFETY DATA SHEET REQUIRE WITH DELIVERY	570	L
PAINT TRFC:BLACK;5 L	PAINT, TRAFFIC: COLOR: BLACK, CONTAINER: 5 L	100	EA
PAINT WTR:WHITE;20 L;PVA;ACRYLIC	PAINT, WATER: COLOR: WHITE, CONTAINER: 20 L, PHYSICAL FORM: PVA, SPECIFIC USE: INTERIOR/EXTERIOR, FINISH: ACRYLIC	1 014	EA
PAINT TRFC:RED;5 L	PAINT, TRAFFIC: COLOR: RED, CONTAINER: 5 L	40	EA
PAINT TRFC:WHITE;5 L	PAINT, TRAFFIC: COLOR: WHITE, CONTAINER: 5 L	100	EA
PAINT TRFC:YELLOW;5 L	PAINT, TRAFFIC: COLOR: YELLOW, CONTAINER: 5 L	151	EA
TRAY:PAINT ROLLER;ROLLERS	TRAY: PAINT ROLLER, APPLICATION: ROLLERS	1 000	EA
PAINT:ENAMEL;ULTRA MARINE;HIGH GLOSS	PAINT: TYPE: ENAMEL, COLOR: ULTRA MARINE, FINISH: HIGH GLOSS, CONTAINER: CAN 5 L, APPLICATION: BRUSH/ROLLER/SPRAY; SUPPL P/N: A32-7; NOTE; MATERIAL DATA SHEET REQUIRE WITH DELIVERY	1 000	L
PAINT:LIBRA SHEEN;IVORY;5 L	PAINT: TYPE: LIBRA SHEEN, COLOR: IVORY, CONTAINER: 5 L	1 416	EA
PAINT:QUICK DRY;BLUE;MATT;CAN	PAINT: TYPE: QUICK DRY, COLOR: BLUE, FINISH: MATT, CONTAINER: CAN, APPLICATION: BATTERY TERMINAL; NEG; NOTE: MSDS REQUIRED ON DELIVERY	5	EA
PAINT:QUICK DRY;RED;MATT;CAN	PAINT: TYPE: QUICK DRY, COLOR: RED, FINISH: MATT, CONTAINER: CAN, APPLICATION: BATTERY TERMINAL; POS; NOTE: MSDS REQUIRED ON DELIVERY	10	EA
ROLLER:PAINT REFILL;MOHAIR 2	ROLLER: PAINT REFILL, MOHAIR 2	32	EA

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse Scope of work for Paint

THINNER PAINT:TRAFFIC;5 L	THINNER, PAINT: TRAFFIC, CONTAINER: 5 L	275	EA
PAINT:AL	PAINT: TYPE: AL; MANUF P/N: PAL 1	190	L
PAINT PRMR:UNDERCOAT;5 L;WHITE	PAINT, PRIMER: TYPE: UNDERCOAT; CONTAINER: 5 L; COLOR: WHITE; SUPPL P/N: HU201	750	L
PAINT OIL:ENAMEL;GREEN BRILLIANT;5 L	PAINT, OIL: ENAMEL, COLOR: GREEN BRILLIANT, CONTAINER: 5 L; SUPPL P/N: HG40	50	L
PAINT OIL:ENAMEL;YELLOW GOLDEN;CAN 5 L	PAINT, OIL: TYPE: ENAMEL, COLOR: YELLOW GOLDEN, CONTAINER: CAN 5 L, FINISH: GLOSS, SPECIFIC USE: EXTERIOR/INTERIOR, DRYING SPEED: FAST, APPLICATION METHOD: BRUSH OR ROLLER, SPECIFICATION: SABS 630 TYPE 1; SUPPL P/N: G6; NOTE: MATERIAL DATA SHEET REQUIRE WITH DELIVERY	225	L
PAINT OIL:ENAMEL;GOLDEN BROWN;CAN 5 L	PAINT, OIL: TYPE: ENAMEL; COLOR: GOLDEN BROWN; CONTAINER: CAN 5 L; FINISH: GLOSS; SPECIFIC USE: EXTERIOR/INTERIOR; DRYING SPEED: FAST; APPLICATION METHOD: BRUSH OR ROLLER; SUPPL P/N: G17; NOTE; MATERIAL DATA SHEET REQUIRE WITH DELIVERY	25	L
THINNER PAINT:ENAMEL;5 L;TH77	THINNER, PAINT: TYPE: ENAMEL, CONTAINER: 5 L; REFERENCE NO: TH77; NOTE: MATERIAL SAFETY DATA SHEET REQUIRE WITH DELIVERY	130	L
THINNER PAINT:COASTCOTE;5 L;SNK	THINNER, PAINT: TYPE: COASTCOTE, CONTAINER: 5 L; REFERENCE NO: SNK; NOTE: MATERIAL SAFETY DATA SHEET REQUIRE WITH DELIVERY	265	L
PAINT PRMR:GALVANISED;5 L;YELLOW	PAINT, PRIMER: TYPE: GALVANISED, CONTAINER: 5 L, COLOR: YELLOW; SUPPL P/N: GIP 1; NOTE: MATERIAL SAFETY DATA SHEET REQUIRE WITH DELIVERY	10	L

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Business Management System

Supply Chain Management

Warehouse Scope of work for Paint


COATING INSLTN:VARNISH;TIN;5 L	COATING, INSULATION: TYPE: VARNISH; CONTAINER: TIN; QUANTITY: 5 L; COLOR: YELLOW/LIGHT BROWN; SPECIFICATION: ISO14001; REFERENCE NO: ISONEL 31J	50	L
PAINT OIL:RED SIGNAL;SPRAY	PAINT, OIL: COLOR: RED SIGNAL; APPLICATION METHOD: SPRAY	500	EA
PAINT OIL:YELLOW;SPRAY	PAINT, OIL: COLOR: YELLOW, APPLICATION METHOD: SPRAY	50	EA
PAINT OIL:AEROLAC;ORANGE;GLOSS;FAST	PAINT, OIL: TYPE: AEROLAC, COLOR: ORANGE, CONTAINER: CAN AEROSOL 300 ML, FINISH: GLOSS, SPECIFIC USE: EXTERIOR/INTERIOR, DRYING SPEED: FAST, APPLICATION METHOD: SPRAY; NOTE; MATERIAL DATA SHEET REQUIRE WITH DELIVERY	5	EA
COATING INSLTN:RED VARNISH;TIN;5 L;VA42	COATING, INSULATION: TYPE: RED VARNISH, CONTAINER: TIN, QUANTITY: 5 L, SPECIFICATION: DIN51757; REFERENCE NO: VA42; ELMOTHERM; SINGLE COMPONENT, ANTI-TRACKING, FUNGICIDAL VARNISH, SUITABLE FOR TRANSFORMERS, MOTORS AND WINDINGS; NOTE ! MATERIAL SAFETY DATA SHEET REQUIRE WITH DELIVERY	215	L
COATING INSLTN:GREY VARNISH;TIN;5 L	COATING, INSULATION: TYPE: GREY VARNISH, CONTAINER: TIN, QUANTITY: 5 L, SPECIFICATION: DIN51757; REFERENCE NO: VA39; ELMOTHERM; SINGLE COMPONENT, ANTI-TRACKING, FUNGICIDAL VARNISH, SUITABLE FOR TRANSFORMERS, MOTORS AND WINDINGS; NOTE ! MATERIAL SAFETY DATA SHEET REQUIRE WITH DELIVERY	741	L
THINNER PAINT:XYLENE;5 L;S27	THINNER, PAINT: TYPE: XYLENE, CONTAINER: 5 L; REFERENCE NO: S27; NOTE: MATERIAL SAFETY DATA SHEET REQUIRE WITH DELIVERY	206	L

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Rotek Industries SOC Ltd.

Complied By: Cynthia Tsotetsi

Signature.....

Date...12/05/2023.....

Approved By: Boitshoko Mokolobate

Signature.....

Date...12/05/2023.....

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom RoteK Industries SOC Ltd.