

## **Annexure A:**

**\*\*This is strictly an example of showcasing the specifications met for verification by the Bid Evaluation Committee:**

<b>Part Number</b>	<b>Description</b>	<b>QTY</b>
[210-BDZY]	<b>PowerEdge R760 Server</b>	<b>1</b>
[461-AAIG]	<b>Trusted Platform Module 2.0 V3</b>	<b>1</b>
[404-BBFB]	<b>2.5" Chassis with 8 Universal Drive Slots (SAS/SATA/NVME), Front PERC 11, 2 CPU</b>	<b>1</b>
[338-CPBY]	<b>Intel® Xeon® Silver 4509Y 2.6G, 8C/16T, 16GT/s, 22.5M Cache, Turbo, HT (125W) DDR5-4400</b>	<b>1</b>
[338-CPBY] [379-BDCO]	<b>Intel® Xeon® Silver 4509Y 2.6G, 8C/16T, 16GT/s, 22.5M Cache, Turbo, HT (125W) DDR5-4400</b>	<b>1</b>
[412-ABCN]	<b>Heatsink for 2 CPU configuration (CPU less than or equal to 165W)</b>	<b>1</b>
[370-AAIP]	<b>Performance Optimized</b>	<b>1</b>
[370-BBRX]	<b>5600MT/s RDIMMs</b>	<b>1</b>
[370-BBRY]	<b>(2) 32GB RDIMM, 5600MT/s, Dual Rank</b>	<b>2</b>
[780-BCDS]	<b>C7, Unconfigured RAID for HDDs or SSDs (Mixed Drive Types Allowed)</b>	<b>1</b>
[405-AAZB] [750-ADWP]	<b>PERC H755 with rear load Brackets</b>	<b>1</b>
[400-AVFE]	<b>(3) 1.2TB Hard Drive ISE SAS 12Gbps 10k 512n 2.5in Hot-Plug</b>	<b>3</b>
[750-AABF]	<b>Power Saving Dell Active Power Controller</b>	<b>1</b>
[800-BBDM]	<b>UEFI BIOS Boot Mode with GPT Partition</b>	<b>1</b>
[387-BBEY]	<b>No Energy Star</b>	<b>1</b>
[750-ADGK]	<b>Standard Fan x6</b>	<b>1</b>

[450-AKKS]	<b>Dual, Hot-Plug, Power Supply FTR, 1100W MM (100-240Vac) Titanium, Redundant (1+1)</b>	<b>1</b>	
[450-AADY]	<b>(2) Rack Power Cord 2M (C13/C14 10A)</b>	<b>2</b>	
[330-BBXY]	<b>Riser Config 2, 2x8 FH Slots (Gen4), 4x8 FH Slots (Gen5), 2x16 LP Slots (Gen4)</b>	<b>1</b>	
[329-BKCJ]	<b>Motherboard supports ONLY CPUs below 250W (cannot upgrade to CPUs 250W and above), MLK</b>	<b>1</b>	
[540-BCOB]	<b>Broadcom 5720 Quad Port 1GbE BASE-T Adapter, OCP NIC 3.0</b>	<b>1</b>	
[540-BDKD]	<b>Broadcom 5720 Dual Port 1GbE LOM</b>	<b>1</b>	
[470-AEYU]	<b>No Cables Required, No GPU Blanks</b>	<b>2</b>	
[321-BHMY] [325-BEVI]	<b>PowerEdge 2U Standard Bezel</b>	<b>1</b>	
[329-BERC]	<b>BOSS Blank</b>	<b>1</b>	
[611-BBBF]	<b>No Operating System</b>	<b>1</b>	
[605-BBFN]	<b>No Media Required</b>	<b>1</b>	
[528-CTIC]	<b>iDRAC9, Enterprise 16G</b>	<b>1</b>	
[350-BBYX]	<b>No Quick Sync</b>	<b>1</b>	
[379-BCSF]	<b>iDRAC,Factory Generated Password</b>	<b>1</b>	
[379-BCQX]	<b>iDRAC Service Module (ISM), NOT Installed</b>	<b>1</b>	
[379-BCQY]	<b>iDRAC Group Manager, Disabled</b>	<b>1</b>	
[770-BDRQ] [770-BEKK]	<b>ReadyRails Sliding Rails With Cable Management Arm</b>	<b>1</b>	
[631-AACK]	<b>No Systems Documentation, No OpenManage DVD Kit</b>	<b>1</b>	
[340-DKCH]	<b>PowerEdge R760 Shipping EMEA1 (English/French/German/Spanish/Russian/Hebrew)</b>	<b>1</b>	

[340-DJQY]	<b>PowerEdge R760 Shipping Material</b>	<b>1</b>	
[343-BBUC]	<b>PowerEdge R760 CE and CCC Marking, No BIS Marking</b>	<b>1</b>	
[379-BFFD]	<b>No HBM</b>	<b>1</b>	
[293-10049]	Order Configuration Shipbox Label (Ship Date, Model, Processor Speed, HDD Size, RAM)	1	
[817-BBBP]	Decline Selection	1	
[709-BBIM]	Basic Next Business Day 36 Months, 36 Month(s)	1	
[865-BBMY]	ProSupport and Next Business Day Onsite Service Initial, 36 Month(s)	1	
[883-BBFN]	No Field Deployment Customer Install Required	1	
[883-17666]	Infrastructure Deployment Selected	1	
[293-10025]	Asset Tag - ProSupport (Website, barcode, Onboard MacAddress)	1	