

								
TYPE	D2F		C2F		E2		E1	
NUMBER	W01 TO W07, W11 TO W15, W16 TO W19, W26 TO W33 NO REQD: 21		W08, W20/21, W23 NO REQD: 4		W08/09, W21, W25 NO REQD: 4		W24, W26 TO W29 NO REQD: 4	
FRAME	STANDARD STEEL RESIDENTIAL OPEN OUT, SABS APPROVED		STANDARD STEEL RESIDENTIAL OPEN OUT, SABS APPROVED		STANDARD STEEL RESIDENTIAL OPEN OUT, SABS APPROVED		STANDARD STEEL RESIDENTIAL OPEN OUT, SABS APPROVED	
GLASS	4mm CLEAR FLOAT GLASS WITH STEEL WINDOW PUTTY		4mm CLEAR FLOAT GLASS W10/23 4mm OPAQUE GLASS W022 WITH STEEL WINDOW PUTTY		4mm CLEAR FLOAT GLASS W08/09 4mm OPAQUE GLASS W21/25 WITH STEEL WINDOW PUTTY		4mm OPAQUE GLASS WITH STEEL WINDOW PUTTY	
FITTINGS	STANDARD BRASS FITTINGS		STANDARD BRASS FITTINGS		STANDARD BRASS FITTINGS		STANDARD BRASS FITTINGS	
BURGLAR BARS	FACTORY FITTED		FACTORY FITTED		FACTORY FITTED		FACTORY FITTED	
FINISH	GALVANISED NO PAINTING REQUIRED		GALVANISED NO PAINTING REQUIRED		GALVANISED NO PAINTING REQUIRED		GALVANISED NO PAINTING REQUIRED	
NOTES	HEAVY STEEL SECTION		HEAVY STEEL SECTION		HEAVY STEEL SECTION		HEAVY STEEL SECTION	
SCALE 1:50		WINDOW SCHEDULE						

ING. TEKENINGNOMMER ENG. DRAWING NUMBER  2426 - G03	GETAL VELLE No. SHEETS
--	---------------------------

	SICK ROOM NO REQ.	STAFF TOILETS NO REQ.	KITCHEN NO REQ.
METROUSE CHINA 'AQUASAVE' LOW LEVEL SUITE CODE:750151, WASHDOWN PAN AND MATCHING 6 LT 3850 CISTERNE COMPLETE FITMENTS AND FLUSHPIPE. 1 COBRA 15mm FULLWAY BALLCOCK	1	4	
STEEL SINGLE BOWL DROP IN SINK, SIZE 1200 x 536mm WITH URED FROM GRADE 304 STAINLESS STEEL WITH COBRA C.P. COBRA STAR HI-WAIST PILLAR TAP TYPE 1 (BS 5412).			1
OVERALL 415 x 315 x 275mm, SUPPLIED WITH 38mm C.P. DE: 878/20, C.P. TOP INLET SPREADER CODE: 854320, HANGING CO, COMPLETE WITH COBRA CP FLUSHWAVE FMS300			
CEMIC FRECLAY 'SPRINGBOO' BASIN 550 x 400mm CODE:7031 DRATED OVERFLOW AND CHAINSTAY HOLE FITTED ON 2 CAST IRON 30, SILICON SEAL BETWEEN WALL AND BASIN. 1 COBRA 15mm 15 AND FITTED WITH RESTRICTION WASHER, COBRA 32mm C.P. 5 AND ANTI THEFT PLUG CODE: 356-32 COBRA C.P. BOTTLE BRA 15mm FULLWAY BALLCOCK CODE: 107515	3	3	
2mm WHITE GLAZED CERAMIC TILES, 6 TILES LONG x 3 TILES LENGTH OF WORKTOPS AND SINK x 3 TILES HIGH IN KITCHEN	3	3	1
EL MIRROR, 300x400mm, ITEM NO. CHR91 401, MANUFACTURED STAINLESS STEEL WITH HIGH POLISH FINISH AND WITH 4 MIRROR SCREWS	3	3	
HOLDER, SURFACE MOUNTED, ITEM NO. STRX 671, MANUFACTURED STEEL, SATIN FINISH, AND WITH CYLINDER LOCK	1	4	
ER SURFACE MOUNTED, ITEM NO. STRX 618, MANUFACTURED LESS STEEL, SATIN FINISHED, AND WITH CYLINDER LOCK	3	3	
DISPENSER, SURFACE MOUNTED, ITEM NO. STRX 600, 18/10 1.2mm STAINLESS STEEL, SATIN FINISH, AND WITH	3	3	

[illegible]

SEALS ALLS MINIMUM GOGGE GUTTERS WITH BAKED ENGLISH FINISH AND FIXED TO SUPPLIERS SCHEDULE WITH 100 x 75mm POLYETHYLENE DOWNPINS WITH BAKED ENGLISH FINISH AND FIXED TO SUPPLIERS SCHEDULE

VERANDA WALKWAY:

100mm THICK CONCRETE SLAB (20 MPA) REINFORCED WITH MESH REB. 139, SET 25mm ABOVE FINISH. REINFORCING BARS USE GREEN DPC ON 50mm TREATED AND RAMMED RIVER SAND ON FILL COMPACTED TO 95% MOAD ASHTO. 100mm THICK POLYMER SILL AWAY ON WALL AND CAST IN ALTERNATE PANELS OF 2000mm, 2000mm AND 2000mm.

POLYISOPHENE SEALANT WITH BACKING BACKING STRIP AND SFT BOARD

CONCRETE APRONS / CHANNELS:

100mm THICK 25 MPA CONCRETE APRONS LAID 250mm ABOVE FINISH AND 1000 TO 1500mm. CAST ALTERNATE PANELS WITH EXPANSION JOINTS AT 1000mm. POLYISOPHENE SEALANT TO MOAD ASHTO 95% EXPANSION JOINTS TO BE SEALED WITH 10mm POLYISOPHENE.

DOORS

REFER TO DOOR SCHEDULE

WINDOWS:

REFER TO WINDOW SCHEDULE

WINDOW SILLS:

EXTERNAL SILLS TO BE ROLLER COULSE FREE FACE BRICK SET AT AN ANGLE OF 15 DEGREES TO THE VERTICAL. WEATHER PROOF MEMBRANE BELOW ALL SILLS INTERNAL SILLS TO BE WEATHER PROOF MEMBRANE (PRODUCT NO. 031-059) COMPLETE WITH FINING LOGS AND SELF TAPPING SCREWS

CHALKBOARD

4800 x 1140mm GREEN CHALKBOARD TO COMPLY WITH CKS 38-1980 SUPPLIED COMPLETE WITH CHALK RAILS ONE UNIT. CHALKBOARD TO BE MOUNTED TO WALL WITH 100mm

### GENERAL SPECIFICATION NOTES

GENERAL SPECIFICATION NOTES