

**Technical Specifications for Hydraulic Power Packs for Lines and Servitudes**

	<b>Imperial</b>	<b>Metric</b>
<b>Length</b>	44.68 in	1135 mm
<b>Width</b>	20.86 in	530 mm
<b>Height</b>	30.71 in	780 mm
<b>Weight</b>	473.99 lbs	215 kg
<b>Pull Pressure</b>	8,000 PSI	55.20 MPa
<b>Return Pressure</b>	5,000 PSI	34.50 MPa
<b>Power Supply</b>	Diesel/Electric 12VDC, 50Hz	
<b>Diesel Motor</b>	296 cc, 4 Stroke 6.0 hp, Direct Fuel Injected Intake System	
<b>Bore x Stroke</b>	3.07 x 2.52	78 x 64mm
<b>Displacement</b>	0.296 L	
<b>Fuel Tank Capacity</b>	0.92 gal	3.5 L
<b>Starting System</b>	Recoil Manual Start / Electric Start	
	<b>Minimum</b>	<b>Maximum</b>
<b>Normal Speed</b>	3,000 rpm	3,600 rpm
<b>Rated Output</b>	4.0 kW / 5.5 hp	4.4 kW / 6.0 hp
<b>Cooling System</b>	Forced air cooled by flywheel fan	
<b>Fuel</b>	Diesel (10ppm-50ppm)	
<b>Fuel Consumption</b>	0.78 L p/h	
<b>Lubricating Oil</b>	SAE10W40 (above CC grade)	
<b>Lubrication System</b>	Pressure splash	
<b>Hydraulic Oil</b>	ISO VG 46 or Equivalent	
<b>Oil Flow Volume</b>	2.6 ℓ /min	