

**Compliance Specification Sheet: Supply and delivery of 2 V, 250 Ah
Maintenance-Free Gel type Batteries on a once of period.**

Name of the Bidder:

Tender Number:



COMPLIANCE SPECIFICATION SHEET

1 SPECIFICATIONS OF THE WORK OR PRODUCTS OR SERVICES REQUIRED

No.	Specification Description	PRASA'S Evaluation Compliance Response: (Yes/No)
	SECTRION 1	
1	The manufacturing design of the Maintenance-Free Gel type Batteries to be delivered for this contract shall be compliant to IEC: 61427-1 and IEC 60896-21/22 standards.	
2	Only Gel electrolyte type Batteries will be accepted (NB! valve-regulated lead (VRLA) and flooded lead and or any lead type batteries will not be accepted).	
3	Samples or catalogues of the Maintenance-Free Gel type Batteries shall be sent to the Electrical department before delivery.	
4	Gel type Batteries shall be supplied with Manuals and or catalogues.	
5	All the Maintenance-Free Gel type Batteries to be delivered shall have a Warrantee of 3-5 years and a life span Guarantee of 20 years.	
6	Each Battery set shall consist of 53 cells of 2V, 250Ah capacity.	
7	Each Cell shall be supplied with an insulated cell connector.	
8	Payment shall be done for every equipment delivered. No payment will be made for undelivered and non-compiling Equipment to the IEC standards.	
9	Only Gel electrolyte type Batteries will be accepted (NB! valve-regulated lead (VRLA) and flooded lead and or any lead type batteries will not be accepted).	
10	Samples or catalogues of the Maintenance-Free Gel type Batteries shall be sent to the Electrical department before delivery.	

**Compliance Specification Sheet: Supply and delivery of 2 V, 250 Ah
Maintenance-Free Gel type Batteries on a once of period.**



Name of the Bidder:

Tender Number:

11	Gel type Batteries shall be supplied with Manuals and or catalogues.	
12	All the Maintenance-Free Gel type Batteries to be delivered shall have a Warrantee of 3-5 years and a life span Guarantee of 20 years.	
13	Each Battery set shall consist of 53 cells of 2V, 250Ah capacity.	
14	Each Cell shall be supplied with an insulated cell connector.	
15	Payment shall be done for every equipment delivered. No payment will be made for undelivered and non-compiling Equipment to the IEC standards.	
16	Normal Voltage: 2V	
17	capacity: 250AH	
18	Deep-cycle gel type (NB! Stationary Gel type will not be accepted)	
19	low discharge rate	
20	design life: 20 years at 20°C	
21	Designed floating service life: >20 years @ 25 °C/77 °F.	
22	Cyclic usage: 80% DOD >2000 cycles.	