

UPGRADING OF THE TWEEFONTEIN K WASTE WATER TREATMENT WORKS - PACKAGE 1

ITEM No	PAYMENT CLAUSE	DESCRIPTION	UNIT	QUANTITY	RATE	AMOUNT
2	SABS 1200C	SECTION 2: SITE CLEARANCE				
	8.2.1	Clear and grub:				
2.1		a) 2m wide for pipelines	m	15515		
2.2		b) Other areas as directed by the Engineer	ha	1		
2.3	8.2.2	Remove and grub large trees and tree stumps over 1m and up to and including 2m	No.	10		
2.5	PSC 8.2.10	Remove topsoil to nominal depth of 100mm and stockpile (only where agreed with the Engineer)	m ³	3103		
2.6	8.2.12	Removal of man-made surfaces				
		a) Roads:				
2.6.1		i) Asphalt (<50mm thick and including crusher base, sub-base and subgrades layers up to 800mm deep)	m ²	100		
2.6.2		ii) Kerbing (all types)	m	30		
2.7	PSC 8.2.13	Reinstatement of man-made surfaces				
		a) Roads (Refer to PSDA 3.3.1 for reinstatement of excavation in the roadway)				
2.7.1		i) Backfill of structural layers to top of sub-base course (150mm thick)	m ²	50		
2.7.2		ii) Crushed stone base (150mm thick)	m ²	50		
2.7.3		iv) Permanent reinstatement (125mm total, 100mm Emulsion treated base with 25mm asphalt)	m ²	50		
TOTAL OF SECTION 2 CARRIED TO SUMMARY PAGE						