

ANNEXURE: SPECIFICATION OF THE REQUIRED ITEMS

| ITEM | QUANTITY | Specification |
|-------------------|----------|--|
| Wireless keyboard | 28 | <p>Model: MK345 920-006489</p> <p>Product: Keyboard</p> <p>EAN: 5099206053212</p> <p>Language: English</p> <p>Filetype: EN - 5 Manual (PDF), EN - 79 (PDF)</p> <p>System requirements</p> <p>Windows operating systems supported: Windows 10, Windows 11</p> <p>Other operating systems supported ChromeOS</p> <p>Weight & dimensions</p> <p>Keyboard dimensions (WxDxH): 186.7 x 447.2 x 21.4 mm</p> <p>Keyboard weight: 603 g</p> <p>Mouse dimensions (WxDxH): 67.9 x 38.4 x 105.4 mm</p> <p>Mouse weight: 91 g</p> <p>Packaging data</p> <p>Number of products included 3 pc(s)</p> <p>Receiver included ✓</p> <p>Batteries included ✓</p> <p>User guide ✓</p> <p>Unifying receiver ✗</p> <p>Package weight 960 g</p> <p>Package height 45 mm</p> <p>Package width 193 mm</p> <p>Package depth 531 mm</p> <p>Receiver weight 2 g</p> <p>Receiver dimensions (WxDxH) 14.4 x 6.6 x 18.7 mm</p> <p>Keyboard</p> <p>Numeric keypad ✓</p> <p>Frequency band 2.4 GHz</p> <p>Hot keys ✓</p> <p>Device interface USB</p> <p>Recommended usage Universal</p> <p>Keyboard layout QWERTY</p> |

ANNEXURE: SPECIFICATION OF THE REQUIRED ITEMS

| | | | | |
|--|--|--------------------------------|------------------|-------------|
| | | Connectivity | technology | Wireless |
| | | Keyboard form factor | Full-size (100%) | |
| | | Keyboard language | English | |
| | | Purpose | PC/Server | |
| | | Keyboard key switch | - | |
| | | Pointing device | X | |
| | | USB hub | X | |
| | | Fingerprint reader | X | |
| | | On/off switch | ✓ | |
| | | Multimedia keys | ✓ | |
| | | Spill-resistant up to | 60 ml | |
| | | Design | | |
| | | Wrist rest | ✓ | |
| | | Keyboard style | Straight | |
| | | Product colour | Black | |
| | | Backlight | X | |
| | | Protection features | Spill resistant. | |
| | | Adjustable keyboard height | ✓ | |
| | | Features | | |
| | | Wireless range | 10 m | |
| | | Plug and Play | ✓ | |
| | | Mouse | | |
| | | Mouse battery type | | AA |
| | | Number of batteries (mouse) | | 1 |
| | | Mouse included | | ✓ |
| | | Movement detection technology | | Optical |
| | | Movement resolution | | 1000 DPI |
| | | Buttons quantity | | 3 |
| | | Scroll | | ✓ |
| | | Scroll type | | Ball |
| | | Mouse battery life | | 18 month(s) |
| | | Power | | |
| | | Keyboard battery type | | AAA |
| | | Number of batteries (keyboard) | | 2 |
| | | Battery type | | AAA |
| | | Battery technology | | Alkaline |
| | | Number of batteries supported | | 2 |
| | | Power source type | | Battery |
| | | Service life of battery | | 36 month(s) |

ANNEXURE: SPECIFICATION OF THE REQUIRED ITEMS

| | | |
|----------------------|----|---|
| | | Logistics data Master (outer) case length 202 mm Master (outer) case height 546 mm Master (outer) case gross weight 4210 g Master (outer) case width 190 mm Harmonized System (HS) code 84716060 |
| iPad | 10 | Weight: 688g Dimensions: 280.6 x 214.9 x 6.4mm OS: iPadOS 16 Screen size: 12.9-inch Resolution: 2048 x 2732 pixels CPU: Apple M2 Storage: 128GB/256GB/512GB/1TB/2TB microSD slot: No Battery: Up to 10 hours Rear camera: 12MP + 10MP + LiDAR Front camera: 12MP |
| Small Office Printer | 1 | Main Unit Core Functions Standard: Print, Copy, Scan, Fax, Send (Lite) Item Code 3101C011 Processor Custom Processor Control Panel 5" Color Touch Panel Memory 1 GB Standard Interface Connection USB 2.0 x2 (Host), USB 2.0 x1 (Device) High-Speed, 10/100/1000Base-T Ethernet (Network), Wi-Fi 802.11b/g/n, Wi-Fi® Direct Connection, Near Field Communication Paper Capacity (Letter, 20 lb. Bond) Standard: 300 Sheets Paper Sources (Letter, 20 lb. Bond) Standard: 250-sheet Paper Cassette, 50-sheet Stack Bypass Optional: 550-sheet Paper Cassette (Cassette Unit AF-1) Maximum: 850 Sheets Paper Output Capacity (Letter, 20 lb. Bond) Standard: 75 Sheets Supported Media Types Cassettes: Thin, Plain, Recycled, Color, Thick, Coated, |

ANNEXURE: SPECIFICATION OF THE REQUIRED ITEMS

| | | |
|--|--|---|
| | | <p>Label, Letter, Envelope (10 Envelopes)</p> <p>Stack Bypass: Thin, Plain, Recycled, Color, Thick, Coated,</p> <p>Label, Letter, Envelope (1 Envelope)</p> <p>Supported Media Sizes</p> <p>Cassettes: A4, A5, B5, Letter, Legal, Statement, Executive, Envelope: COM10, Monarch, C5, DL, Custom (Min. 3" x 5" to Max. 8.5" x 14")</p> <p>Stack Bypass: Letter, Legal, Statement, Executive Envelope: COM10, Monarch, C5, DL Custom (Min. 3" x 5" to Max. 8.5" x 14")</p> <p>Supported Media Weights</p> <p>Cassettes: 16 lb. Bond to 53 lb. Bond (60 to 200 g/m2)</p> <p>Stack Bypass: 16 lb. Bond to 53 lb. Bond (60 to 200 g/m2)</p> <p>Warm-up Time</p> <p>From Power On: 13 Seconds or Less</p> <p>From Sleep Mode:</p> <p>6.1 Seconds or Less</p> <p>Dimensions (W x D x H)</p> <p>Standard (Desktop):</p> <p>18.8" x 18.8" x 18.4"</p> <p>(478 mm x 478 mm x 467 mm)</p> <p>Box: 23.7" x 18.8" x 23.2"</p> <p>(602 mm x 479 mm x 589 mm)</p> <p>Installation Space (W x D x H)</p> <p>Standard (Desktop):</p> <p>21.4" x 43.8" x 29"</p> <p>(544 mm x 1,112 mm x 736 mm)</p> <p>Fully Configured:</p> <p>21.4" x 43.8" x 34.1"</p> <p>(544 mm x 1,112 mm x 866 mm)</p> <p>Weight2</p> <p>Unit: Approx. 64 lb. (29.0 kg)</p> <p>Boxed Weight: Approx. 76.1 lb.(35 kg)</p> <p>Supported OS</p> <p>Windows 7/Windows 8.1/Windows 10/Windows Server 2008/Windows Server 2008 R2/Windows Server 2012/Windows Server 2012 R2/Windows Server 2016 / Mac OS X v10.9.5 (or later)</p> |
|--|--|---|

ANNEXURE: SPECIFICATION OF THE REQUIRED ITEMS

| | | |
|--|--|--|
| | | <p>What Comes In The Box</p> <p>MF743Cdw Product, Cartridge 055 CMY Starter: 1,200 Yield/Black Standard: 2,300 Yield, Power Cord, Telephone Cable, Starter Guide, User Software DVD-ROM, Warranty Card</p> <p>Print Specifications</p> <p>Printing Method</p> <p>Laser Beam Printing</p> <p>Print Speed³</p> <p>Up to 28 ppm (Letter); Up to 22.9 ppm (Legal)</p> <p>First-Print-Out Time</p> <p>Approx. 7.5 Seconds</p> <p>Recommended Monthly Page Volume</p> <p>750 - 4,000 Pages</p> <p>Print Resolution (dpi)</p> <p>600 x 600</p> <p>Standard Page Description Languages</p> <p>UFR II</p> <p>Double-Sided Printing</p> <p>Automatic (Standard)</p> <p>Direct Print</p> <p>Available from USB Memory (JPEG, TIFF, PDF)</p> <p>Printing from Mobile and Cloud-based Services⁴</p> <p>Apple® AirPrint®, PRINT Business, Mopria™ Print Service, Google Cloud Print™⁵</p> <p>Copy Specifications</p> <p>Copy Speed</p> <p>Up to 28 ppm (Letter); Up to 22.9 ppm (Legal)</p> <p>First-Copy-Out Time (Letter)</p> <p>Platen: 9.5 seconds/11.1 seconds (BW/Color)</p> <p>ADF: 9.9 seconds/11.8 seconds (BW/Color)</p> <p>Copy Resolution (dpi)</p> <p>600 x 600</p> <p>Copy Size</p> <p>Platen: Up to Letter</p> <p>ADF: Up to Legal</p> <p>Multiple Copies</p> <p>Up to 999 Copies</p> <p>Magnification</p> <p>25% - 400% (1% Increments)</p> <p>Preset Reductions</p> <p>25%, 50%, 64%, 78%</p> <p>Preset Enlargements</p> <p>129%, 200%, 400%</p> <p>Copy Features</p> <p>Paper Setting, Favorite Setting, Two-sided, Original Type</p> |
|--|--|--|

ANNEXURE: SPECIFICATION OF THE REQUIRED ITEMS

| | | |
|--|--|---|
| | | <p>Selection, Cancel, N-on-1, Density Adjustment, Sharpness, Erase Frame, Collate, Copy ID Card Scan Specifications Type Single-Pass Duplexing Automatic Document Feeder Document Feeder Paper Capacity 50 Sheets (20 lb. Bond) Document Feeder Supported Media Sizes Legal, Letter, Statement Document Feeder Supported Media Weights 13-28 lb. Bond (50-105 g/m2) Platen Acceptable Originals Sheet, Book Pull Scan ScanGear MF for TWAIN, and WIA Scan Resolution (dpi) Push Scan: Up to 300 x 600 Pull Scan: Up to 600 x 600 Scan-to-Mobile Devices PRINT Business Scan Speed (Letter) Single-sided: 14/28 ipm (300 x 600 dpi) (Color/BW) Double-sided: 27/51 ipm (300 x 600) (Color/BW) Memory Media Standard USB Memory (JPEG, TIFF, PDF) Send Specifications Destination Email/Internet FAX (SMTP), SMB, FTP Address Book LDAP (50)/Local (300)/Speed Dial (281) Send Resolution (dpi) 600 x 600 (Pull Scan), 196 x 204 (iFax), 300 x 300 (Other) Communication Protocol File: FTP, SMB Email/iFax: SMTP, POP3, iFax (Simple) File Format Standard: TIFF, JPEG, PDF (Compact, Searchable) Optional: PDF (Encrypted, Digital Signature) Fax Specifications Modem Speed Super G3: 33.6 kbps G3: 14.4 kbps Compression Method MH, MR, MMR, JBIG Resolution (dpi)</p> |
|--|--|---|

ANNEXURE: SPECIFICATION OF THE REQUIRED ITEMS

| | | |
|--|--|---|
| | | <p>400 x 400, 200 x 400, 200 x 200, 200 x 100</p> <p>Sending/Recording Size</p> <p>Statement to Legal</p> <p>Fax Memory</p> <p>Up to 512 Pages</p> <p>Speed Dials</p> <p>Max. 281</p> <p>Group Dials/Destinations</p> <p>Max. 299 Dials</p> <p>Sequential Broadcast</p> <p>Max. 310 Addresses</p> <p>Memory Backup</p> <p>Yes</p> <p>Fax Features</p> <p>RX Mode, Resolution, Two-sided Original, Density, Sharpness, Favorite Settings, Duplex Fax</p> <p>Security Specifications</p> <p>Authentication</p> <p>Standard: Department ID Authentication</p> <p>Network</p> <p>Standard: IP/MAC Address Filtering, IPSEC, TLS</p> <p>Encrypted Communication, SNMP V3.0, IEEE 802.1X (Wired Only), IPv6, SMTP</p> <p>Authentication, POP Authentication, POP Authentication before SMTP</p> <p>Document</p> <p>Standard: Secure Print</p> <p>Wi-Fi Authentication Methods</p> <p>Wi-Fi</p> <p>Infrastructure</p> <p>Mode: WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES)</p> <p>Wi-Fi Access</p> <p>Point: WPA2-PSK (AES)</p> <p>Environmental Specifications</p> <p>Operating Environment</p> <p>Temperature: 50 to 86° F</p> <p>Humidity: 20 to 80% RH (no condensation)</p> <p>Power Requirements</p> <p>AC 120-127 V:6.5 A, 60 Hz</p> <p>Power Consumption</p> <p>Maximum: Approx. 1470 W</p> <p>Standby: Approx. 20.5 W</p> <p>Sleep Mode: Approx. 0.6 W</p> <p>Typical</p> <p>Electricity</p> <p>Consumption</p> <p>(TEC) Rating:</p> |
|--|--|---|

ANNEXURE: SPECIFICATION OF THE REQUIRED ITEMS

| | | |
|--------------------------------------|---|--|
| | | <p>0.31 kWh Standards ENERGY STAR® Qualified, Rated EPEAT Silver1 Extended Service Plans Available For Purchase eCarePAK (Exchange/Carry-In) extended service plans extend standard three-year limited warranty6 support to cover additional one to two years. One-Year: 5707B050 Two-Year: 5707B051</p> |
| Voice Recorder and transcription kit | 1 | <p>Connectivity Headphones: 3.5 mm; Microphone: 3.5 mm; USB: micro USB 2.0; Docking connector; Memory card slot</p> <p>Display Type: color TFT, Diagonal screen size: 2.4 inches / 6.1 cm, Resolution: 320 x 240 pixels</p> <p>Storage media Exchangeable memory card; Memory card types: SD/SDHC, up to 32 GB; Mass storage class compliant; Data transfer speed: 6.75 MB/s read speed, 5.0 MB/s write speed.</p> <p>Audio recording -Recording format: DSS/DSS Pro (Digital Speech Standard), MP3, PCM -Built-in microphones: 1 directional microphone, 1 microphone for 360 degree recording -Recording modes: DSS QP (.ds2/mono), DSS SP (.dss/mono), MP3 (.mp3/stereo), PCM Voice (.wav/mono), PCM Stereo (.wav/stereo) -Bit rate: 13.7 kbit/s (DSS SP), 28 kbit/s (DSS QP), 192 kbit/s (MP3), 353 kbit/s (PCM Voice), 705 kbit/s (PCM Stereo) -Edit modes: insert (DSS/DSS Pro), overwrite (DSS/DSS Pro, MP3, PCM), append (DSS/DSS Pro, MP3, PCM) -Recording time (4 GB memory card): 700 hours (SP), 350 hours (QP), 50 hours (MP3), 27 hours (PCM Voice), 13 hours (PCM Stereo) -Sample rate: 44.1 kHz (MP3), 22.05 kHz (PCM), 16 kHz (DSS QP), 12 kHz (DSS SP)</p> |

ANNEXURE: SPECIFICATION OF THE REQUIRED ITEMS

| | | |
|--|--|---|
| | | <p>Sound Speaker type: built-in round, dynamic speaker; Speaker diameter: 28 mm; Acoustic frequency response: 300 – 7500 Hz; Speaker output power: > 200 mW</p> <p>Power Battery type: Philips rechargeable Li-ion battery ACC8100; Battery capacity: 1000mAh; Battery lifetime: up to 30 hours of recording (DSS Pro mode); Standby time: more than 200 days; Charging time (full charge): 3 hours</p> <p>Convenience Expandable through cascading 360 degree sound pick-up Control via remote control USB powered recording Multiple language support: 5 languages Author ID setting File lock Priority setting Exchangeable memory card Voice-activated recording Automatic software updates Voice volume indicator Instant one-touch recording Voice-activated recording Firmware upgradeable Variable playback speed</p> <p>Green Specifications Compliant to 2011/65/EU (RoHS), Lead-free soldered product Meeting microphone Design: boundary layer microphone Type: electret condenser microphone Impedance: approx. 2.2 kOhm @ 1 kHz Sensitivity: -38 dBV Frequency response: 30–18,000 Hz Phantom supply voltage: 1.5–5 V/0.5 mA Connector: 3.5 mm Audio jack (for cascading): 3.5 mm Cable length: 2 m/6.5 ft. Specifications Product dimensions (W × D × H): 53 × 123 × 15 mm / 2.1 × 4.8 × 0.6 inches; Weight: 117 g / 4.1 oz including battery</p> |
|--|--|---|

ANNEXURE: SPECIFICATION OF THE REQUIRED ITEMS

| | | |
|-----------------------------|----|--|
| | | Meeting microphone Design: boundary layer microphone Type: electret condenser microphone Impedance: approx. 2.2 kOhm @ 1 kHz Sensitivity: -38 dBV Frequency response: 30–18,000 Hz Phantom supply voltage: 1.5–5 V/0.5 mA Connector: 3.5 mm Audio jack (for cascading): 3.5 mm Cable length: 2 m/6.5 ft. |
| Noise Cancelling Headphones | 28 | Model: WH-1000xm4 Type: Closed, dynamic DRIVER UNIT: 40mm, dome type (CCAW Voice coil) MAGNET: Neodymium DIAPHRAGM: Aluminum coated LCP FREQUENCY RESPONSE: 4Hz-40,000Hz FREQUENCY RESPONSE (ACTIVE OPERATION): 4Hz-40,000Hz FREQUENCY RESPONSE(BLUETOOTH® COMMUNICATION): 20Hz - 20,000Hz (44.1kHz Sampling) / 20Hz - 40,000Hz (LDAC 96kHz Sampling, 990kbps) SENSITIVITIES (DB/MW): 105dB / mW (1kHz) (when connecting via the headphone cable with the unit turned on) , 101dB / mW (1kHz) (when connecting via the headphone cable with the unit turned off) CORD TYPE: Single-sided (detachable) CORD LENGTH Headphone cable (approx. 1.2m, OFC strands, gold- plated stereo mini plug) PLUG Gold-plated L-shaped stereo mini plug WEARING STYLE Circumaural |

ANNEXURE: SPECIFICATION OF THE REQUIRED ITEMS

| | | |
|--|--|--|
| | | <p>NFC Yes</p> <p>DSEE EXTREME Yes</p> <p>PASSIVE OPERATION Yes</p> <p>Battery</p> <p>BATTERY CHARGE TIME</p> <p>Approx. 3 Hours (Full charge)</p> <p>BATTERY CHARGE METHOD</p> <p>USB</p> <p>BATTERY LIFE(CONTINUOUS MUSIC PLAYBACK TIME WITH INTERNAL MEMORY)</p> <p>Max. 30 hours(NC ON), Max. 38 hours(NC OFF)</p> <p>BATTERY LIFE(WAITING TIME)</p> <p>Max. 30 hours(NC ON), Max. 200 hours(NC OFF)</p> <p>Bluetooth® Specification</p> <p>BLUETOOTH® VERSION</p> <p>Version 5.0</p> <p>EFFECTIVE RANGE</p> <p>Line of sight approx.30ft (10m)</p> <p>FREQUENCY RANGE</p> <p>2.4GHz band (2.4000GHz-2.4835GHz)</p> <p>PROFILE</p> <p>A2DP, AVRCP, HFP, HSP</p> <p>SUPPORTED AUDIO FORMAT(S)</p> <p>SBC, AAC, LDAC</p> <p>SUPPORTED CONTENT PROTECTION</p> <p>SCMS-T</p> <p>Noise Cancelling</p> <p>NOISE CANCELING ON/OFF SWITCH</p> <p>Yes</p> <p>PERSONAL NC OPTIMIZER</p> <p>Yes</p> <p>ATMOSPHERIC PRESSURE OPTIMIZING</p> <p>Yes</p> <p>AMBIENT SOUND MODE</p> <p>Yes</p> <p>QUICK ATTENTION</p> <p>Yes</p> <p>Portable Headphone Amplifier</p> <p>VOLUME CONTROL</p> <p>Touch Sensor</p> <p>Processor/Transmitter</p> <p>INPUT(S)</p> |
|--|--|--|

ANNEXURE: SPECIFICATION OF THE REQUIRED ITEMS

| | | |
|--|--|--|
| | | <p>Stereo Mini Jack</p> <p>Colour Options</p> <p>silverblack</p> <p>What's In The Box</p> <ul style="list-style-type: none">• Carrying Case• Plug Adaptor for In-flight Use• Headphone cable (approx. 1.2m)• USB Cable: Type-C™ (approx. 20 cm) |
|--|--|--|

Tools of Trade- IT Equipment