

## **DECLARATION CERTIFICATE FOR LOCAL PRODUCTION AND CONTENT FOR DESIGNATED SECTORS**

This Standard Bidding Document (SBD) must form part of all bids invited. It contains general information and serves as a declaration form for local content (local production and local content are used interchangeably).

Before completing this declaration, bidders must study the General Conditions, Definitions, Directives applicable in respect of Local Content as prescribed in the Preferential Procurement Regulations, 2017, the South African Bureau of Standards (SABS) approved technical specification number SATS 1286:2011 (Edition 1) and the Guidance on the Calculation of Local Content together with the Local Content Declaration Templates [Annex C (Local Content Declaration: Summary Schedule), D (Imported Content Declaration: Supporting Schedule to Annex C) and E (Local Content Declaration: Supporting Schedule to Annex C)].

### **1. General Conditions**

- 1.1. Preferential Procurement Regulations, 2017 (Regulation 8) make provision for the promotion of local production and content.
- 1.2. Regulation 8.(2) prescribes that in the case of designated sectors, organs of state must advertise such tenders with the specific bidding condition that only locally produced or manufactured goods, with a stipulated minimum threshold for local production and content will be considered.
- 1.3. Where necessary, for tenders referred to in paragraph 1.2 above, a two stage bidding process may be followed, where the first stage involves a minimum threshold for local production and content and the second stage price and B-BBEE.
- 1.4. A person awarded a contract in relation to a designated sector, may not sub-contract in such a manner that the local production and content of the overall value of the contract is reduced to below the stipulated minimum threshold.
- 1.5. The local content (LC) expressed as a percentage of the bid price must be calculated in accordance with the SABS approved technical specification number SATS 1286: 2011 as follows:

$$LC = [1 - x / y] * 100$$

Where

x is the imported content in Rand

y is the bid price in Rand excluding value added tax (VAT)

Prices referred to in the determination of x must be converted to Rand (ZAR) by using the exchange rate published by South African Reserve Bank (SARB) at 12:00 on the date of advertisement of the bid as indicated in paragraph 4.1 below.

**The SABS approved technical specification number SATS 1286:2011 is accessible on [http://www.thedti.gov.za/industrial development/ip.jsp](http://www.thedti.gov.za/industrial%20development/ip.jsp) at no cost.**

1.6. A bid may be disqualified if this Declaration Certificate and the Annex C (Local Content Declaration: Summary Schedule) are not submitted as part of the bid documentation;

2. The stipulated minimum threshold(s) for local production and content (refer to Annex A of SATS 1286:2011) for this bid is/are as follows:

PROJECT NAME: ELECTRICAL AND MINOR WORKS AT MAYERTON STATION		
BOQ item no's	Description	Minimum Threshold for Local Content
	<b><u>BILL NO 2</u></b>	
	<b><u>CARPENTRY AND JOINERY</u></b>	
	<b><u>DOORS</u></b>	
	44mm thick exterior grade flush solid core timber single door with 3mm thick commercial ply on both sides with consolidated edges fitted and complying with SABS 545 in pressed steel frame. All painted in accordance with architect's colour schedules	
1	813 x 2032 x 44mm single leaf solid core with commercial veneer for paint. pricing shall include painting as per manufactures specification	100%
	44mm thick interior grade flush solid core timber single door with 3mm thick commercial ply on both sides with consolidated edges fitted and complying with SABS 545 in pressed steel frame. All painted in accordance with architect's colour schedules	
2	813 x 2032 x 44mm single leaf solid core with commercial veneer for paint. pricing shall include painting as per manufactures specification	100%
	<b><u>Level G3 bullet resistant Anti-bandit door, complete with 100 x 50 x 3mm gauge mild steel rectangular frame and 25 x 25 x 3mm MS anlg e rebates, overall size 930 x 2100mm high in powder coating and or galvinised cladding with peep hole, supplied with a 6 pin tumbler key system, mortice dead lock with an additional heavy duty magnetic lock and striker including key switch and surface mounted casing, 6 Amp power supply, push buttons and interlock system, heavy duty aluminium continuous hinge, aluminium slam bar with heavy duty door closer and D-style pull handles. Door to comply to SABS 1658-1996</u></b>	
3	Level G3 bullet resistant anti-bandit external door	100%
	<b><u>BILL NO 3</u></b>	
	<b><u>CEILING WORK</u></b>	
	6.4mm “Rhino” gypsum plaster board with H-Type pressed steel jointing	

	<b>strips</b>	
1	Ceiling including 38 x 38mm sawn softwood bandering at 450mm centres	100%
2	Extra over ceiling for 800 x 800mm trap door of 38 50mm wrought softwood rebated framing with one 38 x 38mm sawn softwood cross brander covered with ceiling board and fitted flush in opening	100%
	<b>“Rhino” gypsum plasterboard cornice</b>	
3	75mm coved cornices fixed to ceiling	100%
	<b><u>BILL NO 4</u></b>	
	<b><u>IRONMONGERY</u></b>	
	<b><u>LOCKS</u></b>	
	<b><u>Supply and install</u></b>	
1	Ultra-security heavy duty locks	100%
2	3 liver mortice lockset with handles	100%
3	Indicator door lock chrome plated	100%
	<b><u>BILL NO 5</u></b>	
	<b><u>PLUMBING WORK</u></b>	
	<b><u>SANITARY FITTINGS</u></b>	
	<b><u>SANITARY FITTINGS</u></b>	
	<b><u>Supply and install</u></b>	
1	Anti-vandal High traffic suite complete (Front flush), suite to includes CC Cistern, <b>including CC Pan and</b> and heavy duty seat.	100%
2	Close coupled suite colour White , comprising 90° outlet open rim pan with matching 9 litre front single flush cistern including lid and fitments and heavy duty seat.	100%
3	Sanitary ware white vitreous china wall mounted urinal with top inlet (code 705426) or back inlet (code 7054Z1). Overall size 600x385x380mm. Supplied with 38mm c.p. domical grating, a spreader(with a 20mm tread) and two hanger brackets	100%

4	Wall mounted white Vandal Resistant Wash Hand Basin, 330mm (w) x 310 (d) x 325mm (h). Installation as per manufacturer's specification.	100%
5	Ceramic wash hand basin colour White, size 510 x 405mm with one tap hole including integrated overflow and chain stay hole bolted to wall with two x 10mm bolts and including Classic floor mounted pedestal and sealed with silicone sealant where basin meets wall.	100%
6	50mm pipes with all connection and make good	100%
	<b>TAPS, VALVES, ETC</b>	
	<b>Supply and install</b>	
7	Pillar tap for hot and cold water	100%
8	15mm chrome plated deck mounted sink mixer with overarm swivel outlet and adjustable flanges, manufactured in accordance with SANS 226:2004 Type 1.	100%
9	Exposed type urinal flush valve with ball-o-stop, wall flange, chrome plate finish and non-hold open feature	100%
10	Flexi connector	100%
11	15 Brass Gate Valve	100%
12	Mini Ball Valve	100%
13	22mm Brass Gate Valve including cast iron valve box	100%
	<b>Extra over PVC pipes for fittings</b>	
14	110mm pan connector completely	100%
	<b>WATER SUPPLIERS</b>	
	<b>Class "O" copper pipe</b>	
15	15mm pipes	100%
16	15mm pipes chased into brick walls and make good	100%
17	22mm pipes	100%
18	22mm pipes chased into brick walls	100%
	<b>Extra over class "O" copper pipes for capillary fittings</b>	

19	15mm fitting	100%
20	22mm fitting	100%
21	15mm Tee	100%
22	22mm Tee	100%
	<b>PLATFORM MANHOLE COVERS AND FRAMES</b>	
	<b>The concrete manhole covers to be installed completely frame and cover as per the applicable Standard</b>	
23	Type 9B MD concrete lid and frame including to make good after completion	100%
	<b>CONCRETE COPING BLOCKS</b>	
	<b>25MPa/20mm Concrete</b>	
24	Reinforced 500w x 600l x 150mm thick concrete coping blocks	100%
	<b><u>BILL NO.6</u></b>	
	<b><u>METAL WORK</u></b>	
	<b>SECURITY GATES</b>	
	<b>Supply and install Burglar door</b>	
1	900 x 2100mm high Heavy duty single Burglar door and frame with 16mm steel round bar and 40 x 40 x 2.5mm square tubing as per attached drawing for single door	100%
	<b>Supply and install Burglar windows</b>	
2	12 x 12mm horizontal and vertical bars to fit 200mm W x 2000mm H	100%
	<b>PRESSED STEEL DOOR FRAMES</b>	
	<b>1.2mm double rebated frames suitable for one brick wall</b>	
3	Frame for door 813 x 2032mm high	100%
	<b>FENCING AND GATES</b>	
	<b><u>MILD STEEL PALISADE FENCE</u></b>	

4	Supply and erect 2.4m high welded mesh galvanized fence in concrete footings, complete with post, pales, ground beam, horizontal rails, fixing accessories and recess in rails to be epoxy cement Grouted.	100%
5	2.4m high x 1.5m wide welded mesh galvanized fence gate in concrete footings, complete with post, pales, ground beam, horizontal rails, fixing accessories and recess in rails to be epoxy cement Grouted.	100%
	<b><u>BILL NO.7</u></b>	
	<b><u>GLAZING</u></b>	
	<b><u>GLAZED TO STEEL WITH PUTTY</u></b>	
	<b>4mm clear float glass</b>	
1	Panes exceeding 0.1 m <sup>2</sup> and not exceeding 0.5m <sup>2</sup>	100%
	<b>4mm clear obscure glass</b>	
2	Panes exceeding 0.1 m <sup>2</sup> and not exceeding 0.5 m <sup>2</sup>	100%
	<b><u>BILL NO.8</u></b>	
	<b><u>PAINTWORK</u></b>	
	<b>PAINTWORK, ETC TO NEW WORK</b>	
	<b>ON FLOATED PLASTER</b>	
	<b>One coat professional plaster primer and two coats acrylic paint</b>	
1	On ceiling and cornices	100%
	<b>One coat wood primer, one Universal Undercoat and two coats Prasa Oakley Brown enamel paint</b>	
2	On doors	100%
	<b>ON METAL</b>	
	<b>One coat zinc chromate primer, one under coat and two coats professional white gloss enamel paint</b>	

3	On buglers, gates, door frames, window frames, gutters and down pipes	100%
	<b>PAINTWORK ETC TO PREVIOUSLY PAINTED WORK</b>	
	<b>One coat professional plaster primer and two coats acrylic paint</b>	
4	On ceiling and cornices	100%
	<b><u>BILL NO.9</u></b>	
	<b><u>TILING</u></b>	
	<b>WALL TILING</b>	
	<b>Matt Full Bodied Porcelain tiles, size 600 x 300mm x 12mm fixed to internal wall plaster backing with TAL tile adhesive mixed with TAL bonding liquid in lieu of water with joints continuous in both directions and grouted with TAL tile grout, excess grout on the surface to be cleaned with water as work proceeds.</b>	
1	On walls	100%
	<b><u>BILL NO.10</u></b>	
	<b><u>ROOF COVERING ETC</u></b>	
	<b>PROFILED METAL SHEETING AND ACCESSORIES</b>	
	<b><u>Roof sheeting to be Concealed Fix interlocking "KLIP-LOK 700", 0,58mm thick heavy industrial Z275 spelter galvanised steel sheeting with Chromadek, ColorPlus, Colourbond or Globalcoat finish to one side and Grey other side and accessories, fixed to steel purlins using SL 700 approved clips and fasteners. Cover width 700mm. High wind - 120km/h plus - loading to be considered with installation and fixing must be in accordance with manufacturer's recommendations and specifications.</u></b>	
1	Roof covering to flat roof on existing purlins	100%
2	1.25mm thick polycarbonate clear IBR sheeting's on the existing purlins completely installed as per manufactures specification	100%

	<b><u>BILL NO.2</u></b>	
	<b><u>ELECTRICAL WORK</u></b>	
	<b>Fluorescent fittings waterproofed fixture white including 2x58w T8 LED Fluorescent tubes and polycarbonate base with clear polycarbonate cover IP65</b>	
1	Waterproof polycarbonate LED 5ft 2 x58w T8 fluorescent fitting including 2 LED tubes	100%
2	1500m (5 foot) 58w Open channel LED Fluorescent fittings double tubes for ticket office building	100%
	<b>Bulkhead fittings</b>	
3	Vandal proof incandescent compact ceiling light fittings 75w power, 1210 lumens with Die cast aluminum housing and tough polycarbonate refractors	100%
4	7w LED bulk head fittings completely with bulbs	100%
	<b>High mast pole street light fitting</b>	
5	279W LED Luminaire (34460 lumen) with 3 an optical compartment with LED engine, glass protector, LED warm light with colour temperature of 3000 kelvin, gear compartment and a spigot top entry adjustable compartment. Both optical and gear compartments to be rated IP 66. 20kV/kA surge protection. The luminaire housing to be manufactured of marine grade cast aluminium (EN 1706 AC-44300). Including 1 opening tool	100%
	<b>Bridge fittings</b>	
6	125W HPS-T SE/230V C/W LAMP with 4800 lumen and the laminair to bear SANS 475 ( Complete with lamp, control gear and spigot compartment	100%
7	125W HPS BALLAST AND LAMP	100%
	<b><u>SWITCHES</u></b>	
8	Day light switches	100%
9	11 kw contactors	100%
10	White 1 lever 2 way switch	100%
11	White 2 lever 1 way switch	100%
	<b>Electrical cables</b>	



12	50mm <sup>2</sup> 4 core cable on sleeves (priced elsewhere)	90%
13	16mm <sup>2</sup> 4 core cable on sleeves (priced elsewhere)	90%
14	10mm <sup>2</sup> 4 core cable on sleeves (priced elsewhere)	90%
15	4mm <sup>2</sup> GP wires for stove and geyser	90%
16	2.5mm <sup>2</sup> GP wires (Red, white, blue, black and earth) for lights rewiring of shelters, footbridge, ablutions and access points in 3 phase system	90%
17	2.5mm <sup>2</sup> suffix cable or GP wire for plugs	90%
18	1.5mm <sup>2</sup> suffix cable or GP wire for lights	90%
	<b>Electrical casing</b>	
19	20mm galvanized SABS conduit completely with all the couplings, galvanized saddle, spacer bar assembly and heavy duty U clamps	100%
20	20mm PVC SABS conduit completely with all the couplings, saddle, spacer bar assembly and heavy duty U clamps	100%
	<b>Circuit breakers</b>	
21	10 A 1P 6KA single circuit breaker	100%
22	10 A 3P 6KA circuit breaker	100%
23	12 A 3P Contactor	100%
24	20 A 1P 6KA single circuit breaker	100%
25	20 A 3P 6KA circuit breaker	100%
26	30 A 1P 6KA circuit breaker	100%
27	30 A 2P 6KA circuit breaker	100%
28	40 A 2P 6KA circuit breaker	100%
29	60 A 3P 6KA circuit breaker	100%
30	60 A 3P AC1 Contactor	100%
31	63 A 2P 6KA circuit breaker	100%

32	63 A 3P 6KA circuit breaker	100%
33	63 A 30Ma 3P + N Earth leakage	100%
34	250 A 3P Isolator	100%
35	40 A stove Isolator	100%
36	30A Air conditioner Isolator	100%
	<b>PLUGS</b>	
37	4 x 4 Double plug	100%
38	4 x 4 single plug	100%
	<b>DB BOARDS</b>	
39	Flush mounted min distribution board 2 x 15w completely	70%
40	Lockable fiber glass water proofed 12 way CBI DB Eaves box to be mounted on external walls for platform shelters, waiting areas, access point, ablutions, etc	70%
	<b>HVAC Systems</b>	
41	Supply, install and commission new 24000 BTU split unit, inverter technology air conditioner completely with all accessories (drain pipe, amorflex, copper pipe, refrigerant, cable, communication wire, brackets, circuit breaker, isolator, etc )	70%
	<b><u>BILL NO. 3</u></b>	
	<b><u>EARTHWORKS</u></b>	
	<b><u>EXCAVATION, FILLING, ETC</u></b>	
	<b>15 Mpa/20 mm unreinforced concrete</b>	
3	15 Mpa/20mm unreinforced concrete on top of underground cable	100%

3. Does any portion of the goods or services offered have any imported content?

(Tick applicable box)

YES	<input checked="" type="checkbox"/>	NO	<input type="checkbox"/>
-----	-------------------------------------	----	--------------------------

- 3..1 If yes, the rate(s) of exchange to be used in this bid to calculate the local content as prescribed in paragraph 1.5 of the general conditions must be the rate(s) published by SARB for the specific currency at 12:00 on the date of advertisement of the bid.

The relevant rates of exchange information is accessible on [www.reservebank.co.za](http://www.reservebank.co.za)

Indicate the rate(s) of exchange against the appropriate currency in the table below (refer to Annex A of SATS 1286:2011):

Currency	Rates of exchange
US Dollar	
Pound Sterling	
Euro	
Yen	
Other	

NB: Bidders must submit proof of the SARB rate (s) of exchange used.

4. Where, after the award of a bid, challenges are experienced in meeting the stipulated minimum threshold for local content the dti must be informed accordingly in order for the dti to verify and in consultation with the AO/AA provide directives in this regard.

**LOCAL CONTENT DECLARATION**  
**(REFER TO ANNEX B OF SATS 1286:2011)**

**LOCAL CONTENT DECLARATION BY CHIEF FINANCIAL OFFICER OR OTHER LEGALLY RESPONSIBLE PERSON NOMINATED IN WRITING BY THE CHIEF EXECUTIVE OR SENIOR MEMBER/PERSON WITH MANAGEMENT RESPONSIBILITY (CLOSE CORPORATION, PARTNERSHIP OR INDIVIDUAL)**

**IN RESPECT OF BID NO. WCR/12/08/2019.....**

**ISSUED BY:** (Procurement Authority / Name of Institution):

.....NB

- 1 The obligation to complete, duly sign and submit this declaration cannot be transferred to an external authorized representative, auditor or any other third party acting on behalf of the bidder.
- 2 Guidance on the Calculation of Local Content together with Local Content Declaration Templates (Annex C, D and E) is accessible on [http://www.thdti.gov.za/industrial\\_development/ip.jsp](http://www.thdti.gov.za/industrial_development/ip.jsp). Bidders should first complete Declaration D. After completing Declaration D, bidders should complete Declaration E and then consolidate the information on Declaration C. **Declaration C should be submitted with the bid documentation at the closing date and time of the bid in order to substantiate the declaration made in paragraph (c) below.** Declarations D and E should be kept by the bidders for verification purposes for a period of at least 5 years. The successful bidder is required to continuously update Declarations C, D and E with the actual values for the duration of the contract.

I, the undersigned, ..... (full names),

do hereby declare, in my capacity as .....  
of .....(name of bidder  
entity), the following:

- (a) The facts contained herein are within my own personal knowledge.
- (b) I have satisfied myself that:
- (i) the goods/services/works to be delivered in terms of the above-specified bid comply with the minimum local content requirements as specified in the bid, and as measured in terms of SATS 1286:2011; and
- (c) The local content percentage (%) indicated below has been calculated using the formula given in clause 3 of SATS 1286:2011, the rates of exchange indicated in paragraph 4.1 above and the information contained in Declaration D and E which has been consolidated in Declaration C:

Bid price, excluding VAT (y)	R
Imported content (x), as calculated in terms of SATS 1286:2011	R
Stipulated minimum threshold for local content (paragraph 3 above)	
Local content %, as calculated in terms of SATS 1286:2011	

**If the bid is for more than one product, the local content percentages for each product contained in Declaration C shall be used instead of the table above.**

**The local content percentages for each product has been calculated using the formula given in clause 3 of SATS 1286:2011, the rates of exchange indicated in paragraph 4.1 above and the information contained in Declaration D and E.**

- (d) I accept that the Procurement Authority / Institution has the right to request that the local content be verified in terms of the requirements of SATS 1286:2011.
- (e) I understand that the awarding of the bid is dependent on the accuracy of the information furnished in this application. I also understand that the submission of incorrect data, or data that are not verifiable as described in SATS 1286:2011, may result in the Procurement Authority / Institution imposing any or all of the remedies as provided for in Regulation 14 of the Preferential Procurement Regulations, 2017 promulgated under the Preferential Policy Framework Act (PPPFA), 2000 (Act No. 5 of 2000).

**SIGNATURE:** \_\_\_\_\_

**DATE:** \_\_\_\_\_

**WITNESS No. 1** \_\_\_\_\_

**DATE:** \_\_\_\_\_

**WITNESS No. 2** \_\_\_\_\_

**DATE:** \_\_\_\_\_