

**Returnable: Annexure A – Schedule of Compliance (Non Assets Tools & PPE)**

	<b>Description and Specification</b>	<b>Schedule A (Returnable by Tender(s)</b>	<b>Photo/Picture(s) Yes/No</b>	<b>Datasheet Yes/No</b>	<b>Certificate(s) Yes/No</b>	<b>Eskom Evaluation (COMPLIANT or NON-COMPLIANT)</b>
1	Steel brush (wire brush): Engineering, general cleaning Wire brass and steel hand brushes can be used in a range of applications such as within engineering for rust removal and debris cleaning	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
2	Silicon clothes: The silicone courted clothe wipes are so easy to use. Just zip open a foil packet, pull out the silicone-saturated 8" x 10" lint-free towel and wipe down a hotstick.	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
3	Shifting spanner (580mm): Universal adjustable shifting wrench. Forged from high grade steel. Heat treated. Available in various sizes. What's in the box 1x Adjustable Wrench ...	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
4	Nylon sling (3-Ton, 1m): 3 Ton (3000Kg) flat webbing sling 1m wide can be used for many lifting modes. Our webbing lifting slings are made from 100% polyester with reinforced eyes	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
5	Nylon sling (3-Ton, 500mm): 3 Ton (3000Kg) flat webbing sling 500mm wide can be used for many lifting modes. Our webbing lifting slings are made from 100% polyester with reinforced eyes	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
6	Karabiners: Oval shaped Karabiner made of round Steel Bar. Self closing & manual locking type Karabiner. Locking by screw locking nut. Alloy Steel. OPEN CONDITION.	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
7	Pylon hooks (Red): Alloy Steel · Gate opening: 50 mm · Min breaking strength: 23kN · Gate mechanism: Double action/self locking · Weight: 473gm · En std: 362:2004 ·	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
8	Pylon hooks (Silver): Alloy Steel · Gate opening: 50 mm · Min breaking strength: 23kN · Gate mechanism: Double action/self locking · Weight: 473gm · En std: 362:2004 ·	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
9	Pylon hooks (Yellow): Alloy Steel · Gate opening: 50 mm · Min breaking strength: 23kN · Gate mechanism: Double action/self locking · Weight: 473gm · En std: 362:2004 ·	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
10	Polly Dacron rope 12mm 1 drum: Poly Dacron rope is made from polypropylene and Dacron plastic fibers. Fibers are twisted into strands and then the strands are braided into various types	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
11	Polly Dacron rope16mm 1 drum: Poly Dacron rope is made from polypropylene and Dacron plastic fibers. Fibers are twisted into strands and then the strands are braided into various types	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
12	BOOTS, SAFETY: SIZE: 4; TOE CONSTRUCTION TYPE: STRD; STL OR CARBON FIBER; COLOR: BLACK/BROWN; MATERIAL: UPPER LEATHER FULL GRAIN; STYLE: 34-232; TREAD SURFACE TYPE: SOLE RUBBER; OIL/PETROL SLIP RESISTANCE; FASTENING METHOD: LACE; SPECIFICATION: UNIQUE IDENTIFIER 240-44175132; STANDARD BOOTS TO COMPLY WITH SAFETY BOOTS ELECTRICAL TESTING SPECIFICATION 34-232; THE BOOTS TO BE DARK BROWN; WHERE IT IS NOT POSSIBLE TO OBTAIN BROWN THEN BLACK WILL BE THE ONLY ALTERNATIVE AND THE LACES SHALL MATCH THE RELEVANT BOOT COLOUR; ONLY LOCALLY PRODUCED OR MANUFACTURED TEXTILES LEATHER AND FOOTWEAR FROM LOCAL RAW MATERIAL OR INPUT WILL BE CONSIDERED; ITEM TO BE MARKED WITH SABS SANS 20345:2008 MARK OF APPROVAL; WITH PENETRATION-RESISTANT INSERT	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
13	Harness, safety industrial: Type: live work fall arrest; Harness material: webbing anti static, flame retardant/non conductive; Harness webbing size: XL; Lifeline: adjustable double safety lanyard not to exceed 1.75 m, fitted with (2) pylon hooks; Attachment method: 2 straps, 1.5 m; Specification: Eskom SCSSCABA5; STD SANS 50354/50355/50358/50360/50361/50362/50795; Use/Marking SANS 50365; Drawing no: D12701 Rev 1; Manufactured, tested and marked as per SANS specifications for fall arrest equipment; supplied in a package; containing: (1) full body harness with work positioning belt SANS 50358 and SANS 50361; (1) non removable twist-lock karabiner double or triple action to SANS 50362; (1) energy absorber to SANS 50355; (1) adjustable work positioning lanyard not longer than 2 m to SANS 50358 and SANS 50354 with (1) non removable twist-lock karabiner double or triple action to SANS 50362; (1) adjustable single safety lanyard with (2) non removable twist-lock karabiners double or triple action to SANS 50362; (1) protector bag; Test/cert, identification; specification and other related requirements test & certification requirements; certificates: type test certificates at evaluation stage. Declaration of conformity certificate per product supplied instruction for use and marking requirements and, document of the general requirements for instruction for use and for marking and a document on the information supplied by the manufacturer; identification: indelible	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
14	Cloth: Type: disposable silicone; material: cotton; color: white; package type: box; package weight: 1.2 kg; foam filled fiberglass tools removes dust and deposits a thin coat that helps resist accumulation of dirt and other airborne contaminants; packed 50 per box; each packet individually sealed	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				
15	Lubricant: Type: ROCOL; Form: spray; Container: drum stl; base material: silicone; specification: 400 ml	State compliance and provide evidence (Pictures/Photo, Data sheets or Certificates)				