

**SECTION 2.2 SPECIFICATIONS**

| Product Description   | Comply<br>Yes/No | Page to<br>reference | Example/Image |
|---|------------------|----------------------|---------------|
| <b>2.2.1 Two-piece overalls must be:</b>  |                  |                      |               |
| a) Tripple stitched on all seams  |                  |                      |               |
| b) YKK Zip Fly for jacket and pants   |                  |                      |               |
| c) J54 100% Cotton suit   |                  |                      |               |
| d) Royal blue   |                  |                      |               |
| e) SABS-approved fabric (proof to be provided with samples)<br>SC1004I  |                  |                      |               |
| f) 90mm emblem wording (HESSEQUA MUN) embroidered on the left-hand side of the jacket (to be done after award has been made and on placement of an order) |                  |                      |               |
| g) Reflective strip on sleeves and pants  |                  |                      |               |
| h) Suitable for welders   |                  |                      |               |
| i) Jacket: 3 pockets  |                  |                      |               |
| j) Side pocket right leg (Fit pliers in)  |                  |                      |               |
| <b>2.2.2 Overall Jacket</b>   |                  |                      |               |
| a) Tripple stitching on all seams   |                  |                      |               |
| b) Fabric: J54 100% Cotton  |                  |                      |               |
| c) Royal blue   |                  |                      |               |
| d) SABS approved fabric (proof to be provided with samples)<br>SC1004I  |                  |                      |               |
| e) 90mm emblem wording (HESSEQUA MUN) embroidered on the left-hand side of the jacket (to be done after award has been made and on placement of an order) |                  |                      |               |
| f) Reflective tape on sleeves   |                  |                      |               |
| g) Front pockets  |                  |                      |               |
| h) Chest pocket with concealed press stud   |                  |                      |               |
| i) Side slits for comfort   |                  |                      |               |
| j) Concealed YKK Zip front  |                  |                      |               |
| k) Hanger loop  |                  |                      |               |
| <b>2.2.3 Overall Pants</b>  |                  |                      |               |
| a) Royal blue   |                  |                      |               |
| b) Tripple stitched on all seams  |                  |                      |               |
| c) YKK Zip on pants   |                  |                      |               |
| d) Fabric: J54 100% Cotton  |                  |                      |               |
| e) SABS approved fabric (proof to be provided with samples)<br>SC1004I  |                  |                      |               |
| f) Reflective tape on pants   |                  |                      |               |
| g) Side pocket right leg (Fit pliers in)  |                  |                      |               |
| <b>2.2.4 Overalls for Ladies (resorts)</b>  |                  |                      |               |
| a) Button front   |                  |                      |               |
| b) Polycotton 65/35   |                  |                      |               |

|   |  |  |  |   |  |
|---|--|--|--|---|--|
| c)  | Short sleeve   |  |  |    |  |
| d)  | Royal blue   |  |  |   |  |
| e)  | 90mm emblem wording (HESSEQUA MUN) embroidered on the left-hand side of the jacket (to be done after award has been made and on placement of an order) |  |  |   |  |
| f)  | 3 pockets  |  |  |   |  |
| g)  | Reflective strip on sleeves  |  |  |   |  |
| <b>2.2.5 Mr. Engineer Denim trousers (or similar)</b> |  |  |  |   |  |
| a)  | Triple stitched on inside of leg and between crutch  |  |  |   |  |
| b)  | PVC YKK zip or YKK metal zip on pants  |  |  |    |  |
| c)  | Reflective tape on trouser   |  |  |   |  |
| d)  | Side pockets right leg (Fit Pliers in)   |  |  |   |  |
| e)  | SABS approved fabric (proof to be provided with samples) SC 1004I  |  |  |   |  |
| f)  | Navy blue  |  |  |   |  |
| g)  | Fabric: 12 ons (Thickness)100% Cotton stonewashed denim  |  |  |   |  |
| <b>2.2.6 Golf shirts</b>                              |  |  |  |   |  |
| a)  | Golf type  |  |  |   |  |
| b)  | 90mm emblem wording (HESSEQUA MUN) embroidered on the left-hand side of the jacket (to be done after award has been made and on placement of an order) |  |  |   |  |
| c)  | 195gm 100% Cotton  |  |  |   |  |
| d)  | Double knit  |  |  |   |  |
| e)  | Royal blue   |  |  |   |  |
| f)  | Reflective tape on the sleeves   |  |  |   |  |
| <b>2.2.7 Polycotton shirts</b>                        |  |  |  |   |  |
| a)  | Golf type  |  |  |  |  |
| b)  | 90mm emblem wording (HESSEQUA MUN) embroidered on the left-hand side of the jacket (to be done after award has been made and on placement of an order) |  |  |   |  |
| c)  | 175g 65/35 Poly Cotton Jersey fabric   |  |  |   |  |
| d)  | Double knit  |  |  |   |  |
| e)  | Royal blue   |  |  |   |  |
| f)  | Reflective tape on the sleeves   |  |  |   |  |
| <b>2.2.8 Polycotton Long sleeve shirt</b>             |  |  |  |   |  |
| a)  | Long sleeve Lounge shirts  |  |  |   |  |
| b)  | 90mm emblem wording (HESSEQUA MUN) embroidered on the left-hand side of the jacket (to be done after award has been made and on placement of an order) |  |  |   |  |
| c)  | 175g 65/35 Poly Cotton Jersey fabric   |  |  |   |  |
| d)  | Double knit  |  |  |   |  |
| e)  | Royal blue   |  |  |   |  |
| f)  | Reflective tape on the sleeves   |  |  |   |  |
| <b>2.2.9 Chainsaw Operators Trouser</b>               |  |  |  |   |  |
| a)  | Holistic product: chain clogging pad to offer good protection  |  |  |   |  |

|   |   |  |  |   |
|---|---|--|--|---|
| b)  | Coverage: chain clogging pad extends from hip to ankle and fully encloses the calf from knee to ankle   |  |  |    |
| c)  | Polycotton Workwear- 65% Polyester and 35% cotton outer combines max, strengthen with the cooling qualities of cotton   |  |  |   |
| d)  | Climate Control nylon- Protects the chain clogging pad from brambles, oil and water- light weight to facilitate airflow/ reduce heat Protective tape around the hem prevents boot wear. |  |  |   |
| e)  | A double layer of fabric reinforces the seat area.  |  |  |   |
| <b>2.2.10 Brush Cutter Trouser (Parks &amp; Streets)</b>          |   |  |  |   |
| a)  | Hip Padding: Pocket on the hip to place padding protection during trimming  |  |  |    |
| b)  | Padded Protection at lower part of the legs to prevent soreness from spattering gravel and stones   |  |  |   |
| c)  | Zipper on the back of the leg can be opened for better ventilation  |  |  |   |
| d)  | Reinforcement on the back and front of the legs   |  |  |   |
| <b>2.2.11 Men's Chelsea HD &amp; Gripper (or similar) (Parks)</b> |   |  |  |    |
| a)  | PVC (HD) or recycle PVC(Gripped) with elastic gusset  |  |  |   |
| b)  | Sole Nitrile PVC (HD) or recycle PVC (Gripper)  |  |  |   |
| c)  | F1505 Steel toe cap   |  |  |   |
| <b>2.2.12 Furlined Wet Terrain (or similar)</b>                   |   |  |  |   |
| a)  | Waterproof winter Gumboot   |  |  |   |
| b)  | PVC with cold resistance additive compound without cadmium, lead or barium for cold resistance of up to 15°C  |  |  |   |
| c)  | Cold and insulation of 500/gyms, synthetic polyester and polyadenine with 4mm foam  |  |  |   |
| d)  | 4mm bio-component felt insole for better stability and comfort (fixed in the boot)  |  |  |   |
| e)  | Knee length   |  |  |   |
| f)  | Unisex  |  |  |   |
| g)  | Sole to be a minimum of 15mm thick with grooves to avoid slipping   |  |  |   |
| <b>2.2.13 Rebel Steel cap (or similar)</b>                        |   |  |  |   |
| a)  | Light weight unisex safety overshoe   |  |  |  |
| b)  | Aluminum toe cap  |  |  |   |
| c)  | Durable and flexible rubber anti-slip sole  |  |  |   |
| d)  | An adjustable Velcro strap  |  |  |   |
| <b>Safety Boots and Shoes</b>                                     |   |  |  |   |
| <b>2.2.14 Lemaitre Maxeco Chukka (or similar) (EPWP)</b>          |   |  |  |   |
| a)  | Slip resistant  |  |  |   |
| b)  | Resistant to oil, petrol and solvents   |  |  |   |
| c)  | Shock absorbent   |  |  |   |
| d)  | Heat resistant  |  |  |   |
| e)  | Antistatic properties   |  |  |   |
| f)  | SABS approved (must carry the SABS mark)  |  |  |   |

|  |  |  |  |  |
|--|--|--|--|--|
| g)   | Extra wide steel toe cap resistant to 200 j  |  |  |  |
| h)   | High quality genuine leather uppers  |  |  |  |
| i)   | Parabolic sole   |  |  |  |
| j)   | Non-conductive   |  |  |  |
| <b>2.2.15 Lemaitre Robust Safety shoe (or similar) (EPWP)</b>  |  |  |  |  |
| a)   | Double-density PU/Pu sole  |  |  |  |
| b)   | Heat resistant up to 95 degrees Celsius  |  |  |  |
| c)   | With Steel toe cap   |  |  |  |
| d)   | Slip resistant   |  |  |  |
| e)   | Black  |  |  |  |
| f)   | Antistatic   |  |  |  |
| <b>2.2.16 Lemaitre Hawk 8024 (or similar) (Electricity)</b>    |  |  |  |  |
| a)   | Extra wide steel toecap resistant to 200J.   |  |  |  |
| b)   | Resistance to oil, petrol and solvents.  |  |  |  |
| c)   | Resistance to acids and alkalis.   |  |  |  |
| d)   | Safety footwear that has slip resistance.  |  |  |  |
| e)   | High quality genuine leather uppers  |  |  |  |
| f)   | Sued leather upper   |  |  |  |
| g)   | Anti-static properties   |  |  |  |
| h)   | Heat resistance to 90°   |  |  |  |
| i)   | SABS Approved  |  |  |  |
| <b>2.2.17 Lamaitre Osprey Hiker (or similar) (Solid Waste)</b> |  |  |  |  |
| a)   | Upper  |  |  |  |
| •  | Cut from a 2.0mm-2.2mm Pull Up full grain leather  |  |  |  |
| •  | S2 leather scuff with PU coating on back counter and vamp  |  |  |  |
| •  | 10mm Extra padded collar and bellows tongue  |  |  |  |
| •  | 125cm Black braided nylon laces  |  |  |  |
| •  | 4 Pair mogul eyelets and 2 pairs lace hooks  |  |  |  |
| •  | Heel stiffener for shape longevity   |  |  |  |
| b)   | In-Sock and Top sock   |  |  |  |
| •  | Footology Elastopan climate control insole is an ergonomically moulded insole which provides superior cushioning, lightweight comfort, breathability and durability. |  |  |  |
| •  | PU Elastopan material ensure good thermal regulation to keep feet cool   |  |  |  |
| •  | Treated with antibacterial and antimicrobial agent which provides optimum foot hygiene and combats infections  |  |  |  |
| •  | Anti-static stich conducts electricity away from the foot  |  |  |  |
| c)   | Lining   |  |  |  |
| •  | Laminated vamp lining with 10mm foam open cell PU on collar and tongue for enhanced comfort and breathability  |  |  |  |

|  |  |  |  |
|--|--|--|--|
| <ul style="list-style-type: none"> <li>Quarter tongue lining made from a Cambrill non-woven material laminated to 4mm foam for enhanced comfort and excellent ventilation</li> </ul> |  |  |  |
| d) Toe Cao   |  |  |  |
| <ul style="list-style-type: none"> <li>Steel toe cap</li> </ul>  |  |  |  |
| <ul style="list-style-type: none"> <li>Can withstand an impact of 200 joules</li> </ul>  |  |  |  |
| <ul style="list-style-type: none"> <li>Also available with a soft toe -8238</li> </ul>   |  |  |  |
| e) Extra wide toe cap  |  |  |  |
| <ul style="list-style-type: none"> <li>Shrank reinforcement for additional arch support</li> </ul>   |  |  |  |
| <ul style="list-style-type: none"> <li>The raptor sole is made from Double Density PU/PU</li> </ul>  |  |  |  |
| <ul style="list-style-type: none"> <li>The midsole is made from a flexible low-density Polyurethane with shore hardness of 55-70</li> </ul>  |  |  |  |
| <ul style="list-style-type: none"> <li>The boot can withstand temperatures up to 95 degrees</li> </ul>   |  |  |  |
| <ul style="list-style-type: none"> <li>The boot has SRA rated slip resistance</li> </ul>   |  |  |  |
| <ul style="list-style-type: none"> <li>The boot must be anti-static</li> </ul>   |  |  |  |
| <ul style="list-style-type: none"> <li>Extra wide sole unit for stability and torsion control</li> </ul>   |  |  |  |
| <b>2.2.18 Lemaitre Falcon Safety boot (or similar)</b>   |  |  |  |
| a) Genuine leather upper   |  |  |  |
| b) Additional padding on collar and tongue for enhanced durability   |  |  |  |
| c) Ankle support while the Dual Density PU sole unit and TPU insert allow for a aggressive grip  |  |  |  |
| d) Torsion control and rigidity and stability making this style perfect  |  |  |  |
| e) Black   |  |  |  |
| f) Extra wide 200J steel toe cap   |  |  |  |
| <b>2.2.19 Bova Bremen (or similar) (Special shoe)</b>  |  |  |  |
| a) Double density PU/Pu (Heat-resistant up to 90 degrees)  |  |  |  |
| b) Padded below tongue and collar for comfort  |  |  |  |
| c) Steel toe cap-extra wide fitting  |  |  |  |
| d) Full grain leather  |  |  |  |
| e) Extra wide fitting upper as per Podiatry Specifications   |  |  |  |
| f) 3 pair D-ring lace-up with hooks  |  |  |  |
| g) Carries the SABS mark   |  |  |  |
| <b>2.2.20 Bova Hiker (or similar) (Mechanical)</b>   |  |  |  |
| a) Single density PU sole  |  |  |  |
| b) Water repellent, Oil and acid resistant, static resistant, shock absorbent  |  |  |  |
| c) Steel toe cap   |  |  |  |
| d) Full grain leather upper  |  |  |  |
| e) Walnut and Black  |  |  |  |
| f) SABS approved   |  |  |  |
| g) Steel toe cap   |  |  |  |



|   |   |  |  |   |
|---|---|--|--|---|
| <b>2.2.21 Profit Assassin Chelsea boot (or similar) (Special shoe) Not for wet conditions</b> |   |  |  |   |
| a)  | Upper material: S2 Oily Waxy Water Repellent full grain leather   |  |  |    |
| b)  | Sole material: Dual Density Polyurethane  |  |  |   |
| c)  | Slip-on   |  |  |   |
| d)  | Toe cap: 200 Joules   |  |  |   |
| e)  | Inner sole: Archna comfort  |  |  |   |
| f)  | Colour: Brown   |  |  |   |
| <b>2.2.22 Bova Columbia (or similar) (Electric and Special shoe)</b>                          |   |  |  |   |
| a)  | Upper   |  |  |    |
| i.  | Cut from 2.0mm- 2.2mm full grain Printed Water buffalo Sides  |  |  |   |
| ii.   | Increase girth area as per podiatry specifications  |  |  |   |
| iii.  | Padded bellows, tongue is from a closed cell foam and makes use of PU coagulated lining   |  |  |   |
| iv.   | 5 pair Chillie loops and 2 pair non-metallic hooks  |  |  |   |
| v.  | Braided lace from polyester yarn and central core for additional strength   |  |  |   |
| b)  | Lining  |  |  |   |
| i.  | The quarter lining is from a 4-D meh material   |  |  |   |
| ii.   | The vamp lining is from a hi-tech needed-fibre blend with excellent perspiration absorbency and treated with Ultra-fresh to impart hygienic and anti-bacterial properties to the material |  |  |   |
| c)  | In- sock & Top Sock   |  |  |   |
| i.  | The in-sock is from an anti-static non-woven material that is bonded to a layer of EVA and contains Poron inserts at the heel and ball of the foot for enhanced comfort and support       |  |  |   |
| ii.   | The Poron inserts at the ball and heel of the top sock offer optimum support where it is needed most, ensuring dynamic impact compression and a gentle rebound with every step.           |  |  |   |
| iii.  | The top sock responds to weight and temperature, molding itself to the foot, resulting in fewer arches and pains.   |  |  |   |
| iv.   | The top sock has been treated with Ultra-fresh to impact hygienic and anti-bacterial properties to the material.  |  |  |   |
| d)  | Sole  |  |  |   |
| <b>2.2.23 Bova Chelsea (or similar) (Special boots) Any department</b>                        |   |  |  |   |
| a)  | Dual density PU/PU sole   |  |  |  |
| b)  | Toe steel cap   |  |  |   |
| c)  | Heat resistant up to 95 degree Celsius  |  |  |   |
| d)  | Oil and acid-resistant  |  |  |   |
| e)  | Slip resistant  |  |  |   |
| f)  | Antistatic non-woven in sock for flexibility, comfort and stability   |  |  |   |
| g)  | Colours: Black/Brown  |  |  |   |
| h)  | Upper: Elastic side gussets and 2 pull straps for ease of entering and exiting the boot   |  |  |   |
| i)  | Antibacterial Energizer woolen top sock with anti-microbial properties  |  |  |   |

|   |  |  |  |
|---|--|--|--|
| <b>2.2.24 Bova Tahoe Safety shoe with Velcro (or similar) (Special safety shoe)</b>                                     |  |  |  |
| a) Sued leather   |  |  |  |
| b) Velcro straps for easy adjustment with reflective stitching for increased visibility                                 |  |  |  |
| c) Padded collar and tongue for enhanced comfort  |  |  |  |
| d) Punched holes in the vamp area and guater cut-outs for increased breathability                                       |  |  |  |
| e) PU/Elastopan material for comfort padding and climate control technology and antistatic stitching                    |  |  |  |
| f) The top sock is made from a durable polyester material that offers abrasion resistance and is quick drying in nature |  |  |  |
| g) The tongue and quarter lining are from non-woven, spot mesh fabric laminated to foam for improve comfort             |  |  |  |
| h) Vamp lining is from a hi-tech needle fibre and treated with Ultra-fresh for excellent perspiration absorbency        |  |  |  |
| i) Toe – steel extra wide fitting   |  |  |  |
| j) Mid-sole - Dual density with PU/PU with SRC slip resistance rating   |  |  |  |
| k) Heat resistant up to 95 degrees Celsius  |  |  |  |
| l) Engineered with an EVA insert at the heel of shock absorption  |  |  |  |
| m) Shank reinforcement for additional arch support  |  |  |  |
| <b>2.2.25 Jennifer ladies' shoe (Sissie) (or similar)</b>   |  |  |  |
| a) Full grain leather   |  |  |  |
| b) Padded collar and tongue from mesh   |  |  |  |
| c) Double-density PU/Pu sole  |  |  |  |
| d) Black  |  |  |  |
| e) Sole to be minimum of 15mm thick with grooves to avoid slipping  |  |  |  |
| f) Steel toe cap  |  |  |  |
| g) Unisex   |  |  |  |
| <b>2.2.26 Profit Ladies slip-on LS05 (or similar)</b>   |  |  |  |
| a) Dual Density polyurethane  |  |  |  |
| b) 200 joules   |  |  |  |
| c) Anti-static  |  |  |  |
| d) Arachna Comfort Innersole  |  |  |  |
| e) Black  |  |  |  |
| <b>2.2.27 Profit Charlotte Ladies safety shoe LS02 (or similar)</b>   |  |  |  |
| a) 4 sets of D-rings for lacing   |  |  |  |
| b) Lightweight, anti-static, slip and abrasion-resistant sole   |  |  |  |
| c) Oil, acid, petrol and diesel resistant   |  |  |  |
| d) Care should always be taken on wet or oily surfaces  |  |  |  |
| e) Black  |  |  |  |
| <b>2.2.28 Nicole ladies' shoe (Sissi) (or similar)</b>  |  |  |  |
| a) Upper:   |  |  |  |
| i. Cut from 2.0 – 2.2mm Full Grain Leather  |  |  |  |



|  |  |  |   |
|--|--|--|---|
| ii. 10mm padded collar from mesh fabric for enhanced comfort and support   |  |  |    |
| iii. pair punch hole lace-up   |  |  |   |
| iv. Braided lace from polyester yarn and central core for additional strength  |  |  |   |
| b) The quarter lining is from an industrial ferriable non-woven material.  |  |  |   |
| i. The vamp lining is from a hi-tech needle-fibre blend with excellent perspiration absorbency and is treated with Ultra-Fresh* to impart hygienic and anti-bacterial properties to the material |  |  |   |
| c) The in-sock is from an anti-static non-woven material.  |  |  |   |
| i. The Energizer top sock is from a combination of polyester and wool, with excellent perspiration absorbency.   |  |  |   |
| ii. The top sock features EVA foam inserts on the ball and heel area for enhanced comfort and shock absorption   |  |  |   |
| iii. The top sock has been treated with Ultra-Fresh* to impart hygienic and anti-bacterial properties to the material  |  |  |   |
| d) The sole is from a dual density PU/PU   |  |  |   |
| i. The midsole is from a low-density flexible Polyurethane with a shore hardness of 0.45mm – 0.50mm  |  |  |   |
| ii. The outer sole is from Polyurethane with a shore hardness of 0.64mm – 0.65mm   |  |  |   |
| iii. A shank reinforcement is molded into the midsole for additional arch support.   |  |  |   |
| iv. This shoe can withstand temperatures of up to 950C.  |  |  |   |
| v. This shoe has an SRC slip-resistance rating.  |  |  |   |
| vi. This shoe is anti-static   |  |  |   |
| e) Steel toe cap   |  |  |   |
| f) Withstand an impact load of 200joules   |  |  |   |
| <b>2.2.29 Two tone PVC Rain suits 2 piece (or similar)</b>   |  |  |   |
| a) EN 471 class 3 lined 100% waterproof jacket   |  |  |  |
| b) Color: Fluorescent Yellow and orange  |  |  |   |
| c) Fabric: PVC coated Polyester  |  |  |   |
| d) Two Pieces (Jacket and trouser)   |  |  |   |
| e) 50mm width reflective tap   |  |  |   |
| f) Insert hood with elastic cord and Auto stop   |  |  |   |
| g) Outer front pocket  |  |  |   |
| h) 1 inner chest pocket  |  |  |   |
| i) Welded seams for permanent resistance to water  |  |  |   |
| j) Zip and popper fastening  |  |  |   |
| k) Class one outer trouser   |  |  |   |
| l) Elastic waist   |  |  |   |
| m) Press stud adjustment on ankle  |  |  |   |
| n) 2 hip pockets change to an EN471 class 3 when used with a class 3 jacket  |  |  |   |
| <b>2.2.30 Furlined Jacket (or similar)</b>   |  |  |   |
| (a) Snapp off Hood   |  |  |   |
| (b) Water Repellent  |  |  |   |

|  |  |  |   |
|--|--|--|---|
| (c) Made from the Oxford Nylon Outer Fabric  |  |  |    |
| (d) Furlined inner with quilted sleeves  |  |  |   |
| (e) High quality Zips  |  |  |   |
| (f) Generous Cut   |  |  |   |
| (g) Colour / Navy  |  |  |   |
| (h) 100% Quality Guarantee   |  |  |   |
| (i) 90mm emblem wording (HESSEQUA MUN) embroidered on the left-hand side of the jacket (to be done after award has been made and on placement of an order) |  |  |   |
| <b>2.2.31 Javlin orange coated gloves –Superior (or similar) (Solid Waste &amp; Streets &amp; Stormwater)</b>  |  |  |   |
| (a) Black elbow length open cuff glove   |  |  |    |
| (b) Crinkle finish on hand   |  |  |   |
| (c) Smooth finish on cuff  |  |  |   |
| (d) Orange inner liner   |  |  |   |
| (e) Colour: Orange   |  |  |   |
| <b>2.2.32 Pioneer Flex Snug-Pluz Glove (or similar) (Solid waste, Street &amp; Stormwater)</b>   |  |  |   |
| a) EN 388 (2131)   |  |  |    |
| b) Code: G113  |  |  |   |
| <b>2.2.33 Lined Leather welder Glove (Electric)</b>  |  |  |   |
| (a) Leather suited for welding   |  |  |   |
| (b) 6cm  |  |  |   |
| <b>2.2.34 Latex surgical gloves (Cleaners)</b>   |  |  |  |
| (a) Material- Natural latex rubber   |  |  |   |
| (b) Weight - 22g   |  |  |   |
| (c) Colour- Blue   |  |  |   |
| (d) Size: Small - Large  |  |  |   |
| <b>2.2.35 PVC Gloves (Water &amp; Sewerage)</b>  |  |  |  |
| (a) Medium weight  |  |  |   |
| (b) Smooth finish  |  |  |   |
| (c) Knit wrist   |  |  |   |
| (d) Red  |  |  |   |
| (e) 6cm  |  |  |   |
| <b>2.2.36 PVC Gloves (Water and Sewerage &amp; Pesticides)</b>   |  |  |   |
| (a) PVC  |  |  |   |

|  |  |  |   |
|--|--|--|---|
| (b) Red  |  |  |    |
| (c) Heavy Duty   |  |  |   |
| (d) 20CM   |  |  |   |
|  |  |  |   |
| <b>2.2.37 PVC Gloves (Water and Sewerage &amp; Pesticides)</b>                     |  |  |   |
| (a) Extended to shoulders length with elastic cuff                                 |  |  |    |
| (b) Medium weight smooth finish  |  |  |   |
| (c) 40 cm  |  |  |   |
| (d) Red  |  |  |   |
| <b>2.2.38 Impact gloves (or similar) (Machine operators)</b>                       |  |  |   |
| a) High visibility Glove   |  |  |   |
| b) Breathable spandex material   |  |  |   |
| c) Inner padding for insulation  |  |  |   |
| d) Impact protection   |  |  |   |
| e) Extra knuckle protection  |  |  |   |
| <b>2.2.39 Rough finish rubber glove (or similar) (Waste removal &amp; EPWP)</b>    |  |  |   |
| a) High quality cotton liner   |  |  |  |
| b) Knit wrist  |  |  |   |
| c) 6 cm  |  |  |   |
| d) Crinkle Rubber  |  |  |   |
| <b>2.2.40 Electrical Insulation Gloves (Electric)</b>                              |  |  |   |
| a) Exclusive for electrical purposes -voltage up to 1KV (Kilovolts)                |  |  |  |
| b) R-cid, oil, ozone, C-resistant to extremely low temperatures                    |  |  |   |
| c) High flexibility preventing hand fatigue  |  |  |   |
| d) Fits well when worn with protective leather over gloves                         |  |  |   |
| e) Each glove must be electrically tested & issued with an examination certificate |  |  |   |
| f) 360mm long  |  |  |   |
| <b>2.2.41 Chainsaw gloves (Environmental)</b>                                      |  |  |   |
| a) Leather/Kevlar/Polyester  |  |  |  |
| b) Orange/Black  |  |  |   |
| c) Sizes: M - 2XLarge  |  |  |   |
| <b>2.2.42 Hard hats Nikki (or similar)</b>   |  |  |   |

|   |  |  |   |
|---|--|--|---|
| a) Lightweight ABS (Acrylonitrile Butadiene Styrene) offering superior rigidity, protection, and durability.                          |  |  |    |
| b) The inner of hard hat shell is engineered with reinforced ribs for increased protection against impact and lateral formation.      |  |  |   |
| a) Turn top adjustable crown vent allows for double crown protection.   |  |  |   |
| b) Integrated slots that allow for the majority of accessories  |  |  |   |
| c) Point comfort ratchet lining for easy one-handed adjustment with Perma sweat breathable sweatband and high visibility rear insert. |  |  |   |
| d) Anti-glare peak.   |  |  |   |
| e) Supporting ridge for cap attachment spring.  |  |  |   |
| f) ARC-rated and electrical insulation - tested to 18cal/cm <sup>2</sup> and 1000 volts dielectric                                    |  |  |   |
| <b>2.2.44 Apron Front (Welding)</b>   |  |  |   |
| (a) Leather   |  |  |    |
| <b>2.2.45 Green PVC Apron (Graveyard &amp; Streets)</b>   |  |  |   |
| a) 120x90cm   |  |  |   |
| b) Superior splash protection   |  |  |   |
| c) Resistance to chemicals and oils.  |  |  |   |
| <b>2.2.46 Elasticated back support Kidney Belt (Operators &amp; Truck drivers)</b>  |  |  |   |
| a) Velcro Fastener  |  |  |   |
| b) Heavy duty elastic   |  |  |   |
| c) Strong upright struts for back support   |  |  |  |
| <b>2.2.47 Fall arrest Harness (Electricity, Handy Man, Cleaners and Process controllers)</b>  |  |  |   |
| a) For Working on Height  |  |  |   |
| b) Full Shock absorbent   |  |  |   |
| c) Lanyard  |  |  |   |
| d) Heavy Duty webbing   |  |  |   |
| e) SABS-EN 358:1992   |  |  |   |
| f) SABS- EN 354/355:1992  |  |  |   |
| g) Absorption Lynard  |  |  |  |


|   |  |  |  |   |
|---|--|--|--|---|
| <b>2.2.48 Forestry Cap (CAPF) (Parks)</b>   |  |  |  |    |
| a) Safety Cap   |  |  |  |   |
| b) Mesh visor   |  |  |  |   |
| c) Earmuffs   |  |  |  |   |
| <b>2.2.49 Earmuffs Standard (All)</b>   |  |  |  |    |
| a) SNR 29 dB  |  |  |  |   |
| b) Larger ear cup opening and soft, foam-filled cushioned for a snug, comfortable fit   |  |  |  |   |
| c) Durable, lightweight construction  |  |  |  |   |
| d) Adjustable band  |  |  |  |   |
| <b>2.2.50 Face shield clear visor with clip on earmuffs (Parks)</b>   |  |  |  |    |
| a) Twin point mounted cups  |  |  |  |   |
| b) Low risk of entanglement on machinery  |  |  |  |   |
| c) Hearing protection for extended periods  |  |  |  |   |
| d) Visor must easily slip up and down   |  |  |  |   |
| e) Durable self-adjusting ABD cups  |  |  |  |   |
| f) Close fitting wire headband for comfort  |  |  |  |   |
| <b>2.2.51 Harness Brush Cutter (Parks)</b>  |  |  |  |   |
| a) Shoulder Pads  |  |  |  |   |
| b) Hip pad  |  |  |  |   |
| c) Kidney pad   |  |  |  |   |
| d) Quick release  |  |  |  |   |
| e) Suitable for weed eating   |  |  |  |   |
| f) Fully adjustable   |  |  |  |   |
| <b>2.2.52 Disposable mask with Valve (Dust &amp; Lime)</b>  |  |  |  |  |
| a) Traditional cup shape, with nose clip and twin strap design.   |  |  |  |   |
| b) The convex shape, twin strap design, nose foam and nose clip ensure comfortable wear over a range of face sizes.   |  |  |  |   |
| c) 3M™ Cool Flow™ Valve: Effective removal of heat buildup provides a cooler and more comfortable wear, removes exhaled air and minimizes the risk of misting eyewear |  |  |  |   |
| d) Reliable, effective protection against fine particles. Colour coded straps, blue = FFP2 (APF 10)   |  |  |  |   |
| <b>2.2.53 Double respirator (Pesticides)</b>  |  |  |  |   |
| a) A light weight and easy to use half mask respirator  |  |  |  |   |

|   |  |  |  |
|---|--|--|--|
| b) A higher efficiency dual cartridge half mask respirator  |  |  |  |
| <b>2.2.54 Double respirator Filter (Pesticides)</b>   |  |  |  |
| a) Filter suitable for inorganic  |  |  |  |
| b) Face mask filters  |  |  |  |
| <b>2.2.55 Hazmet Full Face Mask (Chlorine &amp; Methane Gas)</b>                                  |  |  |  |
| a) Full Face respirator features state-of-art design to allow resistance                          |  |  |  |
| b) Nose cup reduces fogging   |  |  |  |
| c) Silicone faceplate to increase comfort   |  |  |  |
| d) Wraparound lens for the wide field -or-vision with adjustable straps to offer a consistent fit |  |  |  |
| <b>2.2.56 Rabek Cannister (or similar) (Chlorine, Methane Gas)</b>                                |  |  |  |
| a) Gasses and vapour from organic compounds   |  |  |  |
| b) Right-handed screw in  |  |  |  |
| c) Gases: Ammonia, acid and organic and inorganic   |  |  |  |
| d) Solid and liquid toxic particles   |  |  |  |
| <b>2.2.57 Half face mask (Asbestos)</b>   |  |  |  |
| a) Connection Type: Bayonet   |  |  |  |
| b) Harness Type: 4 Point  |  |  |  |
| c) Net Weight (Metric): 82g   |  |  |  |
| d) Primary material: Thermoplastic Elastomer (TPE)  |  |  |  |
| e) Product Series: 600 Series   |  |  |  |
| f) 3M   |  |  |  |
| <b>2.2.58 Gas and vapour Filter (Asbestos)</b>  |  |  |  |
| a) Gas and Vapour Cartridge 6059 protects against organic vapours hazards                         |  |  |  |
| b) Suitable for 3M 6000 and 3M7000 Series half and Full Face masks                                |  |  |  |
| c) Bayonet fitting allows filters to be clicked into place for ease of fitting                    |  |  |  |
| d) Lightweight with low breathing resistance  |  |  |  |
| <b>2.2.59 Goggles(Asbestos)</b>   |  |  |  |
| a) Standard: ANSI   |  |  |  |
| b) Lens thickness (mm): 2.2   |  |  |  |
| c) Frame material: Soft Polyvinyl Chloride (Soft PVC)   |  |  |  |
| d) Dust Prove   |  |  |  |
| e) Band material: Fabric Elasticised rubber blend   |  |  |  |
| <b>2.2.60 Eye Protection</b>  |  |  |  |
| a) Spectacle PVC Grey shaded  |  |  |  |
| b) Full front & side protected  |  |  |  |

|  |  |  |   |
|--|--|--|---|
| c) Frame 100% polycarbonate  |  |  |    |
| d) CE EN 166-1F  |  |  |   |
| <b>2.2.61 Spoggles Eye Protection</b>  |  |  |   |
| a) Lens inner attachment   |  |  |   |
| b) Polycarbonate mono lens   |  |  |   |
| c) Soft rubber face seal   |  |  |   |
| d) Efficiency indirect ventilation system  |  |  |   |
| e) Detachable black vinyl adjustable temple  |  |  |   |
| f) Ergonomic design to fit snug with the efface contour  |  |  |   |
| g) Complete with a detachable prescription (rX0 lens contour   |  |  |   |
| h) Anti-fog lens   |  |  |   |
| i) 180-degree lateral vision   |  |  |   |
| j) Clear/gray  |  |  |   |
| <b>2.2.62 Chain saw goggles</b>  |  |  |   |
| a) Material: PVC   |  |  |    |
| b) Lens color: Transparent   |  |  |   |
| c) Effectively prevent dust, wind, sand and impact.  |  |  |   |
| <b>2.2.63 Reflective Jacket</b>  |  |  |    |
| a) Woven Mesh Polyester  |  |  |   |
| b) Black Polyester binding   |  |  |   |
| d) Nylon Zip with metal slider   |  |  |   |
| e) 50mm PVC (Poly Vinyl chloride) White reflective tape  |  |  |   |
| <b>2.2.64 Bibs (EPWP)</b>  |  |  |  |
| a) Health and Safety Bibs  |  |  |   |
| b) Lime green  |  |  |   |
| <b>2.2.65 Chest wader (Process controllers and Water)</b>  |  |  |  |
| a) Adjustable nylon suspenders   |  |  |   |
| b) Integrated quick-release nylon buckles on each shoulder with 38mm webbing and a single row of silver reflective stitching |  |  |   |
| Elasticated chest collar suited for sizes S-XL   |  |  |   |
| c) Bib and brace with rounded corner chest pocket with single-stitched flap and 2 plastic press studs                        |  |  |   |
| d) Elasticated on either side of the waistline   |  |  |   |
| e) 100% waterproof smooth PVC seam stitching   |  |  |   |
| f) Top stitching on front and back rise, with welding over the stitching   |  |  |   |
| g) Top stitching on in-seams, with welding over the stitching  |  |  |   |
| h) All stress points are bar tacked  |  |  |   |
| i) Threads is inherently flame retardant   |  |  |   |
| j) Pressure-tested to 6 bars to ensure seam integrity  |  |  |   |
| k) 400gsm polyester reinforced PVC – 90% PVC and 10% Polyester blend   |  |  |   |
| l) PVC injection-moulded seamless gumboot construction for 100% waterproof protection  |  |  |   |

|   |  |  |  |
|---|--|--|--|
| m) Size- 5-12   |  |  |  |
| n) Colour: Bottle green   |  |  |  |
| <b>2.2.66 Pepper Spray (<i>Meter readers &amp; Solid Waste</i>)</b>                                 |  |  |  |
| a) Ingredients: Extract of Habanero peppers (15% oleoresin Capsicum)                                |  |  |  |
| b) Power blend Super Formula  |  |  |  |
| c) Nylon pouch with single close & popper fastener  |  |  |  |
| d) Belt slot on back  |  |  |  |
| e) Color: Standard  |  |  |  |
| <b>2.2.67 Pepper spray Pouch (<i>Meter readers &amp; Solid Waste</i>)</b>                           |  |  |  |
| a) Nylon pouch with single closed top case & popper fastener  |  |  |  |
| b) Belt slot on back  |  |  |  |
| c) Size: 110mm length   |  |  |  |
| d) Colour: Standard   |  |  |  |
| <b>2.2.68 Snake tongs</b>   |  |  |  |
| a) 0.90 thick wall standard aluminum tube   |  |  |  |
| b) Weight: 590g   |  |  |  |
| c) Material: Cast aluminum  |  |  |  |
| d) Length: 1,5 m  |  |  |  |
| e) Rubber cushion to create a gentle grip   |  |  |  |
| <b>2.2.69 Snake handling tube</b>   |  |  |  |
| (a) Length: 110mm Plastic piping  |  |  |  |
| (b) Covered on one end with screw-on the other  |  |  |  |
| (c) Holes for ventilation on the lid  |  |  |  |
| <b>2.2.70 Disposable suits (<i>Asbestos</i>)</b>  |  |  |  |
| a) Style: Disposable full body coverall with elastic wrists, legs and waist                         |  |  |  |
| b) Hooded and nylon zipper front  |  |  |  |
| c) Material: 50gsm non-woven spun-bond polypropylene  |  |  |  |
| <b>2.2.71 Sun hats</b>  |  |  |  |
| a) Colour: Lime Poly cricket hat 125 gsm2 RWP 125 L with silver reflective tape on brim             |  |  |  |
| b) Protection Type: Sun Protection  |  |  |  |
| c) Material: 125 gsm2 100% Polyester (neon yellow) conforming to EN471 and SANS 50471 STANDARD SIZE |  |  |  |
| d) Head string for head adjustment mesh for allowing fresh air A strap around the chin              |  |  |  |
| e) Hessequa Municipality Logo embroidered in the front of the hat                                   |  |  |  |
| <b>2.2.72 GENERAL INFORMATION SAFETY SIGNS</b>  |  |  |  |
| a) Instruction that needs to be followed  |  |  |  |

Initials of Service Provider's Authority: .....

|   |  |  |   |
|---|--|--|---|
| b) A white symbol or pictogram within a green square sign         |  |  |    |
| c) SANS 1186-1 SABS approved                                      |  |  |   |
| d) Chromadek steel  |  |  |   |
| e) ABS plastic  |  |  |   |
| f) SABS approved sizes are 150x150mm,                             |  |  |   |
| g) 190x190mm  |  |  |   |
| h) 440x440mm  |  |  |   |
| i) 880x880mm  |  |  |   |
| <b>2.2.73 WARNING SIGNS</b>                                       |  |  |   |
| a) Indicate danger and that special precautions are needed        |  |  |    |
| b) Black and Red colors   |  |  |   |
| c) SANS 1186-1 SABS approved.                                     |  |  |   |
| <b>2.2.74 FIRE FIGHTING SIGNS</b>                                 |  |  |   |
| a) Vinyl sticker  |  |  |   |
| b) ABS Plastic  |  |  |   |
| c) Chromadek  |  |  |   |
| d) Magnet   |  |  |   |
| e) 190x380mm  |  |  |   |
| f) 150x300mm  |  |  |   |
| g) Fire extinguisher with red arrow                               |  |  |   |
| <b>2.2.75 MANDATORY SIGNS (DO)</b>                                |  |  |  |
| a) ABS approved   |  |  |   |
| b) 290x290mm  |  |  |   |
| c) Material: Plastic/Chromadek                                    |  |  |   |
| d) White safety symbol or pictogram with a blue background        |  |  |   |
| <b>2.2.76 PROHIBITORY SIGN (DON'T)</b>                            |  |  |   |
| a) Type: WSH AH EH  |  |  |   |
| b) Part no. 700 052   |  |  |   |
| c) ABS approved   |  |  |   |
| d) Material: Plastic/Chromadek                                    |  |  |   |
| <b>2.2.77 Peak Cap</b>  |  |  |  |
| a) Peak cap   |  |  |   |
| b) Adjustable   |  |  |   |
| c) Material: Protective ABS                                       |  |  |   |
| d) Head size 52-65cm  |  |  |   |
| e) Integrated sweatband   |  |  |   |
| f) Complies with EN812  |  |  |   |
| g) Hessequa Municipality Logo embroidered in the front of the hat |  |  |   |

|   |  |  |  |   |
|---|--|--|--|---|
| <b>2.2.78 Beanie</b>  |  |  |  |    |
| a) Wool   |  |  |  |   |
| b) Durable  |  |  |  |   |
| c) Stretchable  |  |  |  |   |
| d) Hessequa Municipality Logo embroidered in the front of the hat   |  |  |  |   |
| <b>2.2.79 Buff</b>  |  |  |  |    |
| a) Green-38 gsm; colors-53gsm   |  |  |  |   |
| b) Multiple users for all training activities   |  |  |  |   |
| c) Breathable and seamless material   |  |  |  |   |
| d) Available in a variety of sport colors   |  |  |  |   |
| e) Soft feel and easy to wash   |  |  |  |   |
| f) Material: 95% Polyester & 5% spandex   |  |  |  |   |
| g) One size fit all   |  |  |  |   |
| <b>2.2.80 FJK Cutters Tunic Forestry Jacket</b>   |  |  |  |    |
| a) Orange/Blue  |  |  |  |   |
| b) 65/35 polycotton   |  |  |  |   |
| c) Stud fastening front   |  |  |  |   |
| d) Underarm ventilation and cross the back  |  |  |  |   |
| e) Back longer than front   |  |  |  |   |
| <b>2.2.81 High Visibility Jacket</b>  |  |  |  |   |
| a) Water resistant oxford nylon with reflective tape  |  |  |  |   |
| b) Stand UP color   |  |  |  |   |
| c) Hand slot behind front pockets   |  |  |  |   |
| d) Zip away hood  |  |  |  |   |
| e) 90mm emblem wording (HESSEQUA MUN) embroidered on the left-hand side of the jacket (to be done after award has been made and on placement of an order) |  |  |  |   |
| f) Padded for warmth and insulation   |  |  |  |   |
| g) Highly reflective tape for night visibility  |  |  |  |   |
| <b>2.2.82 Fisherman trouser</b>   |  |  |  |  |
| a) Drawstring   |  |  |  |   |
| b) Yakking trouser  |  |  |  |   |
| c) Green  |  |  |  |   |
| d) PVC  |  |  |  |   |
| <b>2.2.83 Arachna Inner sole (or similar)</b>   |  |  |  |  |
| a) Biochemical Footbed inner sole   |  |  |  |   |
| b) Arachna Yellow Cut to fit  |  |  |  |   |

**Failure to adhere to the above specifications, may result in your tender being declared non-responsive.**

DECLARATION,

I, THE UNDERSIGNED (NAME) .....  
CERTIFY THAT THE INFORMATION FURNISHED ABOVE IS CORRECT. I ACCEPT THAT THE MUNICIPALITY  
MAY ACT AGAINST ME SHOULD THIS DECLARATION PROVE TO BE FALSE.

AUTHORISED SIGNATURE: .....

NAME: .....

CAPACITY: ..... DATE: .....

Initials of Service Provider's Authority: .....