

engineering
Transnet Ltd Reg. No. 17591/09/000/06

07 July 2025
Durban
Configuration

TRANSENET
Engineering

NOTE:

1. MATERIAL - ARAMID FIBRE WITH NBR BINDER, NITRILE RUBBER ACRYLONITRILE BUTADIENE (COMPRESSIBILITY: 7-15%)
RECOVERY: 50 MIN, TENSILE STRENGTH >= 8.5 MPA)
2. MAXIMUM OPERATING TEMPERATURE: 300 DEGREES CELSIUS.
3. MIN OPERATING TEMPERATURE: -100 DEGREES CELSIUS.

-/A
MATERIAL ALTERED
PD_PEL_KLP_05A
2020/09/18
N.T.N.

AMENDMENTS

MASS	0.12 Kg
------	---------

COPYRIGHT
THIS DRAWING TOGETHER WITH THE COPYRIGHT
IS THE PROPERTY OF
TRANSNET
THIS DRAWING OR ANY PART THEREOF IS NOT
TO BE COPIED OR OTHERWISE REPRODUCED
OR USED FOR MANUFACTURE OR ANY OTHER
PURPOSE WITHOUT THE WRITTEN PERMISSION
FROM
CHIEF EXECUTIVE,
TRANSNET ENGINEERING

ASSEMBLY DRG No. - -

DRAWN

N.T.N.

— — — — —

CHECKE

N.C.L

CLASS -

APPROV

B.E.D.

TYPE -

DATE _____

-02-2020

-

SCALE

1:2

KILNER PARK

ROTATING MACHINES

GASKET

VV230-180 COMPRESSOR

MATERIAL

SEE NOTE

-


SHEET 1

438X154

SHEET 1 OF 1

A-3

PROJECTION



DOCUMENT REFERENCE No.

PD_PEL_KLP_DRW_05A

TRANSNET ENGINEERING

No.	
-----	--

PEL05A0395^R

EV
A