

	Scope Of Work	Hendrina Power Station
---	----------------------	-------------------------------

Title: **Scope of Work for Supply and delivery of Plant Consumables on an “as and when required” at Hendrina Power Station for a Period of 5 Years**

Unique Identifier:

Alternative Reference Number: **N/A**

Area of Applicability: **Stores**




Documentation Type: **Specification**

Revision: **1**

Total Pages: **57**

Next Review Date: **N/A**

Disclosure Classification: **CONTROLLED DISCLOSURE**

Compiled by	Functional Responsibility	Authorised by /
 [Redacted] [Redacted] [Redacted] Date: [Redacted]	 [Redacted] [Redacted] [Redacted] Date: [Redacted]	 [Redacted] [Redacted] [Redacted] Date: [Redacted]

CONTENTS

1. INTRODUCTION	3
2. SUPPORTING CLAUSES	3
2.1 SCOPE	3
2.1.1 Purpose	3
2.2 NORMATIVE/INFORMATIVE REFERENCES	3
2.2.1 Normative	3
2.2.2 Informative	3
2.3 DEFINITIONS	3
2.3.1 Disclosure Classification	3
2.4 ABBREVIATIONS	3
2.5 ROLES AND RESPONSIBILITIES	3
2.6 PROCESS FOR MONITORING	3
2.7 RELATED/SUPPORTING DOCUMENTS	3
3. SYSTEM REQUIREMENTS	4
3.1 7 CONSUMABLES SUPPLY REQUIREMENTS	4
Below are Consumables that Hendrina Power Station currently using, scope of work does not limit any Consumables that might require to be supplied at Hendrina Power Station.	4
4. AUTHORISATION	30
5. REVISIONS	30
6. DEVELOPMENT TEAM	30
7. ACKNOWLEDGEMENTS	30

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

1. INTRODUCTION

The purpose of this document is to provide a clear statement of the scope of work for the **Supply and delivery of Plant Consumables on an “as and when required” at Hendrina Power Station for a Period of 5 Years**. This document defines detail description of stores components requirements, which shall be met by the supplier.

This document collects all the information related stakeholder requirements for the supply of plant consumables and forms the basis of the scope.

2. SUPPORTING CLAUSES

2.1 SCOPE.

This document describes the detail scope of work required for the Supply and Delivery of plant consumables on an “as and when required” at Hendrina Power Station, however not limiting the unforeseen during the supply

2.1.1 Purpose

The purpose of this document is to provide or outline area of responsibility during Supply and Delivery of plant consumables at Hendrina Power Station.

This document shall apply to Eskom Hendrina Power Station

2.2 NORMATIVE/INFORMATIVE REFERENCES

2.2.1 Normative

N/A

2.2.2 Informative

N/A

2.3 DEFINITIONS

N/A

2.3.1 Disclosure Classification

Controlled disclosure: controlled disclosure to external parties (either enforced by law, or discretionary).

2.4 ABBREVIATIONS

Abbreviation	Description
SOW	Scope of Work

2.5 ROLES AND RESPONSIBILITIES

Materials Management at Hendrina Power Station is responsible for issuing plant consumables SOW.

Materials Management will be responsible for managing the contract.

2.6 PROCESS FOR MONITORING

N/A

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

2.7 RELATED/SUPPORTING DOCUMENTS

N/A

3. SYSTEM REQUIREMENTS

3.1 MATERIALS MANAGEMENT PLANT CONSUMABLES REQUIREMENTS

As per scope of work:

Below is a list of Plant Consumables at Hendrina Power Station required, scope of work does not limit any consumable that might be required to be added supplied at Hendrina Power Station.

Material no	Short description	QTY	Unit of Measure
016830	PAINT, OIL: TYPE: ENAMEL; COLOR: RED; CONTAINER: CAN 5 L; FINISH: GLOSS; SPECIFIC USE: STOEP; REFERENCE NO: SP3; SPREADING RATE 6 M2/LITRE; DRYING TIME: TOUCH DRY 4HRS/23 DEG C; RE-COATING 16HRS/23 DEG C; DRY TO HANDLE 16HRS/23 DEG C; VISCOSITY 65 KREBS UNITS; SHOULD COMPLY WITH CHEMICAL HAZARDOUS REGULATION OF HEALTH AND SAFETY ACT; CHEMICAL DATA SHEET MUST BE SUPPLIED WITH EVERY DELIVERY	15 000.00	L
016834	PAINT, OIL: TYPE: ENAMEL; COLOR: RED SIGNAL; CONTAINER: CAN 500 ML; FINISH: HIGH GLOSS; SPECIFICATION: SABS 630-1972; REFERENCE NO: D29; EXTERIOR AND INTERIOR USE, REF:CKS279:1971, MATERIAL SAFETY DATA SHEETS THAT COMPLIES WITH THE OCCUPATIONAL HEALTH AND SAFETY ACT'S REGULATIONS TO BE SUPPLIED,NO SUBSTANCES AND/OR INGREDIENTS THAT FALL UNDER TABLE 1 CATAGORY WILL BE USED,ANY CHEMICAL FALLING UNDER TABLE 3 OF THE SAME REGULATIONS SHALL NOT BE USED,SHALL BE BIODEGRADABLE AND OZONE FRIENDLY,COPY OF MSDS TO BE SENT TO MEDICAL CENTRE AND SAFETY RISK	2 500.00	EA

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Scope of Work for Supply and delivery of Plant Consumables on an “as and when required” at Hendrina Power Station for a Period of 5 Years

Unique Identifier:

Revision:

1

Page:

5 of 30

016836	PAINT, OIL: TYPE: ENAMEL; COLOR: YELLOW GOLDEN; CONTAINER: CAN 5 L; FINISH: HIGH GLOSS; SPECIFIC USE: EXTERIOR/INTERIOR; SPECIFICATION: CKS 279-1971; SABS 630-1972; REFERENCE NO: B49; USE, MATERIAL SAFETY DATA SHEETS THAT COMPLIES WITH THE OCCUPATIONAL HEALTH AND SAFETY ACT'S REGULATIONS TO BE SUPPLIED, NO SUBSTANCES AND/OR INGREDIENTS THAT FALL UNDER TABLE 1 CATEGORY WILL BE USED, ANY CHEMICAL FALLING UNDER TABLE 3 OF THE SAME REGULATIONS SHALL NOT BE USED, SHALL BE BIODEGRADABLE AND OZONE FRIENDLY, COPY OF MSDS TO BE SENT TO MEDICAL CENTRE AND SAFETY RISK	5 000.00	L
016843	PAINT, WATER: COLOR: IVORY SHEEN; CONTAINER: 5 L; PHYSICAL FORM: LIQUID; SPECIFIC USE: EXTERIOR/INTERIOR; SPECIFICATION: FZA000566 SHEEN-PASTEL TINT BASE; FZA003547 TINTING SHADE 1; FINISH: SMOOTH	12 000.00	L
158819	BRUSH, PAINT: TYPE: STENCIL; MATERIAL: BRISTLE CHINA BLACK; SHAPE: RD; HANDLE: WOOD; REFERENCE NO: NO. 8; SIZE: 35MM DIA X 175MM LG	500.00	EA
159888	PAINT, OIL: TYPE: ENAMEL; COLOR: BLUE STRONG; CONTAINER: CAN 5 L; FINISH: HIGH GLOSS; SUPPL P/N: 111; COLOUR THOLA, TO SABS SPEC, HG 180, INTERNAL AND EXTERNAL USE, MATERIAL SAFETY DATA SHEETS THAT COMPLIES WITH THE OCCUPATIONAL HEALTH AND SAFETY ACT'S REGULATIONS TO BE SUPPLIED, NO SUBSTANCES AND/OR INGREDIENTS THAT FALL UNDER TABLE 1 CATEGORY WILL BE USED, ANY CHEMICAL FALLING UNDER TABLE 3 OF THE SAME REGULATIONS SHALL NOT BE USED, SHALL BE BIODEGRADABLE AND OZONE FRIENDLY, COPY OF MSDS TO BE SENT TO MEDICAL CENTRE AND SAFETY RISK	13 000.00	L
159891	PAINT, OIL: TYPE: ENAMEL; COLOR: CREAM/IVORY; CONTAINER: CAN 5 L; FINISH: HIGH GLOSS; SPECIFIC USE: EXTERIOR/INTERIOR; SPECIFICATION: SABS 630 GR 1; SUPPL P/N: HG3;	13 000.00	L

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an "as and when required" at Hendrina Power Station for a Period of 5 Years

Unique Identifier:
Revision: 1
Page: 6 of 30

	REFERENCE NO: C66; SABS 1091, CKS 279:1971, CHEMICAL HAZARD DATA SHEET TO ACCOMPANY DELIVERY, RECOMMENDED DRY FILM THICKNESS 25 MICRONS, SPREADING RATE 10 M2/LITRE, DRYING TIME: TOUCH DRY 4HRS/23 DEG C, RE-COATING 16HRS/23 DEG C, DRY TO HANDLE 16HRS/23 DEG C, VISCOSITY 70 KREBS UNITS		
159898	PAINT, OIL: TYPE: ENAMEL; COLOR: RED SIGNAL; CONTAINER: CAN 5 L; FINISH: HIGH GLOSS; SPECIFICATION: SABS 630-1972; REFERENCE NO: D29; CKS279 1971; MATERIAL SAFETY DATA SHEETS THAT COMPLIES WITH THE OCCUPATIONAL HEALTH AND SAFETY ACT'S REGULATIONS TO BE SUPPLIED, NO SUBSTANCES AND/OR INGREDIENTS THAT FALL UNDER TABLE 1 CATAGORY WILL BE UDED, ANY CHEMICAL FALLING UNDER TABLE 3 OF THE SAME REGULATIONS SHALL NOT BE USED, SHALL BE BIODEGRADABLE AND OZONE FRIENDLY, COPY OF MSDS TO BE SENT TO MEDICAL CENTRE AND SAFETY RISK	7000.00	L
159907	PAINT, OIL: TYPE: ENAMEL; COLOR: WHITE; CONTAINER: CAN 5 L; FINISH: HIGH GLOSS; SPECIFICATION: SABS 630-1972 TYPE 1; PSB CODE 1000, INTERIOR AND EXTERIOR USE, RECOMMENDED DRY FILM THICKNESS 25 MICRONS, SPREADING RATE 10 M2/LITRE, DRYING TIME: TOUCH DRY 4HRS/23 DEG C, RE-COATING 16HRS/23 DEG C, DRY TO HANDLE 16HRS/23 DEG C, VISCOSITY 70 KREBS UNITS, INENT PAINT MATERIAL SAFETY DATA SHEETS THAT COMPLIES WITH THE OCCUPATIONAL HEALTH AND SAFETY ACT'S REGULATIONS TO BE SUPPLIED, NO SUBSTANCES AND/OR INGREDIENTS THAT FALL UNDER TABLE 1 CATAGORY WILL BE USED, ANY CHEMICAL FALLING UNDER TABLE 3 OF THE SAME REGULATIONS SHALL NOT BE USED, SHALL BE BIODEGRADABLE AND OZONE FRIENDLY, COPY OF MSDS TO BE SENT TO MEDICAL CENTRE AND SAFETY RISK	7 000.00	L
159921	PAINT, OIL: TYPE: ENAMEL; COLOR: IVORY; CONTAINER: CAN 5 L; FINISH: GLOSS; SPECIFIC USE:	13 000.00	L

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Scope of Work for Supply and delivery of Plant Consumables on an "as and when required" at Hendrina Power Station for a Period of 5 Years

Unique Identifier:
Revision: 1
Page: 7 of 30

	INTERIOR; SUPPL P/N: HM2; REFERENCE NO: B77,182/L; EGGSHELL, PLASCON HYSHEEN , TO THE LATEST EDITION OF SABS 515/1091/1975 AND BEARING THE SABS MARK OF APPROVAL, RECOMMENDED DRY FILM THICKNESS 25 MICRONS, SPREADING RATE 10 M2/LITRE, DRYING TIME: TOUCH DRY 4HRS/23 DEG C, RE-COATING 16HRS/23 DEG C, DRY TO HANDLE 16HRS/23 DEG C, VISCOSITY 75 KREBS UNITS,MATERIAL SAFETY DATA SHEET THAT COMPLIES WITH THE OCCUPATIONAL HEALTH AND SAFETY ACT'S REGULATIONS TO BE SUPPLIED,NO SUBSTANCES AND/OR INGREDIENTS THAT FALL UNDER TABLE 1 CATAGORY WILL BE USED,ANY CHEMICAL FALLING UNDER TABLE 3 OF THE SAME REGULATIONS SHALL NOT BE USED,SHALL BE BIODEGRADABLE AND OZONE FRIENDLY,COPY OF MSDS TO BE SENT TO MEDICAL CENTRE AND SAFETY RISK		
159947	PAINT, OIL: TYPE: ENAMEL; COLOR: CREAM; CONTAINER: CAN 5 L; FINISH: HIGH GLOSS; SPECIFIC USE: EXTERIOR/INTERIOR; SPECIFICATION: SABS 630 GR 1; SUPPL P/N: HG3; REFERENCE NO: P5; SABS1091,REF C66,CKS279:1971-,RECOMMENDED DRY FILM THICKNESS 25 MICRONS,SPREADING RATE 10 M2/LITRE,DRY TIME:TOUCH DRY 4HRS/23 DEG C,RE-COATING 16HRS/23 DEG C,DRY TO HANDLE 16HRS/23 DEG C,VISCOSITY 70 KREBS UNITS,MATERIAL SAFETY DATA SHEETS THAT COMPLIES WITH THE OCCUPATIONAL HEALTH AND SAFETY ACT'S REGULATIONS TO BE SUPLIED,NO SUBSTANCES AND/OR INGREDIENTS THAT FALL UNDER TABLE 1 CATAGORY WILL BE USED,ANY CHEMICAL FALLING UNDER TABLE 3 OF THE SAME REGULATIONS SHALL NOT BE USED,SHALL BE BIODEGRADABLE AND OZONE FRIENDLY,COPY OF MSDS TO BE SENT TO MEDICAL CENTRE AND SAFETY RISK	13 000.00	L
159982	THINNER, PAINT: TYPE: LACQUER; CONTAINER: CAN 5 L; REFERENCE NO: A; ILS; SHOULD COMPLY WITH THE CHEMICAL HAZARDOUS SUBSTANCES	17 000.00	L

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Scope of Work for Supply and delivery of Plant Consumables on an "as and when required" at Hendrina Power Station for a Period of 5 Years

Unique Identifier:
Revision: 1
Page: 8 of 30

	REGULATION OF OCCUPATIONAL HEALTH AND SAFETY ACT; REQUIRED A MATERIAL SAFETY DATA SHEET WITH EVERY DELIVERY		
160050	BRUSH, PAINT: TYPE: SETTER; WIDTH: 25 MM; MATERIAL: BRISTLE CHINESE PURE; SHAPE: FLAT; HANDLE: PLASTIC; SIZE: 48MM LG X 16MM THK; THE ITEM MUST BE PROTECTIVE PACKE	2 500.00	EA
160051	BRUSH, PAINT: TYPE: SETTER; WIDTH: 50 MM; MATERIAL: BRISTLE CHINESE PURE; SHAPE: FLAT; HANDLE: PLASTIC	2 500.00	EA
160052	BRUSH, PAINT: TYPE: SETTER; WIDTH: 75 MM; MATERIAL: BRISTLE CHINESE PURE; SHAPE: FLAT; HANDLE: PLASTIC; SIZE: 65MM LG X 22MM THK; THE ITEM MUST BE PROTECTIVE PACKED	2 500.00	EA
160053	BRUSH, PAINT: TYPE: SETTER; WIDTH: 100 MM; MATERIAL: BRISTLE CHINESE PURE; SHAPE: FLAT; HANDLE: PLASTIC; LG 79 MM X THK 22 MM	2 500.00	EA
160055	BRUSH, PAINT: TYPE: WHITE WASH; WIDTH: 150 MM; MATERIAL: MANILA; SHAPE: FLAT; HANDLE: WOOD; 15MM THK	1 500.00	EA
160056	BRUSH, PAINT: TYPE: SETTER; WIDTH: 12 MM; MATERIAL: BRISTLE CHINESE PURE; SHAPE: FLAT; HANDLE: PLASTIC; SIZE: 48MM LG X 10MM THK; THE ITEM MUST BE PROTECTIVE PACKED	1 500.00	EA
160060	BRUSH, PAINT: TYPE: SETTER; WIDTH: 38 MM; MATERIAL: BRISTLE CHINESE PURE; SHAPE: FLAT; HANDLE: PLASTIC; SIZE: 55MM LG X 16MM THK	1 500.00	EA
160064	ROLLER: TYPE: PAINT; DIMENSIONS: WD 228 X LG 230 MM; MATERIAL: WOOL LAMB; HANDLE COVERED	2 500.00	EA
174241	PAINT, ENAMEL GOLDEN BROWN B13 5L ~ PAINT; ENAMEL; HIGH GLOSS; COLOUR GOLDEN BROWN; GRADE 1; PACKED IN 5 LITRE TIN; REF NO. HG31	13 000.00	L
174253	PAINT, LATEX: COLOR: IVORY; REFERENCE NO: HB120; PVA EMULSION TYPE; SYNTHETIC POLYMER BASED; 5 LITRE TIN	13 000.00	L
206782	PAINT, OIL: COLOR: HUDSON; CONTAINER: CAN 5 L; FINISH: SEMI GLOSS; SUPPL P/N: E14-2; REQUIRED	13 000.00	L

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an "as and when required" at Hendrina Power Station for a Period of 5 Years

Unique Identifier:
Revision: 1
Page: 9 of 30

	THE NEW STANDARD FOR RELIABILITY POINT 1 TO 16 MATERIAL SAFETY DATA SHEET WITH EVERY DELIVERY; EGGSHELL		
206783	PAINT, OIL: TYPE: EGGSHELL; COLOR: PAPYRUS; CONTAINER: CAN 5 L; FINISH: SEMI GLOSS; SUPPL P/N: E14-3; REQUIRED THE NEW STANDARD FOR RELIABILITY POINT 1 TO 16 MATERIAL SAFETY DATA SHEET WITH EVERY DELIVERY	13 000.00	L
206937	PAINT, OIL: COLOR: HUDSON; CONTAINER: CAN 5 L; FINISH: SUPER HIGH GLOSS; SUPPL P/N: E14-2; REQUIRED THE NEW STANDARD FOR RELIABILITY POINT 1 TO 16 MATERIAL SAFETY DATA SHEET WITH EVERY DELIVERY	13 000.00	L
206938	PAINT, OIL: COLOR: PAPYRUS; CONTAINER: CAN 5 L; FINISH: SUPER HIGH GLOSS; SUPPL P/N: E14-3; REQUIRED THE NEW STANDARD FOR RELIABILITY POINT 1 TO 16 MATERIAL SAFETY DATA SHEET WITH EVERY DELIVERY	13 000.00	L
217010	PAINT, WATER: COLOR: CHARCOAL; CONTAINER: DRUM 20 L; SPECIFIC USE: ROOFTOP; REFERENCE NO: TRP42	13 000.00	L
173128	GEYSER: TYPE: DUEL; CAPACITY: 150 L; POTENTIAL: 220 V; MOUNT: HORIZONTAL; POWER: 3 KW; ROUND TYPE; ECONOFLOW	2 500.00	EA
173129	GEYSER: TYPE: WATER; CAPACITY: 50 L; POTENTIAL: 230 V; CONNECTION LOCATION: SIDE; POWER: 3 KW; HORIZONTAL	1000.00	EA
120224	THERMOSTAT: TYPE: GEYSER; POTENTIAL: 250 V; CURRENT: 20 A; SUPPL P/N: VK7; REFERENCE NO: VK 83	2 000.00	EA
54360	ELEMENT: DIMENSIONS: DIA 35 X LG 280 MM; MATERIAL: NICR; TYPE: GEYSER; ELEMENT; TYPE: WNS; 11/4 BSP; INCONEL SHEATH; POTENTIAL: 200/220 VAC; POWER: 2 KW	2 500.00	EA
16208	SOLVENT: TYPE: DEGREASER; CONTAINER: DRUM 20 L; SUPPL P/N: F0128; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT	8 000.00	L

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an “as and when required” at Hendrina Power Station for a Period of 5 Years

Unique Identifier:
Revision: 1
Page: 10 of 30

160241	ADHESIVE: TYPE: COLD GLUE; CONTAINER: CAN 5 L; SUPPL P/N: ALCOLIN; REQUIRED THE NEW STANDARD FOR RELIABILITY, MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT	1000.00	L
160280	ADHESIVE: TYPE: SOLVENT CEMENT; CONTAINER: CAN 500 ML; FOR JOINTING PVC PIPES 24 HOUR DRYING TIME, MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT; SHELF LIFE; MANUFACTURING DATE; EXPIRY DATE	100	EA
160283	ADHESIVE: TYPE: NUT LOCK; CONTAINER: BOTTLE PLASTIC 50 G; SUPPL P/N: 243; REFERENCE NO: 250 T; MEDIUM STRENGTH; HPL 051242; COLOUR BLUE; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT; THE FOLLOWING IS REQUIRED WITH EVERY DELIVERY; SHELF LIFE; DATE OF MANUFACTURE AND METHOD OF STORAGE; LOCKTITE	1 500.00	EA
160299	ADHESIVE: TYPE: RUBBER BONDING; CONTAINER: BOTTLE PLASTIC 20 G; REFERENCE NO: LS12; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT; SHELF LIFE; MANUFACTURING DATE; EXPIRY DATE	2 000.00	EA
157675	SOLVENT: TYPE: EMULSION DEGREASER; CONTAINER: DRUM 25 L; COLOR: GREEN PAIL; TRADE NAME: SOLVEX; SUPPL P/N: ICE113; REFERENCE NO: 45011; ENGINE CLEANER IS A GENERAL-PURPOSE EMULSION DEGREASER APPROVED TO SABS 1216 TYPE1; MUST CONTAIN	4 000.00	L

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an “as and when required” at Hendrina Power Station for a Period of 5 Years

Unique Identifier:

Revision:

1

Page:

11 of 30

	SELECT EMULSIFIER FOR THE REMOVAL OF OIL; GREASE; DIRT AND GRIME FROM METAL SURFACES; EITHER BY IMMERSION SPRAY OR BY HAND APPLICATION; (1) SOLVENT BASE; (2) DENSITY 20 C = 0.813; (3) PH(10PCT SOLUTION) = 8.7; (4) FLASH POINT C MINIMUM(IP303) = 43; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT; MSDS TO BE SUPPLIED AS PART OF THE TENDER; NO SUBSTANCES AND/OR INGREDIENTS THAT FALL UNDER THE TABLE 1 CATEGORY OF THE HAZARDOUS CHEMICAL SUBSTANCES WILL BE USED; ANY CHEMICAL FALL UNDER TABLE 3 OF THE SAME REGULATIONS SHALL NOT BE USED WITHOUT THE PRIOR PERMISSION OF THE MEDICAL CENTRE AND SAFETY RISK; CHEMICALS SHALL BE BIODEGRADABLE AND OZONE FRIENDLY; A COPY OF THE MSDS FOR CHEMICALS		
157708	GREASE: CONTAINER: CAN 1 KG; TRADE NAME: SILICONE MOLYKOTE 55M; REFERENCE NO: 55M; REQUIRED THE NEW STANDARD FOR RELIABILITY POINT 1 TO 16 MATERIAL SAFETY DATA SHEET WITH EVERY DELIVERY; SHELF LIFE; MANUFACTURING DATE; EXPIRY DATE	200	KG
160406	BUCKET: TYPE: DOMESTIC; CAPACITY: 20 L; MATERIAL: PLASTIC; COLOR: WHITE; COMPLETE WITH METAL HANDLE AND SNAP ON LID	2 000.00	EA
158446	BIN, WASTE: TYPE: RUBBISH; DIMENSIONS: DIA (470 X 405) X HT 640 MM; MATERIAL: STL GALV; SEAM WELDED; COMPLETE WITH LID; 85L CAPACITY; SABS493 1954 AMENDMENT 1; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	2 500.00	EA
163013	TAPE, SAFETY BARRIER: DESIGNATION: CAUTION P.T.W. NO IN FORCE; VERSIGTIG P.T.W. NO IN WERKING; LAYOUT: YELLOW W/RED LETTERING; DIMENSIONS: WD 24 MM X	1 500.00	EA

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an "as and when required" at Hendrina Power Station for a Period of 5 Years

Unique Identifier:
Revision: 1
Page: 12 of 30

	LG 65 M; MATERIAL: PVC; SELF ADHESIVE		
174282	PAINT, TRAFFIC: COLOR: BLACK; CONTAINER: 5 L; SPECIFIC USE: ROAD MARKING; REFERENCE NO: TP28; LOW SHEEN FINISH, NON-REFLECTIVE, SPREADING RATE 30 M ROADLINE/LITRE, DRYING TIME 20 MINUTES, VISCOSITY 90 KREBS UNITS, MATERIAL SAFETY DATA SHEETS THAT COMPLIES WITH THE OCCUPATIONAL HEALTH AND SAFETY ACT'S REGULATIONS TO BE SUPPLIED, NO SUBSTANCES AND/OR INGREDIENTS THAT FALL UNDER TABLE 1 CATAGORY WILL BE USED, ANY CHEMICAL FALLING UNDER TABLE 3 OF THE SAME REGULATIONS SHALL NOT BE USED, SHALL BE BIODEGRADABLE AND OZONE FRIENDLY, COPY OF MSDS TO BE SENT TO MEDICAL CENTRE AND SAFETY RISK	6 000.00	L
159899	PAINT, OIL: TYPE: ZN CHROMATE; COLOR: RED OXIDE; CONTAINER: CAN 5 L; FINISH: GLOSS; SPECIFICATION: SABS 684-1972; SABS 679 TYPE 1; REFERENCE NO: A. 362-0814; WITH ALKYD BASED, MATERIAL SAFETY DATA SHEETS THAT COMPLIES WITH THE OCCUPATIONAL HEALTH AND SAFETY ACT'S REGULATIONS TO BE SUPPLIED, NO SUBSTANCES AND/OR INGREDIENTS THAT FALL UNDER TABLE 1 CATAGORY WILL BE USED, ANY CHEMICAL FALLING UNDER TABLE 3 OF THE SAME REGULATIONS SHALL NOT BE USED, SHALL BE BIODEGRADABLE AND OZONE FRIENDLY, COPY OF MSDS TO BE SENT TO MEDICAL CENTRE AND SAFETY RISK	6 000.00	L
159902	PAINT, PRIMER: TYPE: UNDERCOAT; CONTAINER: CAN 5 L; COLOR: WHITE; MATT FINISH, TO SABS681, UNIVERSAL, RECOMMENDED DRY FILM THICKNESS 20 MICRONS, SPREADING RATE 9 M2/LITRE, DRYING TIME: TOUCH DRY 4HRS/23 DEG C, RE-COATING 16HRS/23 DEG C, DRY TO HANDLE 16HRS/23 DEG C, VISCOSITY 75 KREBS UNITS, FEATURES: PROVIDE ADHESION TO MOST PRIMERS MAY BE OVER COATED BY ALKYD EMULSION BASE TOPCOAT SYSTEMS, MATERIAL SAFETY DATA SHEETS THAT COMPLIES WITH THE OCCUPATIONAL HEALTH AND SAFETY ACT'S REGULATIONS TO BE	6 000.00	L

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an "as and when required" at Hendrina Power Station for a Period of 5 Years

Unique Identifier:

Revision:

1

Page:

13 of 30

	SUPPLIED, NO SUBSTANCES AND/OR INGREDIENTS THAT FALL UNDER TABLE 1 CATEGORY WILL BE USED, ANY CHEMICAL FALLING UNDER TABLE 3 OF THE SAME REGULATION SHALL NOT BE USED, SHALL BE BIODEGRADABLE AND OZONE FRIENDLY, COPY OF MSDS TO BE SENT TO MEDICAL CENTRE AND SAFETY RISK		
159919	COATING, INSULATION: TYPE: VARNISH; CONTAINER: CAN 5 L; REFERENCE NO: CVI14; BONDING LIQUID REQUIRED THE NEW STANDARD FOR RELIABILITY MATERIAL SAFETY DATA SHEET POINT 1 TO 16 WITH EVERY DELIVERY	7 000.00	L
159922	COATING, INSULATION: TYPE: VARNISH; CONTAINER: CAN 5 L; REFERENCE NO: CVI14; BONDING LIQUID REQUIRED THE NEW STANDARD FOR RELIABILITY MATERIAL SAFETY DATA SHEET POINT 1 TO 16 WITH EVERY DELIVERY	3 000.00	L
160152	COATING: TYPE: RUST PROOF; CONTAINER TYPE: CAN; CONTAINER CAPACITY: 1 KG; SPECIFICATION: ISO 9001; SUPPL P/N: ARC855G; SAFETY DATA SHEET T, BE SUPPLIED WITH EVERY DELIVERY, 2 INCH (50 MM) PAINT BRUSH WITH EACH 1 KG, THIS IS TO APPLY	1 500.00	KG
667547	PIPE: INSIDE DIAMETER: 22 MM; LENGTH: 6 M; MATERIAL: COPPER	1 000.00	M
16869	ADHESIVE: TYPE: CONTACT; CONTAINER: CAN 500 ML; HEAT AND WATER RESISTANCE, MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT; SHELF LIFE; MANUFACTURING DATE; EXPIRY DATE	1 000.00	EA
159822	ABSORBENT: TYPE: ORGANIC; FORM: FIBER LOOSE; CONTAINER CAPACITY: 10 KG; CONTAINER: BAG; 100 PCT, NON TOXIC COMPOST, BIODEGRADABLE, PLEASE NOTE; THE ITEM WILL NOT BE ACCEPTED WITHOUT A MATERIAL SAFETY DATA SHEET; FIBRE - SORB	5 000.00	EA
159839	ABSORBENT: TYPE: OIL; FORM: FIBER LOOSE; CONTAINER CAPACITY: 10 KG; CONTAINER: BAG; SUPPL P/N: DRIZIT; REQUIRED A MATERIAL	5 000.00	EA

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an "as and when required" at Hendrina Power Station for a Period of 5 Years

Unique Identifier:

Revision:

1

Page:

14 of 30

	SAFETY DATA SHEET WITH EVERY DELIVERY		
206297	DRUM, STORAGE: TYPE: HAZARDOUS WASTE; CAPACITY: 210 L; STYLE: LID/STRAP; MATERIAL: STL; THE DRUMS WILL BE USED FOR THE DISPOSAL AND STORAGE; EACH RECEIVED NEEDS TO BE CHECKED BY QUALITY DEPARTMENT, IT SHOULD ALSO BE STATED WHEN SUPPLIER IS APPROACHED THAT IT HAS TO MEET SPECIFIC REQUIREMENTS AS THE TYPE AND QUALITY COULD RESULT IN EXPENSIVE SPILLAGE CLEAN UP AND OR FINES/PENALTIES FROM GOVERNMENT, LOCKING MECHANISM: PUSH AND PULL; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	4 000.00	EA
57510	CLAMP, HOSE: TYPE: STAINLESS STEEL; INSIDE DIAMETER: 32-14 MM; WIDTH: 14-32 MM; MATERIAL: STAINLESS STEEL; FASTENING DEVICE TYPE: WORM DRIVE; SPECIFICATION: GRADE 316 HOSE CLAMP STAINLESS STEEL; THE ITEM MUST BE ORIGINAL PROTECTIVE PACKED; GRADE 316 - HOSE CLAMP STAINLESS; DIMENSIONS 14 - 32MM PER PACK OF 10	4 000.00	EA
57505	CLAMP, HOSE: INSIDE DIAMETER: 22-10 MM; MATERIAL: STAINLESS STEEL; FASTENING DEVICE TYPE: WORM DRIVE; SPECIFICATION: SABS 814; SUPPL P/N: GM6; REFERENCE NO: 2	4 000.00	EA
57508	CLAMP, HOSE: INSIDE DIAMETER: 38-17 MM; MATERIAL: STAINLESS STEEL; FASTENING DEVICE TYPE: WORM DRIVE; SUPPL P/N: GS16	4 000.00	EA
57509	CLAMP, HOSE: INSIDE DIAMETER: 57-32 MM; MATERIAL: STAINLESS STEEL; FASTENING DEVICE TYPE: WORM DRIVE; SUPPL P/N: GSS28; SUPPLIER PART NUMBER: GSS28	4 000.00	EA
59518	CLAMP, HOSE: INSIDE DIAMETER: 63-38 MM; MATERIAL: STAINLESS STEEL; FASTENING DEVICE TYPE: WORM DRIVE; SUPPL P/N: GS32	4 000.00	EA
173425	BARREL BOLT; TYPE: PAD; DIMENSIONS: DIA 12 X LG 200 X WD 50 MM; MATERIAL: STL GALV; SIZE 13 MM DIA	4 000.00	EA

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an “as and when required” at Hendrina Power Station for a Period of 5 Years

Unique Identifier:

Revision: 1

Page: 15 of 30

1983	BARREL BOLT: TYPE: GOOSENECK; DIMENSIONS: DIA 7.5 X LG 64 MM; MATERIAL: BRASS; 25MM WIDE WITH OFFSET BOLT; SOLID BRAND ONLY	2 000.00	EA
159885	PAINT, TRAFFIC: COLOR: WHITE; CONTAINER: 5 L; SPECIFIC USE: ROAD MARKING; REFERENCE NO: TP24; NON-REFLECTIVE FINISH, CONTROLLING DESIGNATOR: CSK279, SABS731; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT	17 000.00	L
93786	RIVET, BLIND: TYPE: POP; DIAMETER: 3.2 MM; LENGTH: 6 MM; HEAD DIAMETER: 6.2 MM; MATERIAL: ALUMINIUM; HEAD: DOME; GRIP RANGE: 0-3 MM; GRIP RANGE: 5MM TO 12MM, HOLE SIZE 3.25MM TO 3.35MM, DRILL SIZE 3.3MM, IN PACKETS OF 100	10 000.00	EA
93788	RIVET, BLIND: TYPE: POP; DIAMETER: 3.2 MM; LENGTH: 10 MM; HEAD DIAMETER: 6.4 MM; MATERIAL: ALUMINIUM; HEAD: DOME; GRIP RANGE: 4-7 MM	10 000.00	EA
93839	RIVET, BLIND: TYPE: POP; DIAMETER: 4.8 MM; LENGTH: 12 MM; HEAD DIAMETER: 9.5 MM; MATERIAL: STL; HEAD: DOME; GRIP RANGE: 9 MM	10 000.00	EA
655879	RIVET, BLIND: TYPE: FLANGE; DIAMETER: 4.8 MM; LENGTH: 8 MM; HEAD DIAMETER: 16 MM; MATERIAL: ALUMINIUM; SUPPLIED IN QUANTITY OF 100 PER PACK	10 000.00	EA
403775	PUTTY: TYPE: SOFT, SPOT FILLER; CONTAINER TYPE: PACK; CONTAINER CAPACITY: 5 KG; COLOR: GRAY; APPLICATION: WINDOW GLAZING; REFERENCE NO: MCP3; WITH HARDNER	2 500.00	EA
109469	CLOTH, ABRASIVE: TYPE: SANDING; FLINT/EMERY GRADE DESIGNATOR: 100; OVERALL WIDTH: 50 MM; LENGTH: 50 M; ABRASIVE MATERIAL: AL OXIDE; BACKING MATERIAL: RESIN	500.00	EA
109463	PAPER, ABRASIVE: TYPE: SANDING; OVERALL WIDTH: 230 MM; LENGTH: 250 MM; GRIT: 120; ABRASIVE MATERIAL: GLASS; BACKING MATERIAL: PAPER; USAGE FORM: SHEET; FINE	2 000.00	EA

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an “as and when required” at Hendrina Power Station for a Period of 5 Years

Unique Identifier:

Revision:

1

Page:

16 of 30

109464	PAPER, ABRASIVE: TYPE: SANDING; OVERALL WIDTH: 230 MM; LENGTH: 250 MM; GRIT: M; ABRASIVE MATERIAL: GLASS; BACKING MATERIAL: PAPER	2 000.00	EA
109477	CLOTH, ABRASIVE: TYPE: SANDING; FLINT/EMERY GRADE DESIGNATOR: 60; OVERALL WIDTH: 50 MM; LENGTH: 50 M; ABRASIVE MATERIAL: AL OXIDE; BACKING MATERIAL: RESIN; BOND	500.00	EA
109535	CLOTH, ABRASIVE: TYPE: POLISHING; FLINT/EMERY GRADE DESIGNATOR: 320; OVERALL WIDTH: 230 MM; LENGTH: 350 MM; BACKING MATERIAL: RESIN; SHEET	2 000.00	EA
011523	TIE, CABLE: TYPE: SELF LOCKING; DIAMETER RANGE: 120 MM; WIDTH: 7.6 MM; LENGTH: 385 MM; MATERIAL: NYLON; COLOR: BLACK; SUPPL P/N: T120R; 15 KG STRENGTH, EACH = ONE PACKET OF FIFTY	8 000.00	EA
137096	TIE, CABLE: TYPE: SELF LOCKING; DIAMETER RANGE: 110-5 MM; WIDTH: 4.7 MM; LENGTH: 395 MM; MATERIAL: PLASTIC; STRENGTH: 15 KG; COLOR: BLACK; SUPPL P/N: T50L	19 000.00	EA
108843	TIE, CABLE: TYPE: SELF LOCKING; WIDTH: 4.7 MM; LENGTH: 305 MM; MATERIAL: NYLON; COLOR: BLACK; REFERENCE NO: T50I; PLASTIC, 100 PER PACKET	8 500.00	EA
10142	TAPE, ELECTRICAL: WIDTH: 18 MM; LENGTH: 20 M; MATERIAL: VINYL; COLOR: BLACK; PVC; TO SABS 122; 0.18MM THK; ADHESIVE	500.00	EA
10143	TAPE, ELECTRICAL: WIDTH: 18 MM; LENGTH: 20 M; MATERIAL: VINYL; COLOR: BLUE; PVC; TO SABS 122; 0.18MM THK; ADHESIVE	400.00	EA
10144	TAPE, ELECTRICAL: WIDTH: 18 MM; LENGTH: 20 M; MATERIAL: VINYL; COLOR: RED; PVC; TO SABS 122; 0.18MM THK; ADHESIVE	400.00	EA
135183	TAPE, ELECTRICAL: WIDTH: 18 MM; LENGTH: 20 M; MATERIAL: PVC; COLOR: GREEN; 0.18MM THK; ADHESIVE	350.00	EA
16494	TAPE, ADHESIVE: TYPE: MASKING; DIMENSIONS: WD 24 MM X LG 40 M; MATERIAL: PAPER; COLOR: BUFF; BORE 75MM; MOISTURE OIL AND SOLVENT RESISTANT	4 000.00	EA
108549	PADLOCK: TYPE: KEY; SHACKLE DIAMETER: 6 MM; CASE SIZE: WD 33	5 500.00	EA

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an "as and when required" at Hendrina Power Station for a Period of 5 Years

Unique Identifier:

Revision:

1

Page:

17 of 30

	X THK 40 MM; MATERIAL: BRASS; VERTICAL CLEARANCE: 20 MM; HORIZONTAL CLEARANCE: 23 MM; UNION BRAND ONLY		
1981	PADLOCK: TYPE: KEY; SHACKLE DIAMETER: 8 MM; CASE SIZE: WD 50 X LG 40 X THK 17 MM; MATERIAL: BRASS; VERTICAL CLEARANCE: 45 MM; HORIZONTAL CLEARANCE: 50 X 40 MM; REFERENCE NO: 303; PIN TUMBLER MECHANISM; HARDENED STEEL SHACKLE; 76MM OVERALL LENGTH; VIRO BRAND ONLY	350.00	EA
108549	PADLOCK: TYPE: KEY; SHACKLE DIAMETER: 6 MM; CASE SIZE: WD 33 X THK 40 MM; MATERIAL: BRASS; VERTICAL CLEARANCE: 20 MM; HORIZONTAL CLEARANCE: 23 MM; UNION BRAND ONLY	600.00	EA
108767	LOCK: TYPE: DOOR; MATERIAL: STL; REFERENCE NO: CZ6822461CH; SETS, 4 LEVER	5 000.00	EA
157684	CLEANER: TYPE: CONTACT ANTI RUST; FORM: AEROSOL; CONTAINER: CAN 500 G; COMPOUND FOR SWITCHES, CONTACT AND BREAKERS; PACKED 12 PER BOX; SPANJAARD SPARK BRAND ONLY; REQUIRED THE NEW STANDARD FOR RELIABILITY; MATERIAL SAFETY DATA SHEET POINT 1 TO 16	1 500.00	EA
160097	LUBRICANT: TYPE: ANTI SEIZE; FORM: LIQUID; CONTAINER: CAN 723 G; REFERENCE NO: 0160155; COLOUR BLUE, 50 PCT VOLATILE, FLASH POINT 49 DEG C, METHOD TAG CLOSED CUP, VISCOSITY 100 CPS AT 25 DEG C, DENSITY 0.83 KG, WEIGHT PER VOLUME 6.91BS, GAS AROMATICS BY WEIGHT 2.46	1 000.00	EA
160171	CLEANER: TYPE: CONTACT ANTI RUST; FORM: AEROSOL; CONTAINER: CAN 400 G; ELECTRO; CRC2-26; MUST BE OZONE FRIENDLY; USE AS WATER REPELLENT ON ALL ELECTRICAL SWITCHGEAR; CHEMICAL - MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT; THE FOLLOWING IS REQUIRED WITH EVERY DELIVERY; SHELF LIFE; DATE OF MANUFACTURE AND METHOD OF STORAGE	1 500.00	EA

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an "as and when required" at Hendrina Power Station for a Period of 5 Years

Unique Identifier:

Revision: 1

Page: 18 of 30

179462	PENETRANT: CONTAINER: CAN AEROSOL 400 ML; TRADE NAME: SPOOKPIZZ; FLUID, NON FLAMMABLE HAZARD CLASS 2.2 REQUIRED THE NEW STANDARD FOR RELIABILITY POINT 1 TO 16 MATERIAL SAFETY DATA SHEET WITH EVERY DELIVERY COMPULSORY	4 000.00	EA
161470	PENETRANT: TYPE: FLUID; CONTAINER: CAN 350 ML; REQUIRED THE NEW STANDARD FOR RELIABILITY POINT 1 TO 16 MATERIAL SAFETY DATA SHEET WITH EVERY DELIVERY COMPULSORY	2 000.00	EA
157684	CLEANER: TYPE: CONTACT ANTI RUST; FORM: AEROSOL; CONTAINER: CAN 500 G; COMPOUND FOR SWITCHES, CONTACT AND BREAKERS; PACKED 12 PER BOX; SPANJAARD SPARK BRAND ONLY; REQUIRED THE NEW STANDARD FOR RELIABILITY; MATERIAL SAFETY DATA SHEET POINT 1 TO 16	1 500.00	EA
16853	TAPE, THREAD: TYPE: SEALING; WIDTH: 10 MM; MATERIAL: PTFE; COLOR: WHITE; REFERENCE NO: PTFE; WITHOUT DISPENSER; THK 0.075 MM	6 000.00	EA
162998	TAPE, SAFETY BARRIER: DESIGNATION: WARNING; LAYOUT: RED/WHITE; DIMENSIONS: WD 75 MM X LG 500 M; MATERIAL: PVC; TAPE, SAFETY BARRIER; DESIGNATION WARNING, DIMENSIONS WD 75MM X LG 500M, LAYOUT RED/WHITE, MATERIAL PVC, REFERENCE NO: BARRIER~TAPE, SFTY BARR; WARNING, RED/WHITE, PVC	500.00	EA
160186	COMPOUND, CAULKING: TYPE: SI RUBBER; COLOR: CLEAR; CONTAINER: CARTRIDGE 310 ML; REQUIRED THE NEW STANDARD FOR RELIABILITY POINT 1 TO 16 MATERIAL SAFETY DATA SHEET WITH EVERY DELIVERY; SHELF LIFE; MANUFACTURING DATE; EXPIRY DATE	3 000.00	EA
144646	BATTERY, DRY CELL: MATERIAL: ALKALINE; POTENTIAL: 1.5 VDC; DIMENSIONS: AA; CONNECTION: FLAT PIN; SUPPL P/N: MN1500; SAFETY DATA SHEETS REQUIRED ON DELIVERY HAZARDOUS SUBSTANCES, THIS PRODUCT IS CLASSIFIED AS HAZARDOUS SUBSTANCE AND SAFETY BROCHURES MUST ACCOMPANY DELIVERY, IN ACCORDANCE WITH THE OCCUPATIONAL HEALTH AND SAFETY	6 000.00	EA

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an “as and when required” at Hendrina Power Station for a Period of 5 Years

Unique Identifier:
Revision: 1
Page: 19 of 30

	ACT OHSA, ACT 85 OF 1993 SECTION 10 AND 11; SIZES LR6/R6PP/AA/UM3/MN1500; DIMEN: 14X50MM LG		
144659	BATTERY, DRY CELL: MATERIAL: ALKALINE; POTENTIAL: 1.5 VDC; DIMENSIONS: AAA; CONNECTION: FLAT TERMINALS; SUPPL P/N: MN2400	5 000.00	EA
144652	BATTERY, DRY CELL: MATERIAL: ALKALINE; POTENTIAL: 1.5 VDC; DIMENSIONS: D; CONNECTION: FLAT TERMINALS; SUPPL P/N: MN1300; REFERENCE NO: LR20; AMP HOUR 1300MIN, SAFETY DATA SHEETS REQUIRED ON DELIVERY HAZARDOUS SUBSTANCES; THIS PRODUCT IS CLASSIFIED AS A HAZARDOUS SUBSTANCE AND SAFETY BROCHURES MUST ACCOMPANY DELIVERY; IN ACCORDANCE WITH THE OCCUPATIONAL HEALTH AND SAFETY ACT (OHSA) ACT85 OF 1993 SECTION 10 AND 11	3 200.00	EA
623707	TORCH: TYPE: SWITCH TWIST; DIMENSIONS: ADJUSTABLE; MATERIAL: AL ALLOY; DIMENSIONS 23 X 5.5 X 2.6CM/ 9.06 X 2.17 X 1.02IN; THE TOTAL DIMENSIONS IS LENGTH X HEAD X BODY DIAMETER; MODEL OF LED: CREE XM-L T6 LED; LED QUANTITY: 3 PIECES; LIGHT COLOUR: WHITE; LUMEN: 4000LM; BATTERY: 2 X 18650; SWITCH LOCATION: TAIL; CASING COLOUR: BLACK; PACKAGE SIZE 24 X 8 X 7.5CM/ 9.45 X 3.15 X 2.95IN; PACKAGE WEIGHT: 363G/ 12.80OZ	1 000.00	EA
146089	FLASHLIGHT: TYPE: RECHARGEABLE; CELL: (1) 6 V; LENS COLOR: CLEAR; MATERIAL: PLASTIC; POWER: 10 W; SUPPL P/N: FL-006; MODEL NO: BF 776; NATIONAL MIGHTY LIGHT; LED LIGHT	1 500.00	EA
146095	FLASHLIGHT: CELL: (3) D; LENS COLOR: CLEAR; MATERIAL: RUBBER; POWER: 5 W; SUPPL P/N: RM18; WITH PUSH BUTTON SINGLE CONTACT, GLASS LENS/LAMP, CASE STRAIGHT TUBULAR; RANGE 3 X 1.5VDC 0.5A	1 000.00	
597202	TORCH: TYPE: PROTECTIVE HELMET HEADLAMP; DIMENSIONS: ADJUSTABLE; SHALL BE INTRINSICALLY SAFE; PROVIDE AT LEAST 400 LUMENS AT 20 METER FOR 6 HOURS AND MUST BE ABLE TO FIT ALL TYPES OF PROTECTIVE HELMETS	4 000.00	EA

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an “as and when required” at Hendrina Power Station for a Period of 5 Years

Unique Identifier:

Revision: 1

Page: 20 of 30

630868	LOCK: TYPE: PANEL KEY; DIMENSIONS: THK 4 MM; MATERIAL: DIE CAST; COLOR: SILVER; MANUF P/N: KEY-P4	1 500.00	EA
16511	PAPER, BOND: SIZE: A3; COLOR: WHITE; USAGE FORM: SHEET; NOMINAL BASIS WEIGHT: 80 G/M2; SPECIFIC USE: PHOTO COPYING; PACKAGE TYPE: REAM; PACKAGE QUANTITY: 500 PAGES; REFERENCE NO: A3-80GSM; 500 PER REAM; SIZE: 297 MM WD X 420 MM LG	10 000.00	EA
17223	TWINE: TYPE: M; MATERIAL: COTTON; COLOR: WHITE; SIZE: 3 MM; REFERENCE NO: 304; SUPPLIED IN 500 G ROLLS; FOR OFFICE USE	2 000.00	EA
16878	CLOTH, KNITTED: FIBER MATERIAL: COTTON; WIDTH: 290 MM; COLOR: WHITE; TYPE MUTTON; PLAIN, IN 1 KG ROLL	5 000.00	EA
16810	CLOTH: TYPE: CLEANING RAGS; MATERIAL: COTTON 100 PCT; NEW COLOURED INTERLOCK WIPERS, PACKED IN 5 KILOGRAM BUNDELS AND SUPPLIED IN 50 KILOGRAM BAILS; SIZE: 5 KG	20 000.00	KG
632261	PLUG: TYPE: SOCKET; SIZE: LG 115 MM; MATERIAL: PLASTIC; 3 PIN PLUG; SWITCH OUTLET IP66; UNIQUE SEALING OF CABLE INLET; 15 AMPS RATED CURRENT; 2 POLE EARTH; SURFACE MOUNTING BOX LG 95 X HT 95 MM	500.00	EA
79651	LUBRICATING GUN, HAND: OPERATION METHOD: MANUAL; CAPACITY: 315 ML; LUBRICANT TYPE: SILICON; SEALANT APPLICATOR, FOR TUBES	50.00	EA
160096	COMPOUND, SEALING: TYPE: GASKET; COLOR: RED; CONTAINER: CARTRIDGE 280 ML; MATERIAL: RUBBER SI; REFERENCE NO: RTV 736; HIGH TEMPERATURE SILASTIC SEALANT; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT	12 000.00	EA
160186	COMPOUND, CAULKING: TYPE: SI RUBBER; COLOR: CLEAR; CONTAINER: CARTRIDGE 310 ML; REQUIRED THE NEW STANDARD FOR RELIABILITY POINT 1 TO 16 MATERIAL SAFETY DATA SHEET WITH EVERY DELIVERY;	2 000.00	EA

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an “as and when required” at Hendrina Power Station for a Period of 5 Years

Unique Identifier:

Revision:

1

Page:

21 of 30

	SHELF LIFE; MANUFACTURING DATE; EXPIRY DATE		
218431	GREASE: TYPE: SILICON; TEMPERATURE RATING: 600 DEG C; CONTAINER: CAN 500 G; MATERIAL SAFETY DATA SHEET TO BE SUPPLIED ON DELIVERY	50.00	EA
108523	BUCKLE: TYPE: STRAP; DIMENSIONS: WD 18 X LG 23 MM; MATERIAL: STAINLESS STEEL; REFERENCE NO: C253; FOR 9.5MM (3/8 IN) STRAPPING; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	200.00	EA
108526	BAND, STRAPPING: WIDTH: 9.5 MM; THICKNESS: 0.7 MM; LENGTH: 30 M; MATERIAL: STAINLESS STEEL; SUPPL P/N: 5304S9.5; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	150.00	EA
184018	SEAL, RING: INSIDE DIAMETER: 18 MM; OUTSIDE DIAMETER: 25.4 MM; MATERIAL: PTFE; WITH A CHAMFER ON ONE SIDE; 4.3MM ON THE INSIDE X 2.9MM ON THE OUTSIDE; FOR USE ON DP TRANSMITTERS	5 000.00	EA
90448	WASHER, SEALING: NOMINAL SIZE: 16.2 MM; INSIDE DIAMETER: 6.35 MM; OUTSIDE DIAMETER: 16.2 MM; THICKNESS: 3 MM; MATERIAL: COPPER; FOR USE ON TRANSMITTERS	5 000.00	EA
17792	KIT: TYPE: ADHESIVE; COMPRISING: HARDNER PUTTY STICK 125 G; WHITE AND BROWN, GENERAL HEAVY DUTY USE, SHOULD COMPLY WITH THE CHEMICAL HAZARDOUS SUBSTANCES REGULATION OF OCCUPATIONAL HEALTH AND SAFETY ACT, CHEMEALS TO BE SUPPLIED WITH MSDS AND SECTION 12 (ECOLOGICAL INFORMATION OF THE MSDS TO BE COMPLETED IN DETAIL) WITH EVERY DELIVERY	50.00	EA
160300	ADHESIVE: TYPE: EPOXY; CONTAINER: CAN (2) 250 ML; SUPPL P/N: PRATLEY CLEAR; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE	50.00	EA

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an "as and when required" at Hendrina Power Station for a Period of 5 Years

Unique Identifier:

Revision:

1

Page:

22 of 30

	OCCUPATIONAL HEALTH AND SAFETY ACT; CLEAR		
16869	ADHESIVE: TYPE: CONTACT; CONTAINER: CAN 500 ML; HEAT AND WATER RESISTANCE, MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT; SHELF LIFE; MANUFACTURING DATE; EXPIRY DATE	100.00	EA
37881	WHEELBARROW: TYPE: GENERAL PURPOSE PAN; SIZE: 350 X 76 MM; MATERIAL: STL; MODEL NO: TH163-11CP; TUBULAR FRAME WITH SIZE 14 IN X 3IN SOLID RUBBER TYRE WITH PLAIN BEARINGS	600.00	EA
109082	WHEEL: TYPE: WHEELBARROW; HUB SIZE: 25 MM; OUTSIDE DIAMETER: 355 MM; WIDTH: 75 MM; MATERIAL: RUBBER; REFERENCE NO: WSS 1430 P; SOLID TYPE	500.00	EA
241238	SHOVEL: TYPE: SQ MOUTH; BLADE SIZE: WD 260 MM; BLADE MATERIAL: STL; HANDLE: STL 625 MM; SUPPL P/N: FG00350; REFERENCE NO: 135	2 000.00	EA
79611	BLADE, SAW: SAW TYPE: JIG; TOOTH DESIGN: FINE; TEETH PER INCH: 20; BLADE MATERIAL: HSS; CUT MATERIAL: PLYWOOD PRE FINISHED PANEL; REFERENCE NO: T118A OR 23637; TYPE 2608631 013; 1.2 MM PITCH; PACKED IN FIVES; SIZE: WD 8 MM X LG 75 MM	2 000.00	EA
1001	BLADE, SAW: SAW TYPE: HACK; TOOTH DESIGN: COARSE; TEETH PER INCH: 18; BLADE MATERIAL: HSS; CUT MATERIAL: METAL; SIZE 13MM WD X 305MM LG X 0.6MM THK, 10D/18T, SHATTERPROOF, ULTRA B1 HARD COBALT	2 000.00	EA
5855	CONNECTOR, LUG: TYPE: CRIMPING LUG; CONDUCTOR: 6 MM2; HOLE SIZE: M5; MATERIAL: CU TIN PLTD; TERMINATION END: RING; INSULATION: NON INSULATED; CONDUCTOR CONNECTION: COMPRESSION/CRIMP; REFERENCE NO: YAV10M5; 60-5	3 000.00	EA
144788	WIRE, ELECTRICAL: TYPE: HEAT RESISTANT; SIZE: 1.9 MM2; COLOR: BLACK; STRUCTURE: 28 STRAND;	2 500.00	M

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an “as and when required” at Hendrina Power Station for a Period of 5 Years

Unique Identifier:

Revision:

1

Page:

23 of 30

	MATERIAL: CU; INSULATION: PVC; SILICON SHEATH; SINGLE CORE		
145097	WIRE, ELECTRICAL: TYPE: BUILDING; SIZE: 2.5 MM2; COLOR: BLUE; STRUCTURE: MULTISTRAND; MATERIAL: CU ANNEALED; INSULATION: SILICON; RATING: 500 V; CORE MATERIAL: GLASS BRAIDED; FLEXIBLE; SINGLE CORE	2 500.00	M
159839	ABSORBENT: TYPE: OIL; FORM: FIBER LOOSE; CONTAINER CAPACITY: 10 KG; CONTAINER: BAG; SUPPL P/N: DRIZIT; REQUIRED A MATERIAL SAFETY DATA SHEET WITH EVERY DELIVERY	4 000.00	KG
160135	INHIBITOR: TYPE: ANTI CORROSIVE METAL COATING; CONTAINER: CAN 5 L; TRADE NAME: SAFIC CORCOAT; FOR USE OF COATING ALL ITEMS FABRICATED REF SAF CORCOAT COLOUR RED REQUIRED THE NEW STANDARD FOR RELIABILITY POINT 1 TO 16 MATERIAL SAFETY DATA SHEET WITH EVERY DELIVERY	13 000.00	L
17038	FUEL, PARAFFIN: FUEL GRADE: REGULAR; UNIT PACKAGE TYPE: PLASTIC DRUM; UNIT PACKAGE QUANTITY: 20 L; TYPE: ILLUMINATING; MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT; NO SUBSTANCES AND/OR INGREDIENTS THAT FALL UNDER TABLE 1 CATAGORY WILL BE USED; ANY CHEMICAL FALLING UNDER TABLE 3 OF THE SAME REGULATIONS SHALL NOT BE USED; SHALL BE BIODEGRADABLE AND OZONE FRIENDLY; COPY OF MSDS TO BE SENT TO MEDICAL CENTRE AND SAFETY RISK; PLEASE ENSURE THAT THE PLASTIC CONTAINER TO BE SUPPLIED IN IS NOT SEE THRU AND IS MARKED ACCORDINGLY	2 000.00	L
1986	BOLT, ANCHOR: TYPE: RAW LOOSE; DIAMETER: M10; THREAD LENGTH: 75 MM; MATERIAL: STL; LENGTH: 75 MM; THREAD: 1.5 MM; REFERENCE NO: E19; SIZE 60 MM SHIELD LENGTH, 20 MM FIXING THICKNESS, 1.5 MM PITCH, RECOMMENDED DRILL SIZE 18MM	6 000.00	EA

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an “as and when required” at Hendrina Power Station for a Period of 5 Years

Unique Identifier:

Revision:

1

Page:

24 of 30

1985	BOLT, ANCHOR: TYPE: RAW LOOSE; DIAMETER: M6; THREAD LENGTH: 50 MM; MATERIAL: STL; LENGTH: 58 MM; THREAD: 1 MM; REFERENCE NO: C19; 48MM SHIELD LENGTH INDLUCING NUT, 12MM MAXIMUM FIXING THICKNESS, DRILL SIZE 12MM	6 000.00	EA
108520	BOLT, ANCHOR: TYPE: RAWL; DIAMETER: M5; MATERIAL: STL; LENGTH: 50 MM; REFERENCE NO: A19; ANCHOR MATERIAL: STL; ANCHOR SIZE: DIA 8 X LG 38 MM; DRILL SIZE: 9 MM; SCREW SIZE: M5; THREAD LENGTH: 50 MM; TYPE: RAWLBOLT	6 000.00	EA
159645	BRUSH, WIRE: TYPE: WELDER; TRIM LENGTH: 30 MM; DIMENSIONS: WD 45 X LG 290 X HT 50 MM; MATERIAL: STL; HANDLE: WOOD; SUPPL P/N: W053-003; REFERENCE NO: 1 67; 5 ROW	200.00	EA
109172	CLOTH, ABRASIVE: TYPE: FINISH; FLINT/EMERY GRADE DESIGNATOR: 60; OVERALL WIDTH: 150 MM; LENGTH: 50 M; ABRASIVE MATERIAL: AL OXIDE; BACKING MATERIAL: PAPER ADHESIVE; COARSE; BOND/BACKING	100.00	EA
81990	SET: QUANTITY: BOX 500; COMPRISING: SELF TAPPING SCREW; SIZE RANGE: 4-14; ASSORTED SIZES	1 500.00	EA
161747	SHEET, PLASTIC: WIDTH: 1.22 MM; LENGTH: 1.83 M; THICKNESS: 6.3 MM; MATERIAL: PERSPEX; COLOR: CLEAR; ACRYLIC TYPE, PROTECTED WITH SELLOPHANE	600.00	EA
161746	SHEET, PLASTIC: WIDTH: 1.22 M; LENGTH: 1.83 M; THICKNESS: 3.1 MM; MATERIAL: PERSPEX; COLOR: CLEAR; REFERENCE NO: 3,1MM; (C.O.C; Q4:NSF:NC:NEV); ACRYLIC TYPE; PROTECTED WITH SELLOPHANE	600.00	EA
159921	PAINT, OIL: TYPE: ENAMEL; COLOR: IVORY; CONTAINER: CAN 5 L; FINISH: GLOSS; SPECIFIC USE: INTERIOR; SUPPL P/N: HM2; REFERENCE NO: B77,182/L; EGGSHELL, PLASCON HYSHEEN , TO THE LATEST EDITION OF SABS 515/1091/1975 AND BEARING THE SABS MARK OF APPROVAL, RECOMMENDED DRY FILM THICKNESS 25 MICRONS, SPREADING RATE 10 M2/LITRE, DRYING TIME: TOUCH DRY 4HRS/23 DEG C, RE-COATING	2 500.00	L

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an “as and when required” at Hendrina Power Station for a Period of 5 Years

Unique Identifier:
Revision: 1
Page: 25 of 30

	16HRS/23 DEG C, DRY TO HANDLE 16HRS/23 DEG C, VISCOSITY 75 KREBS UNITS,MATERIAL SAFETY DATA SHEET THAT COMPLIES WITH THE OCCUPATIONAL HEALTH AND SAFETY ACT'S REGULATIONS TO BE SUPPLIED,NO SUBSTANCES AND/OR INGREDIENTS THAT FALL UNDER TABLE 1 CATAGORY WILL BE USED,ANY CHEMICAL FALLING UNDER TABLE 3 OF THE SAME REGULATIONS SHALL NOT BE USED,SHALL BE BIODEGRADABLE AND OZONE FRIENDLY,COPY OF MSDS TO BE SENT TO MEDICAL CENTRE AND SAFETY RISK		
159917	PAINT, OIL: TYPE: CHLORINATED RUBBER; COLOR: BLACK; CONTAINER: CAN 5 L; FINISH: NON SLIP; DRYING SPEED: FAST; REFERENCE NO: CHC3000; HIGH BUILD VINYL PAINT, NON-THIXOTROPIC VINYL COPOLYMER ENAMEL, VOLUME SOLIDS: 27-31PERCENT, RECOMMENDED DFT: MIN = 25UM MAX = 35UM, VISCOSITY AT 25 DEGEES CELCIUS: 60 - 65KU, HIGH CHEMICAL RESISTANCE, TO BE SUPPLIED WITH HAZARDOUS CHEMICAL DATA SHEET	2 500.00	L
158819	BRUSH, PAINT: TYPE: STENCIL; MATERIAL: BRISTLE CHINA BLACK; SHAPE: RD; HANDLE: WOOD; REFERENCE NO: NO. 8; SIZE: 35MM DIA X 175MM LG	100.00	EA
520392	AGGREGATE: TYPE: G5 SUB-BASE; CONTAINER: TRUCK LOAD	250	TON
160241	ADHESIVE: TYPE: COLD GLUE; CONTAINER: CAN 5 L; SUPPL P/N: ALCOLIN; REQUIRED THE NEW STANDARD FOR RELIABILITY, MATERIAL SAFETY DATA SHEETS WITH ENVIRONMENTAL INFORMATION IN THE 16 POINT FORMAT TO BE PROVIDED WITH EVERY DELIVERY AS REQUIRED BY THE OCCUPATIONAL HEALTH AND SAFETY ACT	200.00	L
36044	DISK, CUTTING: OUTSIDE DIAMETER: 100 MM; ARBOR SIZE: 16 MM; THICKNESS: 2.5 MM; GRIT: 80; ABRASIVE MATERIAL: AL OXIDE; SPEED: 15300 RPM; BOND/BACKING: RESINOID; USAGE DESIGN: STL; REFERENCE NO: 80EHT 100-2 A46SG	150.00	EA
173380	HAT & COAT HOOKS 130 MM	300.00	EA

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an “as and when required” at Hendrina Power Station for a Period of 5 Years

Unique Identifier:

Revision:

1

Page:

26 of 30

39462	CHAIN: TYPE: UTILITY; DIMENSIONS: 6.3 X 25 MM; MATERIAL: GS GR 300; LENGTH: 30 M; 39.7 LINKS PER METER	2000.00	M
179	SOLDER: MATERIAL: 40PB60TIN; DIMENSIONS: DIA 1.6 MM; FORM: WIRE RESIN CORE; REFERENCE NO: 60T2; SUPPLIED IN 500 GRAM REELS, REQUIRED A MATERIAL SAFETY DATA SHEET WITH EVERY DELIVERY	50	EA
197	DISK, CUTTING: OUTSIDE DIAMETER: 230 MM; ARBOR SIZE: 22.23 MM; THICKNESS: 3.2 MM; GRIT: 24; ABRASIVE MATERIAL: AL OXIDE; SPEED: 6640 RPM; BOND/BACKING: RESINOID; USAGE DESIGN: STL; REFERENCE NO: RA24T5BFW	1 000.00	EA
198	DISK, GRINDING: DIAMETER: 230 MM; ARBOR SIZE: 22.23 MM; SPEED: 6643 RPM; ABRASIVE MATERIAL: AL OXIDE; BOND/BACKING: RESINOID; USAGE DESIGN: STL; SHAPE: RD; REFERENCE NO: A24-R5-BFW TP27; TP27; REINFORCED; DEPRESSED CENTRE; SIZE 6MM THICK; 80/S MAX	1 000.00	EA
652	UNION, PIPE: SIZE: 25; CONNECTION: FPT; MATERIAL: STEEL GALV; SPECIFICATION: SABS 763	5 000.00	EA
653	UNION, PIPE: SIZE: 15 MM; CONNECTION: FPT; MATERIAL: STL GALV; SPECIFICATION: SABS 763	5 000.00	EA
654	PLUG, PIPE: SIZE: 15 MM; HEAD: SQ; CONNECTION: BSP; MATERIAL: STL GALV; SPECIFICATION: SABS 509-1955 TABLE 15	5 000.00	
655	PLUG, PIPE: SIZE: 20 MM; HEAD: SQ; CONNECTION: THD; MATERIAL: STL GALV; SPECIFICATION: SABS 509-1955 TABLE 15; BS 143:1952	3 000.00	EA
656	PLUG, PIPE: SIZE: 25 MM; HEAD: SQ; CONNECTION: THD; MATERIAL: STL GALV; SPECIFICATION: SABS 509-1955 TABLE 15; BS 143:1952	2 000.00	EA
57099	PLUG, PIPE: SIZE: 10 MM; HEAD: SQ; CONNECTION: NPT; MATERIAL: STEEL; GRADE: 4.6; SPECIFICATION: BS 1740; STEAM	2 500.00	EA
657	TEE, PIPE: SIZE: 15 MM; CONNECTION: FBSP; MATERIAL: STL GALV	1 500.00	EA
658	TEE, PIPE: SIZE: 20 MM; CONNECTION: FBSP; MATERIAL: STL GALV; SUPPLY FOUR PER SEALED BAG	1 500.00	EA

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an “as and when required” at Hendrina Power Station for a Period of 5 Years

Unique Identifier:

Revision:

1

Page:

27 of 30

659	COUPLING, PIPE: SIZE: 15 MM; CONNECTION: FBPT; MATERIAL: STL GALV	2 000.00	EA
660	COUPLING, PIPE: SIZE: 20 MM; CONNECTION: FPT; MATERIAL: MI GALV; SPECIFICATION: SABS 763; STYLE: SOCKET; 33 MM LONG	2 000.00	EA
661	COUPLING, PIPE: SIZE: 25 MM; CONNECTION: FPT; MATERIAL: MI GALV; SPECIFICATION: SABS 509- 1955 TABLE 13; STYLE: SOCKET	2 000.00	EA
662	ELBOW, PIPE: SIZE: 15 MM; CONNECTION: FNPT; MATERIAL: MI SABS 509 GALV HOT DIP; DEGREE: 90 DEG; RADIUS: SHORT	1 500.00	EA
666	NIPPLE, PIPE: TYPE: BARREL; INSIDE DIAMETER: 15 MM; LENGTH: 51 MM; CONNECTION: THD; MATERIAL: STL GALV; RATING: 4830 KPA; SPECIFICATION: SABS 76	2 500.00	EA
667	NIPPLE, PIPE: TYPE: BARREL; INSIDE DIAMETER: 20 MM; LENGTH: 54 MM; CONNECTION: THD; MATERIAL: STL GALV; RATING: 4830 KPA; SPECIFICATION: SABS 763; 62-1971 TABLE 9 FIG 3C	1 500.00	EA
668	NIPPLE, PIPE: TYPE: BARREL; INSIDE DIAMETER: 25 MM; LENGTH: 60 MM; CONNECTION: THD; MATERIAL: STL GALV; RATING: 4830 KPA; SPECIFICATION: SABS 763; 62-1971	3 000.00	EA
57347	NIPPLE, PIPE: TYPE: BARREL; INSIDE DIAMETER: 20 MM; LENGTH: 54 MM; CONNECTION: NPT; MATERIAL: STL; GRADE: 4.6; RATING: 4830 KPA; SPECIFICATION: SABS 62 TABLE 9 FIG 3C; FOR STEAM	3 000.00	EA
57179	REDUCER, PIPE: TYPE: CONCENTRIC BELL; NOMINAL SIZE: 25 X 15 MM; CONNECTION: FNPT; MATERIAL: STL; GRADE: WPB; SPECIFICATION: BS S1740; STEAM PSI, BSP THREAD	2 500.00	EA
57174	REDUCER, PIPE: TYPE: CONCENTRIC; NOMINAL SIZE: 25 X 20 MM; CONNECTION: FPT; MATERIAL: STL; SPECIFICATION: BS S1740-1965 AMENDMENT 1 TABLE 13	2 500.00	EA
101610	REDUCER, PIPE: TYPE: CONCENTRIC; NOMINAL SIZE: 25 X 20 MM; CONNECTION: FPT; MATERIAL: STL; SPECIFICATION: BS S1740-1965 AMENDMENT 1 TABLE 13	150.00	EA
101612	SHEET, GASKET: THICKNESS: 1 MM; LENGTH: 2 M; WIDTH: 1.5 M;	150.00	EA

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an “as and when required” at Hendrina Power Station for a Period of 5 Years

Unique Identifier:

Revision:

1

Page:

28 of 30

	MATERIAL: NON ASB IMPREGNATED; SUPPL P/N: BLACK; KLINGERITE STYLE 3XA, BS2815/1832A, COMPRESSED, BULK, RECTANGULAR, BLACK		
101613	SHEET, GASKET: THICKNESS: 1.5 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: NON ASB IMPREGNATED; SUPPL P/N: C-4430; COMPRESSED; MAX TEMP: 250 DEG C; PRESSURE RATING: 45 BAR; BULK; RECTANGULAR; TENDER RETURNABLES: GASKET SPECIFICATION SHEET; CLASSIFICATION ACC. TO BS 7531:2006: GRADE AX; ASME GASKET FACTORS: $M \leq 1.6$, $Y \leq 20$ MPA	150.00	EA
101615	SHEET, GASKET: THICKNESS: 3 MM; LENGTH: 2 M; WIDTH: 1.5 M; MATERIAL: NON ASB IMPREGNATED; SUPPL P/N: BROWN; KLINGERIT K80, BS2815/1832A, MAX TEMPERATURE 350 DEGREE C, PRESSURE 25 BAR, BULK, RECTANGULAR, BROWN	150.00	EA
108725	SADDLE, PIPE: NOMINAL SIZE: 20 MM; MATERIAL: STL GALV; TYPE: SPACER BAR; HEAVY DUTY; COMPLETE WITH SCREWS	1 000.00	EA
108533	SADDLE, PIPE: NOMINAL SIZE: 20 MM; MATERIAL: STL; WIDTH: 19 MM; LENGTH: 60 MM; HOLE: DIA 5 MM; PROCAST BLACK STEEL AND BLUED-BLACK FINISH	1 500.00	EA
158576	TAPE, EMBOSsing: COLOR: BROWN; NOMINAL WIDTH: 9 MM; NOMINAL LENGTH: 3 M; MATERIAL: VINYL; TO BSI SPECIFICATION NO 678-74/418	200.00	EA
158724	TAPE, EMBOSsing: COLOR: BLACK ON YELLOW; NOMINAL WIDTH: 12 MM; NOMINAL LENGTH: 8 M; SUPPL P/N: TZ631; USED ON BROTHER P-TOUCH 310 MACHINE	200.00	EA
158725	TAPE, EMBOSsing: COLOR: BLACK ON YELLOW; NOMINAL WIDTH: 9 MM; NOMINAL LENGTH: 8 M; SUPPL P/N: TZ621; USED ON BROTHER P-TOUCH 310 MACHINE	200.00	EA
159677	BRUSH, WIRE: TYPE: FOUNDRY; TRIM LENGTH: 20 MM; DIMENSIONS: WD 40 X LG 270 MM; MATERIAL: STL; HANDLE: WOOD; 6 ROW TYPE	350.00	EA
554127	BOOK: TYPE: WORK PERMIT; TITLE: RISK ASSESSMENT FORM; SIZE: A3; COVER TYPE: BROWN CARDBOARD; PAGE QUANTITY: 100	3 500.00	EA

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an “as and when required” at Hendrina Power Station for a Period of 5 Years

Unique Identifier:

Revision: 1

Page: 29 of 30

159327	BOOK, RECORD: TYPE: SHIFT SUPERVISOR LOG; SIZE: WD 190 X LG 300 MM; PAGE QUANTITY: 100; NUMBERED PAGES: YES; TRIPLICATE, COLOUR: WHITE NCR PAPER, 1ST PAGE NOT PERFORATED, 2ND AND 3RD PAGE TO BE PERFORATED, WITH A NEW ESKOM LOGO 2002	500.00	EA
159287	BOOK, RECORD: TYPE: WORKERS REGISTER; SIZE: A4; PAGE QUANTITY: 100; NUMBERED PAGES: YES; FOR HIGH VOLTAGE SYSTEMS AND PLANT SAFETY, DUPLICATE COPY: YELLOW, ORIGINAL COPY: WHITE, PERFORATED AND SELF CARBONATED, BLACK PRINTED, CONSECUTIVELY NUMBERED	3 500.00	EA
158844	BOOK, DUPLICATE: TYPE: PEN CARBON; COMMERCIAL SIZE: 254 X 203 MM; PAGE QUANTITY: 100; REFERENCE NO: JD55	1 000.00	EA
159497	FILE, STATIONERY: TYPE: POCKET; SIZE: A4; MATERIAL: PV; COLOR: CLEAR; 100 PER PACK	10 000.00	EA
17486	PAD, WRITING PAPER: TYPE: EXECUTIVE DESK W/COVERS; SIZE: A4; COLOR: WHITE; PAGE QUANTITY: 80; RULED: YES; REFERENCE NO: EK 74; SIZE 210 MM WD X 297 MM LG; GLUE ON TOP	5 000.00	EA
17417	FILE, STATIONERY: TYPE: ACCESSIBLE; SIZE: WD 270 X LG 315 X THK 40 MM; MATERIAL: PVC; COLOR: BLACK; TWO RING BINDER	2 000.00	EA
17408	FILE, STATIONERY: TYPE: ARCH LEVER; SIZE: WD 280 X LG 350 X HT 70 MM; MATERIAL: CARDBOARD; COLOR: GRAY; REFERENCE NO: W70; COMPLETE WITH DUST COVER, WITHOUT INDEX, METAL LEVER ARCH AND PLASTIC COMPRESSOR	3 000.00	EA
16829	PAINT, OIL: TYPE: ENAMEL; COLOR: GREEN; CONTAINER: CAN 5 L; FINISH: GLOSS; SPECIFIC USE: STOEP; REFERENCE NO: SP2; SHOULD	30 000	L
16831	PAINT, OIL: TYPE: ENAMEL; COLOR: BLACK; CONTAINER: CAN 5 L; FINISH: HIGH GLOSS; SPECIFIC USE: EXTERIOR/INTERIOR; SPECIFICATION: SABS 630-1972 TYPE 1; CONTROLLING COLOURS 770,	12 000	L
0159887	PAINT, OIL: TYPE: ENAMEL; COLOR: BLUE PASTEL; CONTAINER: CAN 500 ML; FINISH: HIGH GLOSS; SPECIFIC	12 000	L

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential

Scope of Work for Supply and delivery of Plant Consumables on an "as and when required" at Hendrina Power Station for a Period of 5 Years

Unique Identifier:

Revision:

1

Page:

30 of 30

	USE: EXTERIOR/INTERIOR; REFERENCE NO: P13; E70; CKS279:1971-SABS630:1972-TYPE1; REQUIRED THE NEW STANDARD FOR RELIABILITY POINT 1 TO 16 MATERIAL SAFETY DATA SHEET TO BE SUPPLIED WITH EVERY DELIVERY		
159880	PAINT, TRAFFIC: COLOR: YELLOW GOLDEN; CONTAINER: CAN 5 L; SPECIFIC USE: ROAD MARKING; REFERENCE NO: TP41; NON-REFLECTIVE FINISH, SPECIFICATION: SABS731-1966;		
0017206	DESICCANT: TYPE: ENVIRO GEL; CONTAINER: BAG PLASTIC 25 KG; MESH: 3-6 MM; GRADE: 3; ENVIROGEL IS A BEADED OR CRYSTAL FORM; FREE-FLOWING 3-6 MM AND NARROW-PORE ORANGE SILICA GEL FREE OF COBALT CHLORIDE; SUITABLE FOR USE IN TRANSFORMER BREATHER APPLICATIONS; SUPPLIED IN 25 KG BAGS; BEFORE PACKING MUST BE SIEVED FOR COMPLIANCE TO PARTICLE SITES; MATERIAL SAFETY DATA SHEET TO BE SUPPLIED WITH DELIVERY	300	KG

4. AUTHORISATION

This document has been seen and accepted by:

Name & Surname	Designation
[REDACTED]	[REDACTED]
[REDACTED]	[REDACTED]

5. REVISIONS

Date	Rev.	Compiler	Remarks
January 2026	1	[REDACTED]	Initial Document

6. DEVELOPMENT TEAM

The following people were involved in the development of this document:

[REDACTED]

7. ACKNOWLEDGEMENTS

N/A

CONTROLLED DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

Sensitivity: Confidential