

**Dark Grey/ Black with straight edge.**

#### **Veneer Worktop**

- 30mm Oak Veneer Monocoat matt top straight edge in colour stain as per furniture catalogue.

#### **Bamboo Worktop**

- 19mm Bamboo vertical carbonised board in colour stain as per furniture catalogue.

#### **Item 15.1**

##### **Links**

- Linking components must be attached using metal brackets or “plates”. No MDF links or plates are to be used.
- All desktops to be pre-drilled (non-handed) for connector plates and leg plates.
- All pre-drilled holes for the leg fixtures and metal connector plates are to be appropriately lined with inserts.
- No chipboard screws are to be used.

##### **, Cable Access**

- A minimum 64mm diameter small porthole covered by a plastic liner and plastic cover plate (to match the finish of the desk top/ frame colour) for cable access to top of desk is to be installed.
- The porthole should have the capacity to accommodate a “power pole” for overhead power supply systems.
- Cable reticulation management to the underside of the main desk components in each configuration must be available. This must be easily accessible by means of a metal black cable tray

##### **Desk Frame**

- **Minimum of 40x40mm (2mm thick wall) square profiled mild steel frame with a level correcting plate at the base of each leg of the frame.**
- The frame height with level correcting should allow ease of access for wheelchair users.
- Frame should attach firmly and neatly to the underside of the worktop with spacer between frame and top (shadow line detail). No chipboard screws are to be used.
- Frame to be powder coated matt finish (black).
- Frame to be predrilled (prior to powder coating) to allow for fixing of modesty panels and fixing of worktop.

##### **Storage Unit**

- **Solid Core Exec workstation unit to have freestanding low storage unit (see catalogue for design) 2000mm x 500mm x 400mm (h) with finger grip detail or aluminium “D” handle upon special request. Unit to be made of 10-18mm solid core board**
- Veneer Exec workstation unit to have freestanding low storage unit (see catalogue for design) 2000mm x 500mm x 400mm (h) with finger grip detail or aluminium “D” handle upon special request. Unit to be made of 12mm oak veneer Monocoat matt finish.
- Bamboo Exec workstation to have freestanding low storage unit (see catalogue for design) 2000mm x 500mm x 400mm (h) with finger grip detail or aluminium “D” handle. Unit to be made of 12mm Bamboo vertical board.

#### **Item 15.2**

##### **Links**

- Linking components must be attached using metal brackets or “plates”. No MDF links or plates are to be used.
- All desktops to be pre-drilled (non-handed) for connector plates and leg plates.
- All pre-drilled holes for the leg fixtures and metal connector plates are to be appropriately lined with inserts.
- No chipboard screws are to be used.

##### **, Cable Access**