



- ### Window Sills:
1. INTERNAL WINDOW SILL – 15mm thick FIBRE CEMENT WINDOW SILL BEADED IN 1-4 CEMENT SAND MORTAR. SAND & APPLY ALKALI RESISTANT SEALER AND TWO COATS MAX EMULSION PAINT.
2. EXTERNAL WINDOW SILL – APPROVED FACINGS ON EDGE, TO MATCH WALLS. JOINTS TO BE SEALED & RECESSED.
- ### Ceiling & Cornice:
1. CORNICE – 75mm GYPSUM CORNICE CORNICE WALLED TO WALL AND CEILING AT 450mm CENTRES MAX. AND TO RECEIVE PAINT FINISH TO MATCH CEILING.
2. CEILING – 4mm GYPSUM BOARD CEILING WELDED TO 38x38mm SPAC BATTEMS AT MAX. 400mm C/M WITH GALVANISED COATED WULFS. PROVIDE GALVANISED H-PROFILE JOINTING STRIPS TO BE PRE PAINTED. PREPARE & APPLY 1mm UNISOL UNDERCOAT & TWO COATS PLACASION FLUORIN SPOUR COAT MAX PAINT.
- ### Roof & Fascia:
1. ROOF SHEETING – 0.6mm "MULPOD" ROOF SHEETING IN CHROMOCLOR SHEET IN 760x260mm SPAC PURLINS AT MAX. 1200mm C/M ON PANT & APPROVED PRE-FABRICATED ROOF TRUSS SYSTEM.
2. ROOF DRAINING – STANDARD FACINGS MANUFACTURED RIDGES AND FLASHING IN FINISH TO MATCH CEILING.
3. FASGA & GUTTERS – 250x100mm THICK TRUSS PRESSURE BORE FACGA BOARD, SCREW FIX TO TRUSS ENDS & COUNTER BATTEN WITH COUNTERSUNK BRASS SCREWS. PREPARE & APPLY ONE UNISOL UNDERCOAT & TWO COATS PLACASION FLUORIN SUPER ACROFLOR PAINT.
- 100 x 100 x 0.6mm GUTTERS WITH 100mm DRA BANNER CORNSET WITH CHROMOCLOR FINISH.
2. TRUSS SYSTEM TYPENET PANT & APPROVED PRE-FABRICATED SYSTEM AT 1200mm C/M MAX. PURLING 50 x 75mm SPAC AT 1400mm C/M MAX. PURLING 14 x 38mm SPAC PANT TO BE CREOSOTED BEFORE FINISHING. CERTIFICATE & GUARANTEE FOR DESIGN & SECTION TO BE SUPPLIED BY TRUSS MANUFACTURER. ALL EXPRESSED TRUSS SECTIONS AS WELL AS SECTIONS IN CONTACT WITH METAL THINGS TO BE CREOSOTED BEFORE FINISHING.
3. TRUSS JOINTS THINGS TO BE SECURED TO WALLS AT WALLPAPER WITH 25mm GALV. STEEL WIRE THINGS, BUILT INTO WALLS IN W. BRICK COURSES.

ELECTRICAL LEGEND			
	CEILING LIGHT FITTING		15 AMP DOUBLE PLUG BUILT IN 340mm ABOVE FFL
	DECORATIVE WALL LIGHT FITTING		15 AMP DOUBLE PLUG POINT BUILT IN 1000mm ABOVE FFL
	DECORATIVE WATERPROOF EXTERNAL WALL MOUNTED LIGHT FITTING		TELEPHONE POINT
	DOUBLE TUBE FLUSH FITTING FLUORESCENT LIGHT COMPLETE WITH DIFFUSER		12 AMP ISOLATOR FOR A/C UNIT MOUNTED 150mm BELOW CEILING
			40 AMP ISOLATOR FOR A/C UNIT MOUNTED 500mm BELOW ROOF'S EAVE
	DISTRIBUTION BOARD & PRE PAID METERBOX		LIGHT SWITCH

[illegible]

consultant/departmental

RABANA ARCHITECTS ARCHITECTS, PLANNERS & PROJECT MANAGERS  REGISTERED OFFICE IN SOUTH AFRICA	167 1st Road 2654 Whitty Manor Office Estate Neerofwyn, Midrand P O Box 758379 Randburg, Sandton 2146 Tel (011) 318 -7097 Fax (011) 318-4872 francis@rabana.co.za
--	--

discipline

ARCHITECTURE

Project

IDT SCHOOLS PROGRAMME 2013/2014

drawing title

4 CLASSROOM BLOCK DRAINAGE, WATER RETICULATION ELECTRICAL & FIRE EQUIPMENTS

<i>ref.no</i>	<i>designed</i>
	GD
<i>scale</i>	<i>drawn</i>
	GD
<i>date</i>	<i>checked</i>
APRIL 2014	FR

Project Number

<i>drawing number</i>	<i>revision</i>
239-W004CR	