



agriculture, rural development,  
land & environmental affairs

MPUMALANGA PROVINCE  
REPUBLIC OF SOUTH AFRICA

Samora Machel Building, No. 7 Government Boulevard, Riverside Park, Extension 2, Mbombela, 1200,  
Mpumalanga Province, Private Bag X 11219, Mbombela, 1200  
Tel: +27 (013) 766 6067/8, Fax: +27 (013) 766 8295, Int. Tel: +27 (13) 766 6067/8, Int. Fax: +27 (13) 766 8295


Litiko Letekullima, Kutfutukiswa  
Kwetindzawo Tasemakhaya, Temhlaba  
Netesimondzawo

Departement van Landbou,  
Landelike Ontwikkeling,  
Grond en Ongewing Sake

umNyango weZelimo  
UkuThuthukiswa kweNdawo zemaKhaya,  
iNarha neeNdaba zeBhoduluko

Ref : 5/4/1/4/24-2022/23  
Enquiries : Mr ST Ngele  
Ext : 013 766 6167

**Ms G Mashiteng**  
Head: Provincial Treasury  
Provincial Treasury  
Private Bag X 11205  
**NELSPRUIT**  
1200



**SUBJECT : REQUEST FOR ADVERTISEMENT OF AN ADDENDUM  
FOR THE BID: ALA/536/22/MP, REFURBISHMENT OF A DAM FOR  
ALLANDALE CITRUS IN THE BUSHBUCKRIDGE MUNICIPALITY  
OF THE BOHLABELA DISTRICT, MPUMALANGA PROVINCE**

The department hereby request for an advertisement of an addendum on the July 2022 bid bulletin for the bid: ALA/536/22/MP, Refurbishment of a Dam for Allandale Citrus in the Bushbuckridge Municipality of the Bohlabela District, Mpumalanga Province as follows:

1. Invalidation of the compulsory briefing session from the Provincial Bid Bulletin.
2. Extension of the closing date of the Bid from 26 July 2022 to 12 August 2022.
3. Advertising the drawings of ALA/536/22/MP Refurbishment of a Dam for Allandale Citrus in the Bushbuckridge Municipality of the Bohlabela District, Mpumalanga Province.

Hope you will find the above in order.

Kind regards

MR C.M. CHUNDA

HEAD: AGRICULTURE, RURAL DEVELOPMENT, LAND AND  
ENVIRONMENTAL AFFAIRS

DATE 22/07/2022



"Should these drawings and Project Specifications be used or relied upon for any other purpose other than what they were intended for on this specific site, without CONRAD's prior knowledge and written consent, then the user shall indemnify the contractor (holder) against all liabilities, claims, damages, losses, fees and/or penalties (either in contract or delict) instituted by the user or any other party as a result of their re-use of or reliance on these drawings and project specifications."

| REV | DATE | DRAWN | CHECK | DESCRIPTION         |
|-----|------|-------|-------|---------------------|
| B   |      |       |       | ISSUED FOR APPROVAL |
| A   |      |       |       | ISSUED FOR APPROVAL |
|     |      |       |       |                     |
|     |      |       |       |                     |
|     |      |       |       |                     |
|     |      |       |       |                     |

## ENGINEERING SERVICES




**DRAWING:**  
**SECTION AA - DAM LINING**

FOR APPROVAL

|             |                        |            |
|-------------|------------------------|------------|
| DESIGNED    | SIGNATURE              | DATE       |
| RAWN        | SE BUTHLELEZI          | 30/05/2022 |
| CHECKED     | SE BUTHLELEZI          | 30/05/2022 |
| APPROVED    | T GOMO                 | 30/05/2022 |
| SCALE       | NOT TO SCALE           | 30/05/2022 |
| PROJECT No. | DISCIPLINE DRAWING No. | SHEET SIZE |
|             | SH 004 D               | A3 A       |

COPYRIGHT RESERVED



Selected fill compacted  
material to min 95%mod  
ashto

**Bidim or equivalent filter fabric**

Flexible corrugated 100mm  
corrugated perforated flexible pipe,  
3% slope

## CONSTRUCTION OF BALANCING DAM

- Refer to drawings for details of construction of the dam.
- Remove all the topsoil to a depth of 100mm in the dam wall external area.
- Excavate to remove major root systems of trees and shrubs in the dam wall area.
- Drain the dam, and scope soft material up 300mm of the dam basin
- Dam to be inspected by the site engineer before wall filling, compaction shaping.
- Construct dam wall to lines and slopes as indicated in drawing.
- Build dam wall in layers of 300mm, to be compacted to 95% to 105% Standard Proctor with soil moisture content Proctor optimum (-1% +0.5%)
- Spread 75mm minimum topsoil over completed dam wall and plant kikuyu grass as slope protection.
- Refer to drawings for details of construction of the sub-drainage channel.
- Excavate 500x500x500mm lining anchor trenching, install lining 1.5mm HDPE SABS approved watertight, fill and compact trenches
- Minimum of 1400mm lining shall be anchored
- Supply and install 1.5mm HDPE DAM LINER (SABS APPROVED), to be welded water joints and minimum overlaps of 500mm.

# LINING OF ALLANDALE DAM

## DISCLAIMER:

"Should these drawings and Project Specifications be used or relied upon for any other purpose other than what they were intended for on this specific site, without DOKO's prior knowledge and written consent, then the user shall indemnify the DOKO from and against all claims, damages, losses, fines and/or penalties (other in contract or delict) incurred by the user, and shall be held as result of their use or reliance on these drawings and project specifications."

|     |      |       |       |                     |  |
|-----|------|-------|-------|---------------------|--|
|     |      |       |       |                     |  |
|     |      |       |       |                     |  |
|     |      |       |       |                     |  |
| B   |      |       |       | ISSUED FOR APPROVAL |  |
| A   |      |       |       | ISSUED FOR APPROVAL |  |
| REV | DATE | DRAWN | CHECK | DESCRIPTION         |  |

PREPARED BY:  
ENGINEERING SERVICES

CLIENT:



MPUMALANGA DEPARTMENT  
OF AGRICULTURE, RURAL  
DEVELOPMENT, LAND AND  
ENVIRONMENTAL AFFAIRS

PROJECT:  
ALLANDALE CITRUS


DRAWING:  
DAM LINING - EMBARKMENTS SETOUT POINTS

## FOR APPROVAL

|          |              |            |
|----------|--------------|------------|
| SURVEYED | SIGNATURE    | DATE       |
| DRAWN    | SE BUTHELEZI | 28/05/2022 |
| CHECKED  | SE BUTHELEZI | 30/05/2022 |
| APPROVED | T GOMO       | 30/05/2022 |
| SCALE    | NOT TO SCALE |            |

|             |            |             |       |       |      |          |
|-------------|------------|-------------|-------|-------|------|----------|
| PROJECT No. | DISCIPLINE | DRAWING No. | STAGE | SHEET | SIZE | REVISION |
|             | SH         | 005         | D     | A3    | A    |          |

COPYRIGHT RESERVED



## LINING OF EARTH DAM CONSTRUCTION PROCEDURE

- Remove all the topsoil to a depth of 100mm in the dam wall external area.
- Excavate to remove major root systems of trees and shrubs in the dam wall area.
- Drain the dam, and scope soil material up 300mm of the dam basin
- Dam to be inspected by the site engineer before wall filling, compaction shaping.
- Construct dam wall to lines and slopes as indicated in drawing.
- Build dam wall in layers of 300mm, to be compacted to 95% to 105% Standard Proctor with soil moisture content Proctor optimum (-1% +0.5%)
- Spread 75mm minimum topsoil over completed dam wall and plant kikuyu grass as slope protection.
- Refer to drawings for details of construction of the sub-drainage channel.
- Excavate 500x500x500mm lining anchor trenching, install lining 1.5mm HDPE SABS approved watertight, fill and compact trenches
- Minimum of 1400mm lining shall be anchored
- Supply and install 1.5mm HDPE DAM LINER (SABS APPROVED), to be welded water joints and minimum overlaps of 500mm.

## LEGEND

|                     |  |
|---------------------|--|
| BUILDING            |  |
| SUBSURFACE DRAINAGE |  |
| EMBARKMENTS         |  |
| FENCE               |  |

**DISCLAIMER:**

\*Should these drawings and Project Specifications be used or relied upon for any other purpose other than what they were intended for on this specific site, without OARDEX prior knowledge and written consent, then the user shall indemnify the copyright holder against all liabilities, claims, damages, losses, fines and/or penalties (either in contract or delict) instituted by the user or any other party as result of their re-use of or reliance on these drawings and project specifications\*.

[illegible]

**PREPARED BY:**  
**ENGINEERING SERVICES**

**CLIENT:**




**MPUMALANGA DEPARTMENT  
OF AGRICULTURE, RURAL  
DEVELOPMENT, LAND AND  
ENVIRONMENTAL AFFAIRS**

**PROJECT:**  
**ALLANDALE CITRUS**

**DRAWING:**  
**DAM Lining**

|             |                          | SIGNATURE    | DATE       |
|-------------|--------------------------|--------------|------------|
| SURVEYED    | SE BUTHLEZI              |              | 28/05/2022 |
| DRAWN       | SE BUTHLEZI              |              | 30/05/2022 |
| CHECKED     | T GOMO                   |              | 30/05/2022 |
| APPROVED    | T GOMO                   |              | 30/05/2022 |
| SCALE       |                          | NOT TO SCALE |            |
| PROJECT No. | DISCIPLINE / DRAWING No. | STAGE        | SHEET SIZE |
|             | SH 006 D                 | A3           | A          |


COPYRIGHT RESERVED



# LINING OF ALLANDALE DAM

## DISCLAIMER:

"Should these drawings and Project Specifications be used or relied upon for any purpose other than what they were intended for on this specific site, without the written consent of the Engineer, the user shall indemnify the Engineer for all claims, damages, costs and expenses, including reasonable attorneys' fees, incurred by the Engineer as a result of their use of or reliance on these drawings and project specifications."



| LEGEND |                     |
|--------|---------------------|
|        | BUILDING            |
|        | SUBSURFACE DRAINAGE |
|        | EMBANKMENTS         |
|        | FENCE               |

## LINING OF EARTH DAM CONSTRUCTION PROCEDURE

- Remove all the topsoil to a depth of 100mm in the dam wall external area.
- Excavate to remove major root systems of trees and shrubs in the dam wall area.
- Drain the dam, and scope soft material up 300mm of the dam basin
- Dam to be inspected by the site engineer before wall filling, compaction shaping.
- Construct dam wall to lines and slopes as indicated in drawing.
- Build dam wall in layers of 300mm, to be compacted to 95% to 105% Standard Proctor with soil moisture content Proctor optimum (-1% +0.5%)
- Spread 75mm minimum topsoil over completed dam wall and plant kikuyu grass as slope protection.
- Refer to drawings for details of construction of the sub-drainage channel.
- Excavate 500x500x500mm lining anchor trenching, install lining 1.5mm HDPE SABS approved watertight, fill and compact trenches
- Minimum of 1400mm lining shall be anchored
- Supply and install 1.5mm HDPE DAM LINER (SABS APPROVED), to be welded water joints and minimum overlaps of 500mm.

## FOR APPROVAL

| SURVEYED     | SIGNATURE    | DATE        |
|--------------|--------------|-------------|
| SE BUTHELEZI |              | 28/05/2022  |
| DRAWN        | SE BUTHELEZI | 30/05/2022  |
| CHECKED      | T GOMO       | 30/05/2022  |
| APPROVED     | T GOMO       | 30/05/2022  |
| SCALE        | NOT TO SCALE |             |
| PROJECT No.  | DISCIPLINE   | DRAWING No. |
|              | SH           | 003         |
|              | D            | A3          |
|              |              | A           |

COPYRIGHT RESERVED