

**INXUBA YETHEMBA
UMASIPALA WASEKHAYA / PLAASLIKE MUNISIPALITEIT /
LOCAL MUNICIPALITY**

P O Box 24
CRADOCK
5880
TEL : +27(0)48 801 5000
FAX : +27(0)48 881 1421



P O Box 55
MIDDELBURG
5900
TEL : +27(0)49 842 1337
FAX : +27(0)49 842 1310

"A coherent developmental municipality putting people first and providing a better life for all its citizens"

REQUEST FOR QUOTATION

To:	ALL PROSPECTIVE SERVICE PROVIDERS
Project Name:	SUPPLY AND DELIVERY OF PA SYSTEM
Requestor:	INXUBA YETHEMBA MUNICIPALITY
QUOTATION NO.	IYM04/08/2024Q
NOTICE NO.	203/2024
Advert Date:	27 AUGUST 2024
Closing Date:	03 SEPTEMBER 2024

SPECIFICATION

SPECIFICATION AND PRICING SCHEDULE: Supply and delivery of PA system.

No.	Description of Goods or Service	Quantity	Unit Price	Total Price
1	<u>ALTO SPEAKERS FOR PUBLIC ADDRESS SYSTEM</u> 700 Watts peak (350 Watts continuous) Class D power. - The 90 H x 60 V horn delivers greater coverage - The full grille delivers style and provides protection for your investment. - is-inch (381 mm) LF driver, 2-inch (51 mm) voice coil. - L-inch (25.4 mm) titanium HF compression driver - Lightweight, portable design for main or wedge monitor operation - Standard speaker pole socket - Bi-amplified design with precision active crossover and EQ - Balanced XLR MicjLine input, Link Output and Volume control - Integrated analog limiter and overload protection Circuitry - Contour switch with low- and high-frequency +3dB boost	2		

2	<u>Extension for public address system</u> PRODUCT FEATURES • 2x 10A Standard SA Socket • Plugs into any standard SA 3 Pin Socket • 15m Cable TECHNICAL SPECS • Colour: Black • Amperage: 10A	2								
3	<u>ALTO SPEAKERS FOR PUBLIC ADDRESS SYSTEM</u> • 700 Watts peak (350 Watts continuous) Class D power. • The 90 H x 60 V horn delivers greater coverage • The full grille delivers style and provides protection for your investment. • is-inch (381 mm) LF driver, 2-inch (51 mm) voice coil. • L-inch (25.4 mm) titanium HF compression driver • Lightweight, portable design for main or wedge monitor operation • Standard speaker pole socket • Bi-amplified design with precision active crossover and EQ • Balanced XLR MicjLine input, Link Output and Volume control • Integrated analog limiter and overload protection Circuitry • Contour switch with low- and high-frequency +3dB boost	2								
4	<u>Aux cable for public address system</u> • Color -Coded rubber ring ensures a secure fit • 3.5mm / line in to AUX premium audio cable • Premium copper connectors for optimal signal transfer and corrosion resistance. • Connects iPhones I iPods and other 3.5mm jack smart devices to stereo receiver, amplifier or speaker system.	2								
5	<u>Extension for public address system</u> PRODUCT FEATURES • 2x 10A Standard SA Socket • Plugs into any standard SA 3 Pin Socket • 15m Cable TECHNICAL SPECS • Colour: Black • Amperage: 10A	2								
6	<u>Microphone stand for public address system</u> <table><tr><td>Minimum Height</td><td>950mm</td></tr><tr><td>Maximum Height</td><td>2150mm</td></tr><tr><td>Boom Arm Lenght</td><td>558mm</td></tr></table>	Minimum Height	950mm	Maximum Height	2150mm	Boom Arm Lenght	558mm	2		
Minimum Height	950mm									
Maximum Height	2150mm									
Boom Arm Lenght	558mm									

	Material	Steel			
	Weight	2.0kg			
7	<u>Multi-Plug for public address system</u> • 6X 16A • 5X SLIM • IXSCHUKO • CABLE LENGTH: 0.5M • SURGE PROTECTION		2		
8	<u>Speaker Stand for public address system</u> • Durable aluminum construction • Tripod base for optimum stability • Ergonomic knobs for easy adjustment and breakdown • Steel safety pin for added stability. • Compatible with all TRUESONIC loudspeakers		2		
9	<u>TFI Mixer for public address system</u> Fader Configuration: 16 + 1(Master) Input Channels: 40 (32 mono + 2 stereo + 2 return) Aux Buses: 20 (8 mono + 6 stereo) Stereo Buses: 1 Sub Buses: 1 Inputs: 16 mic/line (XLRffRS combo) + 2 stereo line (RCA pin) Output: 16(XLR) Expansion slots: 1 On-board processors DSP: 8 Effects + 10 GEQ USB: 34x34 USB Audio Interface, 2-track recording via USB Storage		2		
10	<u>XLR Cables for public address system</u> • Pack of 10 x 10m Male XLR to Female XLR leads • Balanced microphone cable • Ideal for use with microphones. active speakers. studio and stage applications and DMX lighting chains • Lengths: 10m • Lengths: 10m		2		
	Vat @ 15%				
	TOTAL				

Evaluation criteria

The quotes will be evaluated using the 80/20 preferential point system.

- 20 points will be allocated as follows:

Locality: 50%

Locality	Number of Points 80/20
Enterprise within Inxuba Yethemba Local Municipality	10
Enterprise within Chris Hani District Municipality	8
Enterprise within Eastern Cape	5
Enterprise within South Africa	2
Enterprise from outside of South Africa	0

- Municipal Account must be submitted for points to be allocated.

BBBEE: 50%

- 10 points will be allocated to 100% Black owned firms
- BBBEE certificate/ sworn affidavits must be submitted for points to be allocated.

Payment for Services

Payment will be issued with 30 days after goods have delivered.

All relevant information must accompany all quotations submitted. No late or incomplete quotation will be accepted for consideration.

The municipality reserves the right not to accept the lowest or any quotation and no reason for the acceptance or rejection of a quotation will be furnished.

General

- The Inxuba Yethemba Municipality Supply Chain Management policy shall apply
- All prices will be evaluated inclusive of VAT, except where a non-VAT vendor has submitted a responsive bid. In this case, all bids prices will be evaluated exclusive of VAT.
- Certified copies of identity documents of directors.
- Quotations must be signed or annexed with a company stamp.
- Bidders to supply municipal utility bill or lease agreement reflecting status of accounts.
- Bidders to include the following municipal declarations with the quotations: MBD 4 and MBD 9.
- Quotations to be valid for 60 days from the closing date.
- IYM reserves the right to award the quotation in full or part thereof.
- CSD report must be submitted
- SARS Pin or Tax compliance certificate

Note: Failure to attach the B-BBEE Status Level Certificate will result in the bidder losing the preference points.

Formal written price quotations should be submitted in a sealed envelope, clearly marked "QUOTATION NO: IYM04/08/2024Q (**SUPPLY AND DELIVERY OF PA SYSTEM**)" which must be placed in the bid box, located at the Registry Office in the IYM offices No. 1 JA Calata Street, Cradock, 5880, **before 12 pm on the closing date 03 September 2024 . No email submissions will be allowed.**

For inquiries regarding the Request for Quotation, please contact the Project Manager, Mr. S Mahlasela at 0488015042 or email smahlasela@iym.gov.za

All suppliers are required to register on the Central Supplier Database (CSD), as well as submit a Declaration of Interest form (available from the Supply Chain Office). Information on the CSD is available on the CSD website: www.csd.gov.za.

Should you have SCM-related inquiries please contact the **Supply Chain Management Unit**;

- Tandelwetu Petelo (048) 801 5139 or email tpetelo@iym.gov.za

CLOSING DATE: 03 September 2024 AT 12H00