

TECHNICAL DATA	
FRAME:	Aluminium "extruded" or equal 60° clear anodized (only V215 x 1250mm fit profile, with standard extruded not easy to match).
COLOR:	Background: V2155 (background, white with substructure, aluminium) 521210 or equivalent.
FONT:	"Bodoni" (font, "Bodoni") "number" (font) of "Bodoni".
DETAILS:	Reference: Type A, 20, 25, 30, 40, 50, 60, 70, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180, 190, 200, 210, 220, 230, 240, 250, 260, 270, 280, 290, 300, 310, 320, 330, 340, 350, 360, 370, 380, 390, 400, 410, 420, 430, 440, 450, 460, 470, 480, 490, 500, 510, 520, 530, 540, 550, 560, 570, 580, 590, 600, 610, 620, 630, 640, 650, 660, 670, 680, 690, 700, 710, 720, 730, 740, 750, 760, 770, 780, 790, 800, 810, 820, 830, 840, 850, 860, 870, 880, 890, 900, 910, 920, 930, 940, 950, 960, 970, 980, 990, 1000, 1010, 1020, 1030, 1040, 1050, 1060, 1070, 1080, 1090, 1100, 1110, 1120, 1130, 1140, 1150, 1160, 1170, 1180, 1190, 1200, 1210, 1220, 1230, 1240, 1250, 1260, 1270, 1280, 1290, 1300, 1310, 1320, 1330, 1340, 1350, 1360, 1370, 1380, 1390, 1400, 1410, 1420, 1430, 1440, 1450, 1460, 1470, 1480, 1490, 1500, 1510, 1520, 1530, 1540, 1550, 1560, 1570, 1580, 1590, 1600, 1610, 1620, 1630, 1640, 1650, 1660, 1670, 1680, 1690, 1700, 1710, 1720, 1730, 1740, 1750, 1760, 1770, 1780, 1790, 1800, 1810, 1820, 1830, 1840, 1850, 1860, 1870, 1880, 1890, 1900, 1910, 1920, 1930, 1940, 1950, 1960, 1970, 1980, 1990, 2000, 2010, 2020, 2030, 2040, 2050, 2060, 2070, 2080, 2090, 2100, 2110, 2120, 2130, 2140, 2150, 2160, 2170, 2180, 2190, 2200, 2210, 2220, 2230, 2240, 2250, 2260, 2270, 2280, 2290, 2300, 2310, 2320, 2330, 2340, 2350, 2360, 2370, 2380, 2390, 2400, 2410, 2420, 2430, 2440, 2450, 2460, 2470, 2480, 2490, 2500, 2510, 2520, 2530, 2540, 2550, 2560, 2570, 2580, 2590, 2600, 2610, 2620, 2630, 2640, 2650, 2660, 2670, 2680, 2690, 2700, 2710, 2720, 2730, 2740, 2750, 2760, 2770, 2780, 2790, 2800, 2810, 2820, 2830, 2840, 2850, 2860, 2870, 2880, 2890, 2900, 2910, 2920, 2930, 2940, 2950, 2960, 2970, 2980, 2990, 3000, 3010, 3020, 3030, 3040, 3050, 3060, 3070, 3080, 3090, 3100, 3110, 3120, 3130, 3140, 3150, 3160, 3170, 3180, 3190, 3200, 3210, 3220, 3230, 3240, 3250, 3260, 3270, 3280, 3290, 3300, 3310, 3320, 3330, 3340, 3350, 3360, 3370, 3380, 3390, 3400, 3410, 3420, 3430, 3440, 3450, 3460, 3470, 3480, 3490, 3500, 3510, 3520, 3530, 3540, 3550, 3560, 3570, 3580, 3590, 3600, 3610, 3620, 3630, 3640, 3650, 3660, 3670, 3680, 3690, 3700, 3710, 3720, 3730, 3740, 3750, 3760, 3770, 3780, 3790, 3800, 3810, 3820, 3830, 3840, 3850, 3860, 3870, 3880, 3890, 3900, 3910, 3920, 3930, 3940, 3950, 3960, 3970, 3980, 3990, 4000, 4010, 4020, 4030, 4040, 4050, 4060, 4070, 4080, 4090, 4100, 4110, 4120, 4130, 4140, 4150, 4160, 4170, 4180, 4190, 4200, 4210, 4220, 4230, 4240, 4250, 4260, 4270, 4280, 4290, 4300, 4310, 4320, 4330, 4340, 4350, 4360, 4370, 4380, 4390, 4400, 4410, 4420, 4430, 4440, 4450, 4460, 4470, 4480, 4490, 4500, 4510, 4520, 4530, 4540, 4550, 4560, 4570, 4580, 4590, 4600, 4610, 4620, 4630, 4640, 4650, 4660, 4670, 4680, 4690, 4700, 4710, 4720, 4730, 4740, 4750, 4760, 4770, 4780, 4790, 4800, 4810, 4820, 4830, 4840, 4850, 4860, 4870, 4880, 4890, 4900, 4910, 4920, 4930, 4940, 4950, 4960, 4970, 4980, 4990, 5000, 5010, 5020, 5030, 5040, 5050, 5060, 5070, 5080, 5090, 5100, 5110, 5120, 5130, 5140, 5150, 5160, 5170, 5180, 5190, 5200, 5210, 5220, 5230, 5240, 5250, 5260, 5270, 5280, 5290, 5300, 5310, 5320, 5330, 5340, 5350, 5360, 5370, 5380, 5390, 5400, 5410, 5420, 5430, 5440, 5450, 5460, 5470, 5480, 5490, 5500, 5510, 5520, 5530, 5540, 5550, 5560, 5570, 5580, 5590, 5600, 5610, 5620, 5630, 5640, 5650, 5660, 5670, 5680, 5690, 5700, 5710, 5720, 5730, 5740, 5750, 5760, 5770, 5780, 5790, 5800, 5810, 5820, 5830, 5840, 5850, 5860, 5870, 5880, 5890, 5900, 5910, 5920, 5930, 5940, 5950, 5960, 5970, 5980, 5990, 6000, 6010, 6020, 6030, 6040, 6050, 6060, 6070, 6080, 6090, 6100, 6110, 6120, 6130, 6140, 6150, 6160, 6170, 6180, 6190, 6200, 6210, 6220, 6230, 6240, 6250, 6260, 6270, 6280, 6290, 6300, 6310, 6320, 6330, 6340, 6350, 6360, 6370, 6380, 6390, 6400,

Signing Forms & Standards

SIGNAGE

Interior Identification
Code: 09 - "Pause Area" - Flat

Location: Wall mounted at entrance to Pause Area.
 Description: SARS curved face sign located as per signage plan.

TECHNICAL DATA

FRAME: Adjustable stainless steel or anodized aluminium VDS6 + 20mm x 25mm x 1.5mm (20mm x 25mm x 1.5mm) for stainless steel frame

COLOURS: POLYESTER: 3000 (white), 3001 (blue), 3002 (red), 3003 (yellow), 3004 (green), 3005 (black), 3006 (grey), 3007 (orange), 3008 (purple), 3009 (brown), 3010 (pink), 3011 (light blue), 3012 (light green), 3013 (light yellow), 3014 (light red), 3015 (light blue), 3016 (light green), 3017 (light yellow), 3018 (light red), 3019 (light blue), 3020 (light green), 3021 (light yellow), 3022 (light red), 3023 (light blue), 3024 (light green), 3025 (light yellow), 3026 (light red), 3027 (light blue), 3028 (light green), 3029 (light yellow), 3030 (light red), 3031 (light blue), 3032 (light green), 3033 (light yellow), 3034 (light red), 3035 (light blue), 3036 (light green), 3037 (light yellow), 3038 (light red), 3039 (light blue), 3040 (light green), 3041 (light yellow), 3042 (light red), 3043 (light blue), 3044 (light green), 3045 (light yellow), 3046 (light red), 3047 (light blue), 3048 (light green), 3049 (light yellow), 3050 (light red), 3051 (light blue), 3052 (light green), 3053 (light yellow), 3054 (light red), 3055 (light blue), 3056 (light green), 3057 (light yellow), 3058 (light red), 3059 (light blue), 3060 (light green), 3061 (light yellow), 3062 (light red), 3063 (light blue), 3064 (light green), 3065 (light yellow), 3066 (light red), 3067 (light blue), 3068 (light green), 3069 (light yellow), 3070 (light red), 3071 (light blue), 3072 (light green), 3073 (light yellow), 3074 (light red), 3075 (light blue), 3076 (light green), 3077 (light yellow), 3078 (light red), 3079 (light blue), 3080 (light green), 3081 (light yellow), 3082 (light red), 3083 (light blue), 3084 (light green), 3085 (light yellow), 3086 (light red), 3087 (light blue), 3088 (light green), 3089 (light yellow), 3090 (light red), 3091 (light blue), 3092 (light green), 3093 (light yellow), 3094 (light red), 3095 (light blue), 3096 (light green), 3097 (light yellow), 3098 (light red), 3099 (light blue), 3100 (light green), 3101 (light yellow), 3102 (light red), 3103 (light blue), 3104 (light green), 3105 (light yellow), 3106 (light red), 3107 (light blue), 3108 (light green), 3109 (light yellow), 3110 (light red), 3111 (light blue), 3112 (light green), 3113 (light yellow), 3114 (light red), 3115 (light blue), 3116 (light green), 3117 (light yellow), 3118 (light red), 3119 (light blue), 3120 (light green), 3121 (light yellow), 3122 (light red), 3123 (light blue), 3124 (light green), 3125 (light yellow), 3126 (light red), 3127 (light blue), 3128 (light green), 3129 (light yellow), 3130 (light red), 3131 (light blue), 3132 (light green), 3133 (light yellow), 3134 (light red), 3135 (light blue), 3136 (light green), 3137 (light yellow), 3138 (light red), 3139 (light blue), 3140 (light green), 3141 (light yellow), 3142 (light red), 3143 (light blue), 3144 (light green), 3145 (light yellow), 3146 (light red), 3147 (light blue), 3148 (light green), 3149 (light yellow), 3150 (light red), 3151 (light blue), 3152 (light green), 3153 (light yellow), 3154 (light red), 3155 (light blue), 3156 (light green), 3157 (light yellow), 3158 (light red), 3159 (light blue), 3160 (light green), 3161 (light yellow), 3162 (light red), 3163 (light blue), 3164 (light green), 3165 (light yellow), 3166 (light red), 3167 (light blue), 3168 (light green), 3169 (light yellow), 3170 (light red), 3171 (light blue), 3172 (light green), 3173 (light yellow), 3174 (light red), 3175 (light blue), 3176 (light green), 3177 (light yellow), 3178 (light red), 3179 (light blue), 3180 (light green), 3181 (light yellow), 3182 (light red), 3183 (light blue), 3184 (light green), 3185 (light yellow), 3186 (light red), 3187 (light blue), 3188 (light green), 3189 (light yellow), 3190 (light red), 3191 (light blue), 3192 (light green), 3193 (light yellow), 3194 (light red), 3195 (light blue), 3196 (light green), 3197 (light yellow), 3198 (light red), 3199 (light blue), 3200 (light green), 3201 (light yellow), 3202 (light red), 3203 (light blue), 3204 (light green), 3205 (light yellow), 3206 (light red), 3207 (light blue), 3208 (light green), 3209 (light yellow), 3210 (light red), 3211 (light blue), 3212 (light green), 3213 (light yellow), 3214 (light red), 3215 (light blue), 3216 (light green), 3217 (light yellow), 3218 (light red), 3219 (light blue), 3220 (light green), 3221 (light yellow), 3222 (light red), 3223 (light blue), 3224 (light green), 3225 (light yellow), 3226 (light red), 3227 (light blue), 3228 (light green), 3229 (light yellow), 3230 (light red), 3231 (light blue), 3232 (light green), 3233 (light yellow), 3234 (light red), 3235 (light blue), 3236 (light green), 3237 (light yellow), 3238 (light red), 3239 (light blue), 3240 (light green), 3241 (light yellow), 3242 (light red), 3243 (light blue), 3244 (light green), 3245 (light yellow), 3246 (light red), 3247 (light blue), 3248 (light green), 3249 (light yellow), 3250 (light red), 3251 (light blue), 3252 (light green), 3253 (light yellow), 3254 (light red), 3255 (light blue), 3256 (light green), 3257 (light yellow), 3258 (light red), 3259 (light blue), 3260 (light green), 3261 (light yellow), 3262 (light red), 3263 (light blue), 3264 (light green), 3265 (light yellow), 3266 (light red), 3267 (light blue), 3268 (light green), 3269 (light yellow), 3270 (light red), 3271 (light blue), 3272 (light green), 3273 (light yellow), 3274 (light red), 3275 (light blue), 3276 (light green), 3277 (light yellow), 3278 (light red), 3279 (light blue), 3280 (light green), 3281 (light yellow), 3282 (light red), 3283 (light blue), 3284 (light green), 3285 (light yellow), 3286 (light red), 3287 (light blue), 3288 (light green), 3289 (light yellow), 3290 (light red), 3291 (light blue), 3292 (light green), 3293 (light yellow), 3294 (light red), 3295 (light blue), 3296 (light green), 3297 (light yellow), 3298 (light red), 3299 (light blue), 3300 (light green), 3301 (light yellow), 3302 (light red), 3303 (light blue), 3304 (light green), 3305 (light yellow), 3306 (light red), 3307 (light blue), 3308 (light green), 3309 (light yellow), 3310 (light red), 3311 (light blue), 3312 (light green), 3313 (light yellow), 3314 (light red), 3315 (light blue), 3316 (light green), 3317 (light yellow), 3318 (light red), 3319 (light blue), 3320 (light green), 3321 (light yellow), 3322 (light red), 3323 (light blue), 3324 (light green), 3325 (light yellow), 3326 (light red), 3327 (light blue), 3328 (light green), 3329 (light yellow), 3330 (light red), 3331 (light blue), 3332 (light green), 3333 (light yellow), 3334 (light red), 3335 (light blue), 3336 (light green), 3337 (light yellow), 3338 (light red), 3339 (light blue), 3340 (light green), 3341 (light yellow), 3342 (light red), 3343 (light blue), 3344 (light green), 3345 (light yellow), 3346 (light red), 3347 (light blue), 3348 (light green), 3349 (light yellow), 3350 (light red), 3351 (light blue), 3352 (light green), 3353 (light yellow), 3354 (light red), 3355 (light blue), 3356 (light green), 3357 (light yellow), 3358 (light red), 3359 (light blue), 3360 (light green), 3361 (light yellow), 3362 (light red), 3363 (light blue), 3364 (light green), 3365 (light yellow), 3366 (light red), 3367 (light blue), 3368 (light green), 3369 (light yellow), 3370 (light red), 3371 (light blue), 3372 (light green), 3373 (light yellow), 3374 (light red), 3375 (light blue), 3376 (light green), 3377 (light yellow), 3378 (light red), 3379 (light blue), 3380 (light green), 3381 (light yellow), 3382 (light red), 3383 (light blue), 3384 (light green), 3385 (light yellow), 3386 (light red), 3387 (light blue), 3388 (light green), 3389 (light yellow), 3390 (light red), 3391 (light blue), 3392 (light green), 3393 (light yellow), 3394 (light red), 3395 (light blue), 3396 (light green), 3397 (light yellow), 3398 (light red), 3399 (light blue), 3400 (light green), 3401 (light yellow), 3402 (light red), 3403 (light blue), 3404 (light green), 3405 (light yellow), 3406 (light red), 3407 (light blue), 3408 (light green), 3409 (light yellow), 3410 (light red), 3411 (light blue), 3412 (light green), 3413 (light yellow), 3414 (light red), 3415 (light blue), 3416

Building Norms & Standards



SIGNAGE


Interior Identification

Code: 21 - "Male" - Projecting

Last Revised: 19-10-21

Location: Wall mounted at entrance to Male bathrooms.
Standard SARS curved Fence double sided Male Toilet sign located as per Floor plan.





TECHNICAL DATA

FRAME: Vinyl 151 x 203mm (31 light weight non generation profile, with anodized aluminium end caps to finish)

COLORS: Black background. Perimeter 200S, straps (2x4S).

FOUNT: Removable - Type A. Do not print without Type A disc in hand.

GRAPHIC: Type C - 150mm x 40mm to 625 mm.

ES/SC/CH/CH:

Building Norms & Standards

SARS
South African Revenue Service

SIGNAGE

External Signage Code:

Location: Reception (typical) or as per placement plan allocation.
Description: Standard SARS cover face disclaimer pictogram sign.

Top view

V460

275mm

460

30mm

100mm

Section

100mm

DISCLAIMER

NB: Hierdie kennisgewing is slegs bedoel om kennis te maak. Dit is nie bedoel om te wettig of te onwettig te maak, of om te bevestig of te ontkenn dat enige persoon of entiteit 'n oortreder van enige wet of regulasie is. Hierdie kennisgewing is slegs bedoel om kennis te maak dat die SARS bediening 'n oortreder van enige wet of regulasie is.

100

Building Norms & Standards
SIGNAGE

Interior Identification
Code: 57 - "N.S.O.C. /Access Cards"

Location: Reception (typical) or as per floor plan location.
Description: Standard SARS curved face N.S.O.C. emergency telephone numbers & Access Cards sign.

Top view
Section

TECHNICAL DATA
FRAME: New generation V400 x 275mm high (flat to wall), with white aluminium and caps to match.
COLOURS: Black and Pantone 2955C (background on white substrate).
FONT: Humanist 521.
GRAPHIC: See Resources - Type A & B Mount.
ERGONOMICS: Type A - 1500mm AFFL to US frame - wall mounted.

Interior Identification
Code: 58 - "Intercom Signage"

Location: At Intercoms as required by ACAS advisory.
Description: Standard Intercom Signage.

V150
Section

TECHNICAL DATA
FRAME: V150 clear brushed snap V100 x 100mm (70 profile), with brushed aluminium and caps to match.
COLOURS: Pantone 2955C (text and icons) on white substrate.
FONT: Humanist 521 or Verdana Bold.
GRAPHIC: See Resources - Type A.
ERGONOMICS: Mounted at elbow proximity to telephone handset.

Interior Identification
Code: 115 - "Security Guard Notice"

Location: As per floor plan location.
Description: Standard SARS curved face "Security Guard Notice" on new generation V400 sign.

Top view
Section

TECHNICAL DATA
FRAME: V400 clear brushed snap V400 x 275mm high (flat to wall), with white aluminium and caps to match.
COLOURS: Black and Pantone 2955C (text & images on white substrate).
FONT: Humanist 521 or Verdana Bold.
GRAPHIC: See Resources - Type A (do not print without Type A due to hand).
ERGONOMICS: Type A - 1500mm AFFL to US frame - wall mounted.

Interior Identification
Code: 49 - "Information Posters"

Location: Wall mounted in Pause Areas of the building. Non-client areas.
Description: Curved surround aluminium A2 and A1 poster frames with A1 pinup board.
Usage: Internal SARS campaigns & information posters. Pinup for local office information sharing.

A2 Frames (maximum of 3) → A1 Frame A1 Pinup

TECHNICAL DATA
FRAME: Aluminium Poster Frames to suit A1 and A2 prints with top/bottom mechanism to clamp posters. Frame to have poster backing.
COLOURS: Black and Pantone 2955C (text & images on white substrate).
FONT: Humanist 521 or Verdana Bold.
GRAPHIC: See Resources - Type A (do not print without Type A due to hand).
ERGONOMICS: Type A - 1500mm AFFL to underside of frame. Type B - 1200mm AFFL to underside of frame.

Building Norms & Standards
SIGNAGE

Internal Signage
Type: 96 - "Pull" Door Plate - Type 1.

Location: As per floor plan.
Description: 75mm wide x 120mm high brushed 2mm aluminium plate with vertical text laser etched and paint filled.

75mm 120mm 2mm Radius
Section

TECHNICAL DATA
FACE: 75mm wide x 120mm high x 2mm thick brushed aluminium plate. Brush stroke vertical. 5mm radius rounded corners with A1 edge polished smooth.
MOUNTING: Fixed with Normou® V2700 Economical Closed Cell Polyurethane Foam Substrate with a high performance Acrylic Adhesive. Filled "Back to Back".
TEXT: Centre aligned on horizontal & vertical midpoint. Verdana Bold on 120% to 180% horizontal text stretch. 2mm gap to top and bottom. Text to be laser etched into aluminium and paint filled with black enamel paint.
HEIGHTS: 1500mm to US sign from FFL. If door handle is within 50mm of sign, raise sign to clear door handle by 100mm. If height to US exceeds 1250mm AFFL, report to SARS Project Manager BEFORE Raising.

Building Norms & Standards
SIGNAGE

Internal Signage
Type: 97 - "Pull" Door Plate - Type 1.

Location: As per floor plan.
Description: 120mm wide x 75mm high brushed 2mm aluminium plate with horizontal text laser etched and paint filled.

120mm 75mm 2mm Radius
Section

TECHNICAL DATA
FACE: 120mm wide x 75mm high x 2mm thick brushed aluminium plate. Brush stroke horizontal. 5mm radius rounded corners with A1 edge polished smooth.
MOUNTING: Fixed with Normou® V2700 Economical Closed Cell Polyurethane Foam Substrate with a high performance Acrylic Adhesive. Filled "Back to Back".
TEXT: Centre aligned on horizontal & vertical midpoint. Verdana Bold. 20mm gap to left and right. Text to be laser etched into aluminium and paint filled with black enamel paint.
HEIGHTS: 1500mm to US sign from FFL. If door handle is within 50mm of sign, raise sign to clear door handle by 100mm. If height to US exceeds 1250mm AFFL, report to SARS Project Manager BEFORE Raising.

Building Norms & Standards
SIGNAGE

Internal Signage
Type: 98 - "Push" Door Plate - Type 1.

Location: As per floor plan.
Description: 75mm wide x 120mm high brushed 2mm aluminium plate with vertical text laser etched and paint filled.

75mm 120mm 2mm Radius
Section

TECHNICAL DATA
FACE: 75mm wide x 120mm high x 2mm thick brushed aluminium plate. Brush stroke vertical. 5mm radius rounded corners with A1 edge polished smooth.
MOUNTING: Fixed with Normou® V2700 Economical Closed Cell Polyurethane Foam Substrate with a high performance Acrylic Adhesive. Filled "Back to Back".
TEXT: Centre aligned on horizontal & vertical midpoint. Verdana Bold on 120% to 180% horizontal text stretch. 2mm gap to top and bottom. Text to be laser etched into aluminium and paint filled with black enamel paint.
HEIGHTS: 1500mm to US sign from FFL. If door handle is within 50mm of sign, raise sign to clear door handle by 100mm. If height to US exceeds 1250mm AFFL, report to SARS Project Manager BEFORE Raising.

Building Norms & Standards
SIGNAGE

Internal Signage
Type: 99 - "Push" Door Plate - Type 1.

Location: As per floor plan.
Description: 120mm wide x 75mm high brushed 2mm aluminium plate with horizontal text laser etched and paint filled.

120mm 75mm 2mm Radius
Section

TECHNICAL DATA
FACE: 120mm wide x 75mm high x 2mm thick brushed aluminium plate. Brush stroke horizontal. 5mm radius rounded corners with A1 edge polished smooth.
MOUNTING: Fixed with Normou® V2700 Economical Closed Cell Polyurethane Foam Substrate with a high performance Acrylic Adhesive. Filled "Back to Back".
TEXT: Centre aligned on horizontal & vertical midpoint. Verdana Bold. 20mm gap to left and right. Text to be laser etched into aluminium and paint filled with black enamel paint.
HEIGHTS: 1500mm to US sign from FFL. If door handle is within 50mm of sign, raise sign to clear door handle by 100mm. If height to US exceeds 1250mm AFFL, report to SARS Project Manager BEFORE Raising.

Building Norms & Standards
SIGNAGE

External Signage
Code: EXT-Type-61 "Reserved Parking"

Location: Centre and front of Parking bay (when possible).
Description: A4 (210w x 297h)mm Chromadeck sign with Series 7 Vinyl print on rectangular aluminium pole embedded into surface with concrete footing.
Usage: To demarcate SARS only parking bays (Reserved Parking).

RESERVED PARKING
A4 Chromadeck

TECHNICAL DATA
SIGN: A4 Chromadeck sign with rectangular aluminium pole embedded into 150 mm in surface (round with concrete/curb) to meet footing without fastening system as done by regular demarcation. Signage is to be mounted on a concrete footing.
GROUND: Sign to be placed on the full sun vinyl.
COLOURS: Pantone 2955C / white.
NOTES: MUST be supplied by vendor for SARS approval prior to manufacture on part of quotation cost requirement.

Building Norms & Standards
SIGNAGE

COLOUR SPECIFICATIONS

Pantone 2955C Brushed Aluminium (Internal Signs)

Opel PX 050 5mm perspex face panel "aluminium sprayed" 2K fine matt silver 730-0119 ultra clear coat for "Anodised" look (External illuminated signs).

FONT SPECIFICATIONS (Internal)

Font: HUMANIST 521 BT Bold or VERDANA Bold.

Building Norms & Standards
SIGNAGE

Fixing of Signs (Projecting and Flat) to Drywalls

PRODUCTS:

STEP 1: Mark and install drywall fixing screws (RAMPL/Fischer in 12.5mm drywall).

STEP 2: After installing drywall fixing screws, mount base to drywall making sure screws go into nylon fixings.

Place sign over mounting base.

Secure on cover caps to secure sign in place.

Building Norms & Standards
SIGNAGE

SIGN POSITION ERGONOMICS

When considering signage text size and placement on signs, as well as where signs should be located within a space and mounted to equipment, it is important to consider the following criteria:

1. Viewing Distance: The distance from which the sign will be viewed.
2. Viewing Area: The effect of the viewing distance on readability.
3. Ergonomics: Diagrams describing:
a. Sight Line: An imaginary line approximately 15 degrees below the average eye level of the viewer.
b. Optimal viewing area for the sign.
c. Minimum optimal viewing area for viewing signs.

Building Norms & Standards
SIGNAGE

VINYL GRAPHICS - TYPE A (Application)

PAUSE AREA

STEP 1: Remove existing digital print on clear cover.
STEP 2: Apply a new high performance vinyl material.
STEP 3: Insert cover into the vinyl cut.

FONT: HUMANIST 521 BT Bold or VERDANA Bold

Building Norms & Standards
SIGNAGE

VINYL GRAPHICS - TYPE B (Application)

PAUSE AREA

STEP 1: Remove existing digital print on clear non-reflective vinyl sign cover.
STEP 2: Apply a new high performance vinyl material.
STEP 3: Insert cover into the vinyl cut.

FONT: HUMANIST 521 BT Bold or VERDANA Bold

Building Norms & Standards
SIGNAGE

Internal Signage
Type: 05 - "SARS" Aluminium

Location: Typically in reception or lift lobby.
Description: 1000mm wide SARS brushed aluminium sign mounted on 2.4m (w) x full height Risk Autumn quality tiled wall.

1000mm 210mm

TECHNICAL DATA
FRAME: None.
MOUNTING: 25mm off tiled wall surface on non-rail mounting screws.
FACE: "SARS" sign with logo. 25mm laser cut brushed aluminium. Sign mounted 25mm off wall the surface on non-rail mounting screws.
ERGONOMICS: Type B - Sign to be mounted horizontally across tiled wall surface as indicated on Signage layout drawing.

Building Norms & Standards
SIGNAGE

Exterior Identification
Code: 28 - "Parking Disclaimer"

Location: As required.
Description: Disclaimer sign for Parking Areas.

V 400mm
275mm

DISCLAIMER
PARKING OF VEHICLES ON THESE PREMISES IS DONE ENTIRELY AT OWNERS OWN RISK AND SARS WILL NOT BE HELD RESPONSIBLE FOR ANY LOSS OR DAMAGE TO VEHICLES RESULTING FROM ANY CAUSE WHATSOEVER.

TECHNICAL DATA
FRAME: V400 clear brushed V400 x 275mm high (flat to wall), with V400 aluminium and caps to match.
COLOURS: Black text on white substrate with Pantone 2955C blue design.
FONT: Verdana Bold.
ERGONOMICS: 1500mm AFFL to US frame - wall mounted.

Building Norms & Standards

SARS FACILITIES MANAGEMENT

SIGNAGE

External Signage

Type: 31 - "PARKING"

Last Revised: 09-10-2013

Location: On wall adjoining parking ramp.

Description: VB5600 1500 tall x 600 wide SARS brushed aluminium sign and mounted on wall.

TECHNICAL DATA

Frame: VISTA Wall Bracket Double Sided VB5600x1500 with WB6L1 with anodised aluminium end caps to match.

Face: Enamel facing side All graphics from 7 year high performance vinyl ONLY. Client to approve machine.

Back: Manufacturer to insert plain insert to clean back face. Must be 100% rust proof and UV proof.

Fixing: Must be existing steel wall. Top of sign 1200mm from top of bracket wall level. Sign fixed to wall by manufacturer's system. Do not fix too close to edge!

Building Norms & Standards

SARS FACILITIES MANAGEMENT

SIGNAGE

Exterior Identification

Code: 30 - "Practitioner Appointments"

Last Revised: 28-03-2013

Location: External/Internal

Description: Standard SARS curved face sign.

TECHNICAL DATA

Frame: New galvanneal VISA V400 x 200mm high (not to scale), with three aluminium end caps to match.

Colours: Reverse 200% lacquer on white substrate, finished 100% or metallic.

Fixing: Reverse - Type A

Finish: Reverse - Type A

End Cap: Reverse - Type A

Building Norms & Standards

SARS FACILITIES MANAGEMENT

SIGNAGE

Exterior Identification

Code: 28 - "Parking Disclaimer"

Last Revised: 18-07-2012

Location: As required

Description: Disclaimer sign for Parking Areas.

TECHNICAL DATA

Frame: New galvanneal VISA V400 x 200mm high (not to scale), with three aluminium end caps to match.

Colours: Reverse 200% lacquer on white substrate, finished 100% or metallic.

Fixing: Reverse - Type A

Finish: Reverse - Type A

End Cap: Reverse - Type A

Building Norms & Standards

SARS FACILITIES MANAGEMENT

SIGNAGE

External Signage

Code: 20 - Smoking Area

Last Revised: 22-09-2012

Location: At designated smoking areas.

Description: Standard SARS curved face smoking sign.

TECHNICAL DATA

Frame: New galvanneal VISA V400 x 200mm high (not to scale), with three aluminium end caps to match.

Colours: Reverse 200% lacquer on white substrate, finished 100% or metallic.

Fixing: Reverse - Type A

Finish: Reverse - Type A

End Cap: Reverse - Type A

Building Norms & Standards

SARS FACILITIES MANAGEMENT

SIGNAGE

External Signage

Code: 19 "Customs Service Hours"

Last Revised: 25-10-2011

Location: As required

Description: Standard SARS curved face restricted access sign located as per floor plan.

TECHNICAL DATA

Frame: New galvanneal VISA V400 x 200mm high (not to scale), with three aluminium end caps to match.

Colours: Reverse 200% lacquer on white substrate, finished 100% or metallic.

Fixing: Reverse - Type A

Finish: Reverse - Type A

End Cap: Reverse - Type A

Building Norms & Standards

SARS FACILITIES MANAGEMENT

SIGNAGE

Interior Identification

Code: 26 - "Restricted Access" - Flat

Last Revised: 14-10-2009

Location: Wall mounted at any location restricted access is required.

Description: Standard SARS curved face restricted access sign located as per floor plan.

TECHNICAL DATA

Frame: New galvanneal VISA V400 x 200mm high (not to scale), with three aluminium end caps to match.

Colours: Reverse 200% lacquer on white substrate, finished 100% or metallic.

Fixing: Reverse - Type A

Finish: Reverse - Type A

End Cap: Reverse - Type A

Building Norms & Standards

SARS FACILITIES MANAGEMENT

SIGNAGE

Interior Identification

Code: 28 - "Copyright Warning"

Last Revised: 14-02-2013

Location: Print Areas/Libraries.

Description: Standard SARS curved face copyright disclaimer sign.

TECHNICAL DATA

Frame: New galvanneal VISA V400 x 200mm high (not to scale), with three aluminium end caps to match.

Colours: Reverse 200% lacquer on white substrate, finished 100% or metallic.

Fixing: Reverse - Type A

Finish: Reverse - Type A

End Cap: Reverse - Type A

Building Norms & Standards

SARS FACILITIES MANAGEMENT

SIGNAGE

Interior Identification

Code: 31 - "Print Area" - Flat

Last Revised: 07-07-2014

Location: Wall mounted at entrance to Print Area.

Description: SARS curved face sign located as per signage plan.

TECHNICAL DATA

Frame: New galvanneal VISA V400 x 200mm high (not to scale), with three aluminium end caps to match.

Colours: Reverse 200% lacquer on white substrate, finished 100% or metallic.

Fixing: Reverse - Type A

Finish: Reverse - Type A

End Cap: Reverse - Type A

Building Norms & Standards

SARS
South African Revenue Service

Signage

External Signage
Code: 07h30 - 16h15
Friday
Right of admission reserved
Call Centre
0860 12 12 18 or 0800 00 SARS option (4)

Technical Data
FRAME: Agriplast "Tumbler" or equal 10" clear anodised V400 x 300mm high (not to scale), with vinyl aluminium end caps to match.
COLOURS: Black text on white substrate with blue stripes.
FONT: Helvetica Bold, Size of text to be used for each sign.
GRAPHIC: None.
ERGONOMICS: None.

Building Norms & Standards

SARS
FACILITIES MANAGEMENT

Signage

Internal Identification
Code: 61 - Navigation Signage

Technical Data
FRAME: Agriplast "Tumbler" or equal 10" clear anodised Vista V215 x 300mm (H) profile, with anodised aluminium end caps to match.
COLOURS: None.
FONT: Helvetica Bold, Size of text to be used for each sign.
GRAPHIC: None.
ERGONOMICS: None.

Building Norms & Standards

SARS
FACILITIES MANAGEMENT

Signage

Internal Signage
Type: 70 - "Restricted Access"

Technical Data
FRAME: New generation Vista V215 x 250mm (H) to suit, with vinyl aluminium end caps to match.
COLOURS: None.
FONT: Helvetica Bold, Size of text to be used for each sign.
GRAPHIC: None.
ERGONOMICS: None.

Building Norms & Standards

SARS
FACILITIES MANAGEMENT

Signage

Internal Signage
Type: 71 - "Restricted" Server/Patch

Technical Data
FRAME: Agriplast "Tumbler" or equal 10" clear anodised Vista V215 x 300mm (H) profile, with anodised aluminium end caps to match.
COLOURS: None.
FONT: Helvetica Bold, Size of text to be used for each sign.
GRAPHIC: None.
ERGONOMICS: None.

Building Norms & Standards

SARS
South African Revenue Service

Signage

External Signage
Code: 05-09-2018

Technical Data
FRAME: Agriplast "Tumbler" or equal 10" clear anodised Vista V400 x 300mm (H) profile, with vinyl aluminium end caps to match.
COLOURS: None.
FONT: Helvetica Bold, Size of text to be used for each sign.
GRAPHIC: None.
ERGONOMICS: None.

Building Norms & Standards

SARS
FACILITIES MANAGEMENT

Signage

Internal Identification
Code: 61 - Navigation Signage

Technical Data
FRAME: Agriplast "Tumbler" or equal 10" clear anodised Vista V215 x 300mm (H) profile, with vinyl aluminium end caps to match.
COLOURS: None.
FONT: Helvetica Bold, Size of text to be used for each sign.
GRAPHIC: None.
ERGONOMICS: None.

Building Norms & Standards

SARS
FACILITIES MANAGEMENT

Signage

Internal Signage
Type: 70 - "Restricted Access"

Technical Data
FRAME: No frame. 2mm clear glass, backing to entire aluminium sheet.
COLOURS: None.
FONT: Helvetica Bold, Size of text to be used for each sign.
GRAPHIC: None.
ERGONOMICS: None.

Building Norms & Standards

SARS
FACILITIES MANAGEMENT

Signage

Internal Signage
Type: 71 - "Restricted" Server/Patch

Technical Data
FRAME: Agriplast "Tumbler" or equal 10" clear anodised Vista V215 x 250mm (H) profile, with anodised aluminium end caps to match.
COLOURS: None.
FONT: Helvetica Bold, Size of text to be used for each sign.
GRAPHIC: None.
ERGONOMICS: None.

Building Norms & Standards

SARS
FACILITIES MANAGEMENT

Signage

Interior Identification
Code: 78 - "MIND THE STEP"

Technical Data
FRAME: Agriplast "Tumbler" or equal 10" clear anodised Vista V215 x 300mm (H) profile, with vinyl aluminium end caps to match.
COLOURS: None.
FONT: Helvetica Bold, Size of text to be used for each sign.
GRAPHIC: None.
ERGONOMICS: None.

Building Norms & Standards

SARS
FACILITIES MANAGEMENT

Signage

Interior Identification
Type: 137 - "ENTRANCE / EXIT"

Technical Data
FRAME: Agriplast "Tumbler" or equal 10" clear anodised Vista V215 x 300mm (H) profile, with vinyl aluminium end caps to match.
COLOURS: None.
FONT: Helvetica Bold, Size of text to be used for each sign.
GRAPHIC: None.
ERGONOMICS: None.

Building Norms & Standards

SARS
FACILITIES MANAGEMENT

Signage

Interior Identification
Code: 84 - "PARKING DISCLAIMER"

Technical Data
FRAME: Agriplast "Tumbler" or equal 10" clear anodised Vista V215 x 300mm (H) profile, with vinyl aluminium end caps to match.
COLOURS: None.
FONT: Helvetica Bold, Size of text to be used for each sign.
GRAPHIC: None.
ERGONOMICS: None.

Building Norms & Standards

SARS
FACILITIES MANAGEMENT

Signage

Interior Identification
Type: 153 - Counter Nav (Type 2)

Technical Data
FRAME: Agriplast "Tumbler" or equal 10" clear anodised Vista V215 x 300mm (H) profile, with vinyl aluminium end caps to match.
COLOURS: None.
FONT: Helvetica Bold, Size of text to be used for each sign.
GRAPHIC: None.
ERGONOMICS: None.