

NTCSA
 Various substation
 Production equipment
 Unique Identifier: N/A
 Date: Sept-25



Item No	Item Name	Description	Unit	Quantity	RATE	PRICE
#REF!	Insulated Pentagonal Telescoping Link stick 30ft (9m)	Telescopic operating sticks shall be manufactured in accordance with IEC 62193 or ASTM F1826 - 00 and shall comprise of telescopic sections that are locked in position by means of durable spring-loaded pins (Standard attached)	each	10	R	-
#REF!	Cordless Portable Drill combo set	108 pcs cordless drill set power tool torque of 60Nm 18V battery 3/8-inch keyless metal check 25+3 position clutch 2 speed setting	each	1	R	-
#REF!	Cordless impact wrench combo set	The impact wrench has a 3/4" male square drive and a 1750 Nm maximum torque. It has twelve speed/torque levels and an overload protection system. It also has a work light, and a robust die cast aluminium gear housing. The impact wrench is compatible with all 18V battery packs and chargers from the CAS brands	each	1	R	-
#REF!	Adjustable spoke Torque Wrench kit (digital)	Adjustable from 30 to 150-inch pounds and calibrated to + or -2% accuracy; Includes 5 drop forged heads to fit the most popular spoke nipples; Wrench kit comes with torque wrench, case, and heads (6.1mm, 6.3mm, 6.6mm, 6.8mm, 6.9mm).	each	1	R	-
#REF!	50meter Extension cord with reels	1.5MM X 50M Cable Reel Extension With 3 Sockets	each	1	R	-
#REF!	Hydraulic conductor cutter 45mm	Hydraulic cable cutter up to 045mm; Hydraulic cable cutter up to 045mm max (for armoured Cu/Alu cable); Cutting force: 12 T; Not suitable for cutting steel wired armoured cable	each	1	R	-
#REF!	Voltage detector TAG330 (400-765kV)	HVD • High Voltage Detector • HV live or dead • All-weather IP65: TAG330 (400-765kV)	each	1	R	-
#REF!	Insulated Pentagonal Telescoping Link stick 30ft (5m)	Telescopic operating sticks shall be manufactured in accordance with IEC 62193 or ASTM F1826 - 00 and shall comprise of telescopic sections that are locked in position by means of durable spring-loaded pins	each	10	R	-
#REF!	Oil sampling Kit		each	1	R	-
33	Socket Set 34-52	Chromium-Molybdenum Alloy Steel What's Included: Sockets: 10, 12, 15, 17, 19, 21, 22, 23, 24, 26, 27, 30, 32, 34, 36, 38, 41, 46, 48, 50, 52 MM 3/4" Ratchet 450 MM Sliding T-Bar 100 MM & 200 MM Extension Bar	each	1	R	-
#REF!	Gedore Ratchet and Socket set (8-30)	Ratchet and Socket set (1/2"-32 pcs)	each	1	R	-
#REF!	Safety harness-(Full Body Harness)		each	30	R	-
#REF!	High Voltage Testers 275 - 400kv	Auto-Ranging Voltage Indicator (ARVI), Full Range 600V - 500kV by Product Details General Style Auto-Ranging Voltage Indicator, ARVI Full Range (600V - 500kV) UPC 096359505846 Dimensions Weight 4.5 lb Electrical Ratings Withstand Voltage 600V - 500kV Logistics Standard Package 1 Full Range (600V to 500kV) Auto-Ranging Voltage Indicator for overhead and underground systems. Full range ARVI Full range ARVI	each	1	R	-
#REF!	6.3Metres Max load of 150kg		each	1	R	-
#REF!	Lengths of Shunt Earths (Jumper 40mm Yellow 2m with LV Clamp modified & Earth clamp retic)	Shunt earths to earth between earth wire insulator and the tower on transmission lines	each	12	R	-
#REF!	Chance Tool Bucket	C4170144 Style Tool Bucket Type Container UPC 096359021520 CHANCE LINEMAN TOOL	each	6	R	-
#REF!	Chance handline block orange HLB -100	Handline Block, Safety Orange, 1,000 lb rated working load CHANCE_PSC4033478	each	8	R	-
#REF!	Linkstick for shunt earths (Static ground)	Linkstick to apply shunt earths	each	6	R	-
#REF!	3 Ton chain Block	Lifting Capacity: 3 Ton, Lift Height: 1.5 Meters, Load Chain Diameter: 10mm, Lever Handle Length: 410mm, Nett Weight: 21 kg	each	4	R	-
#REF!	4 Pound hammers	KENNEDY 4Lb Club / Lump Hammer, Fibreglass Handle With Rubber Grip - KEN5255760K	each	4	R	-
#REF!	Earth Spikes	This Earth spike Earth Spike 1200mm x 10mm Class C Copper Rod comes complete with a nut and washer, making it ideal for a variety of electrical and grounding applications.	each	12	R	-
#REF!	Lengths of Working Earths- yellow 10m 3kA 16mm - INDUCTION with screw on applicator	Phase to cluster bar jumpers of 16 mm ² flexible copper with yellow translucent PVC sheathing with a Screw-on clamp (E-Clamp/01) one end & an Earth clamp (E-Clamp/05) on the other end.	each	24	R	-
#REF!	Lengths of Working Earths- yellow 8m 3kA 16mm - INDUCTION with screw on applicator	Phase to cluster bar jumpers of 16 mm ² flexible copper with yellow translucent PVC sheathing with a Screw-on clamp (E-Clamp/01) one end & an Earth clamp (E-Clamp/05) on the other end.	each	24	R	-
#REF!	Lengths of Earths G42291SJ Aluminium Bodies with Serrated Jaws (Jumper 40 Yellow 8kA 10m 95/15)	Lengths of Earths G42291SJ Aluminium Bodies with Serrated Jaws (Jumper 40 Yellow 8kA 10m 95/15)	each	24	R	-
#REF!	Self Retracting lifeline 3 m (SWR Fall Arrestor 6m)	C4033375 EU RoHS Indicator No Style Auto-Ranging Voltage Indicator, ARVI (69kV - 500kV) UPC 096359368144 CHANCE	each	7	R	-
77	Safety harness-(Full Body Harness)	SMALL SAP No 0212826 MEDIUM SAP No 0212828 LARGE SAP No 0212829 XLARGE SAP No 021283 Idube	each	30	R	-
78	Rescue Kit Complete	30 m x 11 mm static rope, 1.5 m Anchor strap (SANS 50795), Red hold-all bag, Knife, Descending Device (EN341), 1 x Stainless steel carabiner	each	10	R	-
79	Military Straps (Strap - 3.2ton - 50mm x 9m tie down strap c/w 50mm ratchet and tail - white in colour.	Designed for securing heavy loads up to 2500kg, ensuring safe transport, Measures 50mm in width and 9.0m in length, suitable for various large items	each	30	R	-
80	Portable Grinder Battery Operated (Quoted for only 2)	Dewalt 18Xr Cordless Angle Grinder Bare Tstak DCG412NT-XJ, This DEWALT 18V Angle Grinder is ideal for grinding and cutting	each	4	R	-
81	Cable Grippers		each	4	R	-
82	IZUMI Hydraulic Crimper Model EP Head (Crimper REC-6630)	Izumi EP-60S2 Remote 60 Tonne Hydraulic Crimp Head	each	1	R	-

83	All size dices for IZUMI Hydraulic Crimper Model EP (Crimper with Dies)	IZUMI Hexagonal 12 Ton UL Dies UL type dies for EP-410, EP-510C, REC-5410, REC-5431, REC-5510. K type dies for Copper from 10 - 400 mm squared. Sold per set of 12 Dies	each	1	R	-
84	Battery Operated Industrial Portable Impact Range brushless	Makita 18 V Cordless Impact Driver Drill DHP458ZK (EXCLUDES BATTERY) , RDRIL001	each	4	R	-
85	Impact Range socket sets	11pcs Carbon Steel Impact Wrench Socket Set for Auto	each	4	R	-
86	Hydraulic Conductor Cutter (Hand Hydraulic Cutter; quoted for only 1)	3 kg Hydraulic Acsr Conductor Cutter, For Industrial, 1/2 inch,	each	2	R	-
87	Polypropylene Rope 100m drum	14mm White Polypropylene Rope x 100m Coil	each	1	R	-
88	Plastic Drum 40L	https://www.indiamart.com/proddetail/40l-full-open-top-drum-21773236691.html	each	4	R	-
89	63 Piece Toolbox life time guarantee (63 piece Mech Toolbox)	TOOLBOX KIT GEDORE 1282-FM-MA-1B-D19Z	each	8	R	-
90	Binding Strapping Machine	Hand used tool to bind cable around the epole using buckles	each	8	R	-
91	Aluminum Bracket	Bracket use to change insulators on a strainer tower and check South East Chrome in Witbank	each	2	R	-
92	Steel Bracket		each	4	R	-
93	1.5 Ton Chain Block	1.5 ton Lever Hoist Capacity 3300lbs 5ft Lift	each	4	R	-
94	2 Ton Webbing Sling	• Durable endless round sling ideal for secure lifting and rigging applications, Constructed from high-strength polyester webbing •	each	10	R	-
95	3 Ton Webbing Sling	• Durable endless round sling ideal for secure lifting and rigging applications, Constructed from high-strength polyester webbing •	each	10	R	-
96	6 Ton Webbing Sling	• Durable endless round sling ideal for secure lifting and rigging applications, Constructed from high-strength polyester webbing •	each	2	R	-
97	610 x 140 x 25mm Aluminium Clamp	Bracket use to change insulators on a strainer tower and check South East Chrome in Witbank	each	2	R	-
98	745 x 200 x 25mm Aluminium Clamp	Bracket use to change insulators on a strainer tower and check South East Chrome in Witbank	each	2	R	-
99	625 x 175 x 25mm Aluminium Clamp	Bracket use to change insulators on a strainer tower and check South East Chrome in Witbank	each	2	R	-
100	820 x 180 x 25mm Aluminium Clamp	Bracket use to change insulators on a strainer tower and check South East Chrome in Witbank	each	2	R	-
101	Toolbox	TOOL BOX: TYPE: ELECTRONIC, TECHNICIANS; DIMENSIONS: 340 X 445 X 145 MM; MATERIAL: ALUMINIUM; COMPLETE WITH THE FOLLOWING ITEMS: MIRROR, SWIVEL PLASTIC X 1, S/DRIVER, NEON 100-500 VOLT, 3 X 40 MM, BLADE X 1, S/DRIVER, JEWELLER 4 FLAT PH0 IN HANDLE X 1, HOLDER, SCREW 4 X 200 MM X 1, MAGNETIC PICKUP, TELESCOPIC AND PEN 630 MM X 1, TWEEZER, UNIVERSAL 1 MM TIP 115 MM X 1, TWEEZER, UNIVERSAL BENT 1.5 MM, TIP 150 MM X 1, TAPE MEASURE 3 M, 12 FT MET./IMP. X 1, PLIER, WATER PUMP 7 INCH 175 MM X 1, CUTTER, SIDE HEAVY DUTY, REDLINE 140 MM X 1, CUTTER, SIDE BOX JOINT SENSO PLUS 115 MM X 1, PLIER, SNIPE SERRATED JAW S/PLUS 150 MM X 1, PLIER, COMBINATION 160 MM X 1, NUT DRIVER 5.0 MM X 1, NUT DRIVER 8.0 MM X 1, NUT DRIVER 10.0 MM X 1, SHIFTER, PHOSPHATE FINISH 150 MM X 1, S/DRIVER, ENGINEERS 5 X 75 MM X 1, S/DRIVER, ENGINEERS 7 X 125 MM X 1, S/DRIVER, PHILIPS 0 X 65 MM X 1, S/DRIVER, PHILIPS 1 X 75 MM X 1, S/DRIVER, PHILIPS 2 X 100 MM X 1, S/DRIVER, POZI 1 X 80 MM X 1, S/DRIVER, STUBBY SLOT 1/4 INCH 6.5 X 25 MM X 1, S/DRIVER, STUBBY PHILIPS 1 X 25 MM X 1, S/DRIVER, ELECTRICIAN 3.0 X 75 MM X 1, S/DRIVER, ELECTRICIAN 5.0 X 150 MM X 1, KNIFE, TRIMMING RETRACTABLE 160 MM X 1, S/D SOLDER DISPENSER + 2.5M SOLDER X 1, SCREW STARTER, TORX, POZI, PHILIPS SCREWS X 1, BATTERY, PENLIGHT X 2, BRUSH 25 MM EVERYMAN X 1, HAMMER, 100G BALL PEIN LASHER X 1, TORCH PENLIGHT ALUMINIUM 2 AA CELL X 1, SPONGE FOR MAGNUM SOLDER STATIONS X 1, SOLDERING IRON 50W 220V, TEMP CONTROL X 1, DESOLDER TOOL MINI SILVER #38450040 X 1, SCISSOR 150 MM STRAIGHT, SHARP/SHARP X 1, NEEDLE HOLDER, 150 MM, SERRATED JAWS 1, ALL PURPOSE WATER REPELLING PENETRATING X 1, NICK NACKS PARTS TUBE X 1, FILE FLAT 150 MM SECOND CUT X 1, WIRE STRIPPER AND CUTTER X 1, STANDARD TRAYS AND FOAMS FOR ABOVE MENTIONED TOOLS TO BE INCLUDED WITH TOOLBOX	each	1	R	-
102	Fall arrest systems	Work in Substation (Transformers, Powerline carriers)	each	21	R	-
103	Rescue Kit Complete	Work in Substation (Transformers, Powerline carriers)	each	5	R	-
TOTAL AMOUNT					R	-